



Part 3 — API Testing (Postman)

Author: Rozagul Nodirbekova · Date: 2026-08-10

Files

File	Purpose
Enatega-Auth-Login.postman_collection.json	The collection — import into Postman or run with Newman
Enatega-Auth.postman_environment.json	Environment: base_url , graphql_host , auth_token
results/newman-live-report.html	Rich HTML run report (open in a browser)
results/newman-live-bonus.json	Machine-readable Newman report
screenshots/postman-live-run.png	Screenshot of the passing live run
../docs/pdf/api-postman-run-report.pdf	PDF of the run report

Endpoint under test (per assignment)

```
POST {{base_url}}/api/v1/auth/login
Content-Type: application/json

{ "phone_number": "+998901234567", "otp_code": "123456" }
```

{{base_url}} is an **environment variable** so the collection runs against any conforming server, a Postman **mock server**, or a local backend — nothing is hard-coded.

What API testing means here (what to actually check)

For each request a good API test asserts **more than status code**: - **HTTP status** (200 / 400 / 401 / 404 / 422) - **Body & schema** (token present & is a string; error object shape) - **Error message** (regex, case-insensitive → resilient to wording changes) - **Response time** (SLA, e.g. < 2 s) - **Side effects** (positive test chains the token into {{auth_token}} for reuse)

Test matrix

Folder 1 — Spec contract `POST /api/v1/auth/login`

#	Case	Body	Expected	Key assertions
1	✓ Positive	valid phone + valid OTP	200	JSON, non-empty token (saved), schema, < 2 s
2	✗ Invalid OTP	otp 000000	401	no token, error /otp\ invalid/
3	✗ Missing phone	{otp_code} only	400	error names phone , no token
4	✗ Bad phone format	phone 12345	400/422	error /format\ valid/
5	✗ Empty body	{}	400	no token

#	Case	Body	Expected	Key assertions
6	🚫 Wrong Content-Type	text/plain	415/400	no 5xx (server doesn't crash)

Folder 2 — Live backend (real Enatega GraphQL, executed)

#	Case	Result (captured live)	Assertions
7	✅ Health { __typename }	200 {"data": {"__typename": "Query"}}	status, __typename==Query , < 3 s
8	REST route on real backend	404	route absent (Finding B3)
9	GraphQL login, bad var type	400 GRAPHQL_VALIDATION_FAILED	validation code (Finding B2)
10	GraphQL login, wrong password	200 , data:null + errors[]	no token
11	Protected query, no token	200 , Unauthorized: token missing	error message

Live result: 5 requests · 10 assertions · 0 failures. See the screenshot below.

Live run screenshot

Light ☒ Dark

Summary

Total Requests **5**

Failed Tests **0**

Skipped Tests **0**

Enatega API Tests — Live Run

Tuesday, 11 August 2026 13:05:02

TOTAL ITERATIONS

1

TOTAL ASSERTIONS

10

TOTAL FAILED TESTS

0

TOTAL SKIPPED TESTS

0

FILE INFORMATION

📁 **Collection:** Enatega — Auth / Login API Tests (QA)
📁 **Specified Folders:** 2. Live backend — real Enatega GraphQL
📁 **Environment:** Enatega — Auth (env)

COLLECTION DESCRIPTION

QA Automation assignment — Part 3 (API Testing).

What this collection does

- **Folder 1 — Spec contract:** tests the assignment's POST /api/v1/auth/login (phone_number + otp_code): 1 positive + 5 negative/robustness cases. Each request asserts **status code**, **body/schema**, **error message** and **response time**. {{base_url}} is an environment variable so it runs against any conforming server or a Postman mock.
- **Folder 2 — Live backend:** real requests against the actual Enatega backend (aws-server-v2.enatega.com, GraphQL). These EXECUTE live and assert on real responses (health, 404 on the REST route, auth negatives). This is what the app under test really uses.

How to run

Postman: import this + the environment, pick the env, hit **Run**. Newman: newman run Enatega-Auth-Login.postman_collection.json -e Enatega-Auth.postman_environment.json -r htmlextra

Author: Rozagul Nodirbekova — 2026-08-10

TIMINGS AND DATA

- 🕒 **Total run duration:** 3.5s
- 📄 **Total data received:** 690B
- 🕒 **Average response time:** 678ms

SUMMARY ITEM	TOTAL	FAILED
Requests	5	0
Prerequisite Scripts	0	0
Test Scripts	5	0
Assertions	10	0
Skipped Tests	0	-

Real request/response examples (captured live)

Positive health check

```
POST https://aws-server-v2.enatega.com/graphql
{ "query": "{ __typename }" }
→ 200 OK
{ "data": { "__typename": "Query" } }
```

Negative — protected query without a token

```
POST https://aws-server-v2.enatega.com/graphql
{ "query": "{ configuration { currency currencySymbol } }" }
→ 200 OK
{ "errors": [ { "message": "Unauthorized: token missing",
  "extensions": { "code": "INTERNAL_SERVER_ERROR" } } ], "data": null }
```

Negative — invalid GraphQL variable type

```
→ 400 Bad Request
{ "errors": [ { "message": "Variable \"$type\" of type \"String\" used in position expecting type \"
  \"extensions\": { \"code\": \"GRAPHQL_VALIDATION_FAILED\" } } ] }
```

How to run

Postman (UI): import both JSON files → select the *Enatega — Auth (env)* environment → open the collection → **Run**. Screenshot the green **Test Results** tab per request.

Newman (CLI) with the rich report:

```
npm install -g newman newman-reporter-htmlextra
newman run Enatega-Auth-Login.postman_collection.json \
  -e Enatega-Auth.postman_environment.json \
  -r cli,htmlextra --reporter-htmlextra-export results/newman-live-report.html
# run only the live folder that hits the real backend:
newman run ... --folder "2. Live backend — real Enatega GraphQL"
```

What to show the reviewer (screenshots checklist)

1. Collection Runner / htmlextra **summary** — total requests & assertions, 0 failed  (above).
2. The **positive** request: body + 200 + token, with the **Test Results** all green.
3. One **negative** request: the 4xx status **and** the asserted error message.
4. The **environment** panel showing `base_url` (proves no hard-coded host).