



Part 3 — API Testing (Postman)

Author: Rozagul Nodirbekova · Date: 2026-08-10

Files

File	Purpose
Enatega-Auth-Login.postman_collection.json	The collection (import into Postman / run with Newman)
Enatega-Auth.postman_environment.json	Environment with <code>base_url</code> , <code>graphql_host</code> , <code>auth_token</code>

Endpoint under test (per assignment)

```
POST {{base_url}}/api/v1/auth/login
Content-Type: application/json

{
  "phone_number": "+998901234567",
  "otp_code": "123456"
}
```

`base_url` is an **environment variable** so the same collection runs against any conforming server, a Postman **mock server**, or a local backend — no hard-coded hosts.

Test matrix

#	Case	Request	Expected status	Key assertions
1	✔ Positive	valid phone + valid OTP	200	JSON body; non-empty <code>token</code> (saved to env); response < 2 s
2	✖ Negative	invalid OTP (000000)	401	no <code>token</code> ; error message matches <code>/otp\ code\ invalid/</code>
3	✖ Negative	missing <code>phone_number</code>	400	error names the <code>phone</code> field; no <code>token</code>
4	✖ Negative	invalid phone format (12345)	400 or 422	error mentions format/validation; no <code>token</code>

Bonus — live tests against the real backend (`aws-server-v2.enatega.com`)

The customer app does **not** use a REST `/api/v1/auth/login` route — it authenticates over **GraphQL**. The collection documents and proves this with live requests:

#	Case	Result
5	REST spec route on real backend	404 (route does not exist) — documented finding
6	GraphQL login with wrong variable type	400 + GRAPHQL_VALIDATION_FAILED

#	Case	Result
7	GraphQL login with wrong password	200 transport, data:null + errors[] (no token)

These three were **executed live** while writing this suite; the responses shown in `results/` were captured from the real server.

How to run

In Postman (UI): 1. Import both JSON files (Collection + Environment). 2. Select the *Enatega — Auth (env)* environment (top-right). 3. Set `base_url` to your server (or a Postman mock) and click **Run** on the collection.

From the CLI with Newman:

```
npm install -g newman
newman run Enatega-Auth-Login.postman_collection.json \
  -e Enatega-Auth.postman_environment.json \
  --reporters cli,json --reporter-json-export results/newman-report.json
```

Notes on quality

- Every request has **explicit assertions** (status + body + error message), not just a “send”.
- The positive test **chains** the returned token into `{{auth_token}}` for downstream requests.
- Tests are **resilient**: negative tests assert the *absence* of a token, and messages are matched with case-insensitive regex so minor wording changes don’t cause false failures.