

Custom Statistics in dfSummary

This document shows how to customize the content of the *Stats / Values* column in `summarytools::dfSummary()`. This feature was introduced in version 1.0.0, July 2021.

This feature request came up several times in a form or another, mostly on GitHub.

How it works

Two new options were created: `dfSummary.custom.1` and `dfSummary.custom.2`. The first one has a predefined value – it is the one that makes up the fourth row of the cell (showing IQR and CV). The second one is set to NA by default. If both options are defined (non-NA), the cell will now span on 5 lines rather than 4, provided there are no additional line breaks occurring.

Baseline


We'll use the first column of *iris* for this demo. So let's see the results as they are before making any changes.

First let's set things up:

```
library(knitr)
opts_chunk$set(comment = NA,
                prompt = FALSE,
                cache = FALSE,
                echo = TRUE,
                results = 'asis')
suppressPackageStartupMessages(library(summarytools))
st_options(plain.ascii = FALSE,
           headings = FALSE,
           footnote = NA,
           round.digits = 1,
           dfSummary.varnumbers = FALSE,
           dfSummary.valid.col = FALSE,
           dfSummary.silent = TRUE,
           dfSummary.style = "grid",
           tmp.img.dir = "img")
```

And then show the baseline:


```
iris_subset <- iris[1]
dfSummary(iris_subset, graph.magnif = .45)
```

Variable	Stats / Values	Freqs (% of Valid)	Graph	Missing
Sepal.Length [numeric]	Mean (sd) : 5.8 (0.8) min < med < max: 4.3 < 5.8 < 7.9 IQR (CV) : 1.3 (0.1)	35 distinct values		0 (0.0%)

Example 1 - Removing the IQR (CV) line

Setting the first option to NA will do just that:


```
st_options(dfSummary.custom.1 = NA)
dfSummary(iris_subset, graph.magnif = .35)
```

Variable	Stats / Values	Freqs (% of Valid)	Graph	Missing
Sepal.Length [numeric]	Mean (sd) : 5.8 (0.8) min < med < max: 4.3 < 5.8 < 7.9	35 distinct values		0 (0.0%)

Example 2 : Adding Q1 & Q3

Here we're going to create the expression that is needed to generate the statistics we want; since this bit of is going to be interpreted while looping on column data, there are some variables that are available to us. The most important is, well, `column_data`. Another one that you might want to use is `round.digits`; we have set it to 1 in the initial chunk.


```
st_options(
  dfSummary.custom.1 =
    expression(
      paste(
        "Q1 - Q3 :",
        round(
          quantile(column_data,
                    probs = .25,
                    type = 2,
                    names = FALSE,
                    na.rm = TRUE),
          digits = 1
        ), " - ",
        round(
          quantile(column_data,
                    probs = .75,
                    type = 2,
                    names = FALSE,
                    na.rm = TRUE),
          digits = 1
        )
      )
    )
)
dfSummary(iris_subset, graph.magnif = .45)
```

Variable	Stats / Values	Freqs (% of Valid)	Graph	Missing
Sepal.Length [numeric]	Mean (sd) : 5.8 (0.8) min < med < max: 4.3 < 5.8 < 7.9 Q1 - Q3 : 5.1 - 6.4	35 distinct values		0 (0.0%)

Example 3: Inserting back the IQR & CV

It is always possible to revert the first custom stat to its initial value by using `st_options(dfSummary.custom.1 = "default")`. But let's make things a bit more interesting by actually showing these under the Q1 & Q3 line that we have just defined.

```
st_options(  
  dfSummary.custom.2 =  
    expression(  
      paste(  
        paste0(  
          trs("iqr"), " (", trs("cv"), ") : "  
        ),  
        format_number(  
          IQR(column_data, na.rm = TRUE),  
          round.digits  
        ),  
        " ("  
        format_number(  
          sd(column_data, na.rm = TRUE) /  
            mean(column_data, na.rm = TRUE),  
          round.digits  
        ),  
        ")",  
        collapse = "",  
        sep = ""  
      )  
    )  
  )  
dfSummary(iris_subset, graph.magnif = .65)
```

Variable	Stats / Values	Freqs (% of Valid)	Graph	Missing
Sepal.Length [numeric]	Mean (sd) : 5.8 (0.8) min < med < max: 4.3 < 5.8 < 7.9 Q1 - Q3 : 5.1 - 6.4 IQR (CV) : 1.3 (0.1)	35 distinct values		0 (0.0%)

Don't forget to set `na.rm = TRUE` whenever necessary. Otherwise, just use your imagination!