

Document Object Model (DOM) Made Easy

- **DOM** stands for Document Object Model
- Browsers while browsing a HTML page will build an internal model of the HTML page called the Document Object Model
- D stands for Document → In case of HTML page, the entire page will be treated as a document
- O stands for Object → Each and every element tag in the HTML page will be treated as an object
- M stands for Model → A tree of objects will be constructed as a Model
[Click Here](#) to View Tree DOM model for Example Web
 Page: http://compendiumdev.co.uk/selenium/basic_web_page.html
- Using DOM, JavaScript can access the elements on a HTML page and modify them.
 Example: Change the colors of the text by selecting the button - [View Code Here](#) By the end of the session, you will learn how to do this
- We can execute the below DOM examples (Absolute Way) either in Browser Console or using JavaScript:
 - document - Locates the entire HTML pagedocument.children[0] - Locates the whole HTML codedocument.documentElement - Locates the whole HTML codedocument.documentElement.children - Locates two children head and bodydocument.documentElement.children[0] - Locates the head sectiondocument.documentElement.children[1] - Locates the body section document.documentElement.children[0].children[0] - Locates the title tag elementdocument.documentElement.children[1].children[0] - Locates the first paragraph tagdocument.documentElement.children[1].children[1] - Locates the second paragraph tagdocument.documentElement.children[0].children[0].innerHTML - Locates the content of title elementdocument.documentElement.children[0].children[1].id - Locates the value of the id attribute of p tag
- DOM Methods
 - document.write() - Writes onto the HTML pagedocument.write("Arun Motoori")document.write("<h1> Arun Motoori </h1>")document.write("My name is Arun Motoori ")document.getElementById() - Finds the HTML element by its iddocument.getElementById("para1")document.getElementById("para2")document.getElementsByName()[index] - Finds the HTML element by its namedocument.getElementsByName("q")[0]document.getElementsByName("samename")[0]document.getElementsByName("samename")[1]document.getElementsByName("samename")[2]document.getElementsByClassName()[index] - Finds the HTML element by its class namedocument.getElementsByClassName("hidden-xs hidden-sm hidden-md")document.getElementsByClassName("hidden-xs hidden-sm hidden-md")[0]document.getElementsByClassName("hidden-xs hidden-sm hidden-md ")[1]document.getElementsByClassName("hidden-xs hidden-sm hidden-md ")[2]document.getElementsByTagName()[index] - Finds the HTML element by its Tag

namedocument.getElementsByTagName("a")document.getElementsByTagName("a")
[0]document.getElementsByTagName("a")[1]document.getElementsByTagName("a")[2]

- DOM Properties

innerHTML

property document.getElementById("para1").innerHTML document.getElementById("para1").innerH
TML="My name is Arun Motoori";attribute name property -

document.getElementById("para1").iddocument.title - Gets the Title of the

pagedocument.titledocument.URL- Gets the URL of the pagedocument.URLdocument.style -
Changes the style of the

elementsdocument.getElementById("para1").style.color="red"document.getElementById("para2").st
yle.background="orange"document.links - Gets the links on the

pagedocument.linksdocument.links[0]document.links[1]document.forms - Finds all the forms on
the

pagedocument.formsdocument.nameattributeofformdocument.form1document.form1.getElementsB
yTagName('input')[0]DOM with

Tablesdocument.getElementById('table1').getElementsByTagName('tr')

[2].getElementsByTagName('td')[2]And many others

- The following examples will demonstrate how the JavaScript uses JavaScript Expressions for
locating the HTML elements which are represented as DOM objects:

document.write - [Refer file for Demonstration](#)Demonstrate how DOM can change the elements
dynamically and we are going to use DOM for locating elements - [Refer file for Demonstration](#)

By,

Arun Motoori