

# newBNN

July 18, 2025

```
[17]: # In[1]:
import torch
import torch.nn as nn
import torchvision
import torchvision.transforms as transforms
from torch.utils.data import DataLoader, random_split
from torch.optim.lr_scheduler import ReduceLROnPlateau
from torch.cuda.amp import GradScaler, autocast
from tqdm.notebook import tqdm # Use tqdm.notebook for notebooks
import os
import copy
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.metrics import confusion_matrix
import numpy as np
```

```
[ ]: # In[2]:
class Config:
    # --- Dataset & Hardware ---
    # DATA_DIR = 'path/to/your/soyabean_uav_dataset' # <--- CHANGE THIS
    DATA_DIR = '/home/dragoon/Downloads/dataset' # <--- CHANGE THIS
    # DATA_DIR = '/home/dragoon/Downloads/testset' # <--- CHANGE THIS
    NUM_WORKERS = 4

    # --- Model Architecture ---
    IMG_SIZE = 128
    HIDDEN_LAYERS_CONFIG = [32, 64, 128, 256]
    HIDDEN_SIZE_CLASSIFIER = 512

    # --- Training Hyperparameters ---
    NUM_EPOCHS = 100
    BATCH_SIZE = 16
    LEARNING_RATE = 1e-3

    # --- Early Stopping ---
    EARLY_STOP_PATIENCE = 7
    MIN_LR_TO_START_EARLY_STOPPING = 1e-5
```

```
device = torch.device('cuda' if torch.cuda.is_available() else 'cpu')
print(f"Using device: {device}")
```

Using device: cuda

```
[19]: # In[3]:
train_transform = transforms.Compose([
    transforms.Resize((Config.IMG_SIZE, Config.IMG_SIZE)),
    transforms.RandomHorizontalFlip(),
    transforms.RandomRotation(10),
    transforms.ToTensor(),
    transforms.Normalize(mean=[0.5, 0.5, 0.5], std=[0.5, 0.5, 0.5])
])
val_transform = transforms.Compose([
    transforms.Resize((Config.IMG_SIZE, Config.IMG_SIZE)),
    transforms.ToTensor(),
    transforms.Normalize(mean=[0.5, 0.5, 0.5], std=[0.5, 0.5, 0.5])
])

try:
    full_dataset = torchvision.datasets.ImageFolder(root=Config.DATA_DIR,
    ↪transform=train_transform)
    class_names = full_dataset.classes
    NUM_CLASSES = len(class_names)
    print(f"Successfully detected {NUM_CLASSES} classes: {class_names}")

    train_size = int(0.8 * len(full_dataset))
    val_size = len(full_dataset) - train_size
    train_dataset, val_dataset = random_split(full_dataset, [train_size,
    ↪val_size])

    val_dataset.dataset.transform = val_transform

    train_loader = DataLoader(train_dataset, batch_size=Config.BATCH_SIZE,
    ↪shuffle=True, num_workers=Config.NUM_WORKERS, pin_memory=True)
    val_loader = DataLoader(val_dataset, batch_size=Config.BATCH_SIZE,
    ↪shuffle=False, num_workers=Config.NUM_WORKERS, pin_memory=True)
except FileNotFoundError:
    print(f"ERROR: Dataset not found at '{Config.DATA_DIR}'. Please check the
    ↪path.")
```

Successfully detected 2 classes: ['healthy', 'rust']

## 1 In[4]:

```
def show_transformed_images(data_loader, class_names, num_images=3): # Un-normalize and
display an image
def imshow(inp, title=None): inp = inp.numpy().transpose((1, 2, 0)) mean =
np.array([0.5, 0.5, 0.5]) std = np.array([0.5, 0.5, 0.5]) inp = std * inp + mean
inp = np.clip(inp, 0,
```

```

1) plt.imshow(inp) if title is not None: plt.title(title) plt.pause(0.001)

# Get a batch of training data
inputs, classes = next(iter(data_loader))

# Make a grid from the batch and show
out = torchvision.utils.make_grid(inputs[:num_images*len(class_names)])

fig, ax = plt.subplots(figsize=(15, 8))
imshow(out, title=[class_names[x] for x in classes[:num_images*len(class_names)]])

print("Displaying a sample of transformed images...") show_transformed_images(train_loader,
class_names)

```

```

[20]: # In[4]:
def show_transformed_images(data_loader, class_names, num_images=3):
    # Un-normalize and display an image
    def imshow(inp, title=None):
        inp = inp.numpy().transpose((1, 2, 0))
        mean = np.array([0.5, 0.5, 0.5])
        std = np.array([0.5, 0.5, 0.5])
        inp = std * inp + mean
        inp = np.clip(inp, 0, 1)
        plt.imshow(inp)
        if title is not None:
            plt.title(title)
        plt.pause(0.001)

    # Get a batch of training data
    inputs, classes = next(iter(data_loader))


    # Make a grid from the batch and show
    out = torchvision.utils.make_grid(inputs[:num_images*len(class_names)])

    fig, ax = plt.subplots(figsize=(15, 8))
    imshow(out, title=[class_names[x] for x in classes[:
↪num_images*len(class_names)]])

    print("Displaying a sample of transformed images...")
    show_transformed_images(train_loader, class_names)

```

Displaying a sample of transformed images...



```
[21]: # In[5]:
class Binarize(torch.autograd.Function):
    @staticmethod
    def forward(ctx, i): return i.sign()
    @staticmethod
    def backward(ctx, grad_output): return grad_output

class BinaryConv2d(nn.Module):
    def __init__(self, in_channels, out_channels, kernel_size, stride=1,
padding=0):
        super().__init__()
        self.conv = nn.Conv2d(in_channels, out_channels, kernel_size, stride,
padding, bias=False)
        self.bn = nn.BatchNorm2d(out_channels)
    def forward(self, x):
        self.conv.weight.data = Binarize.apply(self.conv.weight.data)
        return Binarize.apply(self.bn(self.conv(x)))

class BinaryLinear(nn.Module):
    def __init__(self, in_features, out_features):
        super().__init__()
        self.linear = nn.Linear(in_features, out_features, bias=False)
        self.bn = nn.BatchNorm1d(out_features)
    def forward(self, x):
        self.linear.weight.data = Binarize.apply(self.linear.weight.data)
        return Binarize.apply(self.bn(self.linear(x)))

class BNN(nn.Module):
    def __init__(self, config, num_classes):
        super(BNN, self).__init__()
        layers = []
        in_channels = 3
        for out_channels in config.HIDDEN_LAYERS_CONFIG:
            layers.append(BinaryConv2d(in_channels, out_channels,
kernel_size=3, padding=1))
            layers.append(nn.MaxPool2d(2))
            in_channels = out_channels
```

```

        self.features = nn.Sequential(*layers)
        num_pools = len(config.HIDDEN_LAYERS_CONFIG)
        final_img_size = config.IMG_SIZE // (2**num_pools)
        flat_size = config.HIDDEN_LAYERS_CONFIG[-1] * final_img_size *
↪final_img_size
        self.classifier = nn.Sequential(
            BinaryLinear(flat_size, config.HIDDEN_SIZE_CLASSIFIER),
            nn.Linear(config.HIDDEN_SIZE_CLASSIFIER, num_classes)
        )
    def forward(self, x):
        x = self.features(x)
        x = x.view(x.size(0), -1)
        x = self.classifier(x)
        return x

```

```

[ ]: def train_model(model, train_loader, val_loader, config, model_name):
    print(f"\n--- Training {model_name} ---")
    model.to(device)
    criterion = nn.CrossEntropyLoss()
    optimizer = torch.optim.Adam(model.parameters(), lr=config.LEARNING_RATE)
    scheduler = ReduceLROnPlateau(optimizer, 'max', factor=0.2, patience=3)
    scaler = GradScaler()

    best_acc = 0.0
    patience_counter = 0
    history = {'train_loss': [], 'val_loss': [], 'val_acc': []}

    for epoch in range(config.NUM_EPOCHS):
        model.train()
        epoch_train_loss = 0.0
        loop = tqdm(train_loader, desc=f"Epoch {epoch+1}/{config.NUM_EPOCHS}",
↪leave=False)
        for images, labels in loop:
            images, labels = images.to(device), labels.to(device)
            optimizer.zero_grad()
            with autocast():
                outputs = model(images)
                loss = criterion(outputs, labels)
            scaler.scale(loss).backward()
            scaler.step(optimizer)
            scaler.update()
            epoch_train_loss += loss.item()
            loop.set_postfix(loss=loss.item())

    val_loss, val_acc = evaluate_model(model, val_loader, criterion)
    history['train_loss'].append(epoch_train_loss / len(train_loader))
    history['val_loss'].append(val_loss)

```

```

        history['val_acc'].append(val_acc)

        current_lr = optimizer.param_groups[0]['lr']
        print(f"Epoch {epoch+1}/{config.NUM_EPOCHS} -> Val Loss: {val_loss:.4f} |
↳| Val Acc: {val_acc:.2f}% | LR: {current_lr:.1e}")

        scheduler.step(val_acc)

        if val_acc > best_acc:
            best_acc, patience_counter = val_acc, 0
            torch.save(model.state_dict(), f"{model_name}_best.pt")
            print(f" -> New best model saved with accuracy: {best_acc:.2f}%")
        else:
            if current_lr < config.MIN_LR_TO_START_EARLY_STOPPING:
                patience_counter += 1
                print(f" -> No improvement. Patience: {patience_counter}/
↳{config.EARLY_STOP_PATIENCE}")
            if patience_counter >= config.EARLY_STOP_PATIENCE:
                print("\n*** Early stopping triggered ***")
                break

        print(f"Finished training. Best Val Acc: {best_acc:.2f}%")
        model.load_state_dict(torch.load(f"{model_name}_best.pt"))
        return model, history

def evaluate_model(model, data_loader, criterion):
    model.eval()
    model.to(device)
    correct, total, running_loss = 0, 0, 0.0
    with torch.no_grad():
        for images, labels in data_loader:
            images, labels = images.to(device), labels.to(device)
            with autocast():
                outputs = model(images)
                loss = criterion(outputs, labels)
                _, predicted = torch.max(outputs.data, 1)
                total += labels.size(0)
                correct += (predicted == labels).sum().item()
                running_loss += loss.item() * images.size(0)
    accuracy = 100 * correct / total
    avg_loss = running_loss / len(data_loader.dataset)
    return avg_loss, accuracy

```

```

[23]: # In[7]:
def plot_curves(history, model_name):
    fig, (ax1, ax2) = plt.subplots(1, 2, figsize=(18, 6))
    ax1.plot(history['train_loss'], label='Training Loss')

```

```

ax1.plot(history['val_loss'], label='Validation Loss')
ax1.set_title(f'{model_name} - Loss Curves')
ax1.set_xlabel('Epochs'); ax1.set_ylabel('Loss'); ax1.legend()
ax2.plot(history['val_acc'], label='Validation Accuracy', color='green')
ax2.set_title(f'{model_name} - Accuracy Curve')
ax2.set_xlabel('Epochs'); ax2.set_ylabel('Accuracy (%)'); ax2.legend()
plt.tight_layout()
plt.savefig(f'{model_name}_performance_curves.png')
print(f"Performance curves saved to {model_name}_performance_curves.png")
plt.show()

def plot_confusion_matrix(model, data_loader, class_names, model_name):
    model.eval(); model.to(device)
    all_preds, all_labels = [], []
    with torch.no_grad():
        for images, labels in data_loader:
            images, labels = images.to(device), labels.to(device)
            with autocast():
                outputs = model(images)
            _, preds = torch.max(outputs, 1)
            all_preds.extend(preds.cpu().numpy())
            all_labels.extend(labels.cpu().numpy())

    cm = confusion_matrix(all_labels, all_preds)
    plt.figure(figsize=(10, 8))
    sns.heatmap(cm, annot=True, fmt='d', cmap='Blues', xticklabels=class_names,
    ↪yticklabels=class_names)
    plt.title(f'{model_name} - Confusion Matrix')
    plt.xlabel('Predicted Label'); plt.ylabel('True Label')
    plt.savefig(f'{model_name}_confusion_matrix.png')
    print(f"Confusion matrix saved to {model_name}_confusion_matrix.png")
    plt.show()

def get_model_size_mb(model):
    torch.save(model.state_dict(), "temp.p")
    size_mb = os.path.getsize("temp.p") / 1e6
    os.remove("temp.p")
    return size_mb

```

```

[24]: # In[8]:
bnn_model = BNN(config=Config, num_classes=NUM_CLASSES)
trained_bnn, history = train_model(bnn_model, train_loader, val_loader, Config,
    ↪"BNN")

# --- Generate Plots ---
plot_curves(history, "BNN")
plot_confusion_matrix(trained_bnn, val_loader, class_names, "BNN")

```

```

print("\n\n--- FINAL BNN RESULTS ---")
print("="*25)
_, final_accuracy = evaluate_model(trained_bnn, val_loader, nn.
    ↪CrossEntropyLoss())
model_size = get_model_size_mb(trained_bnn)
print(f"BNN Final Validation Accuracy: {final_accuracy:.2f}%")
print(f"BNN Final Model Size: {model_size:.2f} MB")
print("="*25)

```

--- Training BNN ---

```

/tmp/ipykernel_30532/1491822498.py:7: FutureWarning:
`torch.cuda.amp.GradScaler(args...)` is deprecated. Please use
`torch.amp.GradScaler('cuda', args...)` instead.
    scaler = GradScaler()

Epoch 1/100:   0%|          | 0/1 [00:00<?, ?it/s]

/tmp/ipykernel_30532/1491822498.py:20: FutureWarning:
`torch.cuda.amp.autocast(args...)` is deprecated. Please use
`torch.amp.autocast('cuda', args...)` instead.
    with autocast():

Epoch 1/100 -> Val Loss: 1.0841 | Val Acc: 50.00% | LR: 1.0e-03
    -> New best model saved with accuracy: 50.00%

/tmp/ipykernel_30532/1491822498.py:62: FutureWarning:
`torch.cuda.amp.autocast(args...)` is deprecated. Please use
`torch.amp.autocast('cuda', args...)` instead.
    with autocast():

Epoch 2/100:   0%|          | 0/1 [00:00<?, ?it/s]
Epoch 2/100 -> Val Loss: 1.0414 | Val Acc: 25.00% | LR: 1.0e-03
Epoch 3/100:   0%|          | 0/1 [00:00<?, ?it/s]
Epoch 3/100 -> Val Loss: 1.4229 | Val Acc: 25.00% | LR: 1.0e-03
Epoch 4/100:   0%|          | 0/1 [00:00<?, ?it/s]
Epoch 4/100 -> Val Loss: 1.3480 | Val Acc: 25.00% | LR: 1.0e-03
Epoch 5/100:   0%|          | 0/1 [00:00<?, ?it/s]
Epoch 5/100 -> Val Loss: 1.4173 | Val Acc: 25.00% | LR: 1.0e-03
Epoch 6/100:   0%|          | 0/1 [00:00<?, ?it/s]
Epoch 6/100 -> Val Loss: 1.0248 | Val Acc: 25.00% | LR: 2.0e-04
Epoch 7/100:   0%|          | 0/1 [00:00<?, ?it/s]
Epoch 7/100 -> Val Loss: 1.2931 | Val Acc: 25.00% | LR: 2.0e-04

```




Epoch 8/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 8/100 -> Val Loss: 0.7436 | Val Acc: 25.00% | LR: 2.0e-04  
Epoch 9/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 9/100 -> Val Loss: 1.1090 | Val Acc: 25.00% | LR: 2.0e-04  
Epoch 10/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 10/100 -> Val Loss: 1.1974 | Val Acc: 0.00% | LR: 4.0e-05  
Epoch 11/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 11/100 -> Val Loss: 1.3507 | Val Acc: 25.00% | LR: 4.0e-05  
Epoch 12/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 12/100 -> Val Loss: 1.2188 | Val Acc: 0.00% | LR: 4.0e-05  
Epoch 13/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 13/100 -> Val Loss: 1.2761 | Val Acc: 0.00% | LR: 4.0e-05  
Epoch 14/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 14/100 -> Val Loss: 0.7963 | Val Acc: 75.00% | LR: 8.0e-06  
-> New best model saved with accuracy: 75.00%  
Epoch 15/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 15/100 -> Val Loss: 0.8963 | Val Acc: 25.00% | LR: 8.0e-06  
-> No improvement. Patience: 1/7  
Epoch 16/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 16/100 -> Val Loss: 1.2249 | Val Acc: 25.00% | LR: 8.0e-06  
-> No improvement. Patience: 2/7  
Epoch 17/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 17/100 -> Val Loss: 1.1971 | Val Acc: 0.00% | LR: 8.0e-06  
-> No improvement. Patience: 3/7  
Epoch 18/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 18/100 -> Val Loss: 0.9179 | Val Acc: 25.00% | LR: 8.0e-06  
-> No improvement. Patience: 4/7  
Epoch 19/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 19/100 -> Val Loss: 1.1306 | Val Acc: 0.00% | LR: 1.6e-06  
-> No improvement. Patience: 5/7  
Epoch 20/100: 0%| | 0/1 [00:00<?, ?it/s]  
Epoch 20/100 -> Val Loss: 1.1666 | Val Acc: 25.00% | LR: 1.6e-06  
-> No improvement. Patience: 6/7  
Epoch 21/100: 0%| | 0/1 [00:00<?, ?it/s]

Epoch 21/100 -> Val Loss: 1.1357 | Val Acc: 25.00% | LR: 1.6e-06  
-> No improvement. Patience: 7/7

\*\*\* Early stopping triggered \*\*\*


Finished training. Best Val Acc: 75.00%

Performance curves saved to BNN\_performance\_curves.png



Confusion matrix saved to BNN\_confusion\_matrix.png

```
/tmp/ipykernel_30532/4177737073.py:22: FutureWarning:  
`torch.cuda.amp.autocast(args...)` is deprecated. Please use  
`torch.amp.autocast('cuda', args...)` instead.  
  with autocast():
```



--- FINAL BNN RESULTS ---

=====

BNN Final Validation Accuracy: 75.00%

BNN Final Model Size: 35.14 MB

=====

```
/tmp/ipykernel_30532/1491822498.py:62: FutureWarning:
`torch.cuda.amp.autocast(args...)` is deprecated. Please use
`torch.amp.autocast('cuda', args...)` instead.
  with autocast():
```