PwC AGENTS WORKSHOP - HANDBOOK 1
Foundry Platform Reference

1. TOPOLOGY

This workshop uses a hub-and-spoke Foundry topology. One Foundry resource (Microsoft.CognitiveServices/accounts, kind AIServices) acts as the hub. It owns the shared model deployments. Each attendee gets one child Foundry project as their spoke.

Model deployments are shared at the hub. Agents, threads, files and evaluations are isolated per spoke.

2. ACCESS MODEL

Each attendee holds Reader on the hub and Foundry User on their own spoke only. Reader is a control-plane role: you can see that sibling projects exist, but you cannot read their agents or data. Foundry User is the data-plane role that lets you build.

3. IDLE TIMEOUT

Hosted agent sessions terminate after a period of inactivity.
The property is sessionConfiguration.idleTimeoutSeconds.
Minimum 300 seconds. Default 900 seconds. Maximum 3600 seconds.
Values outside that range are rejected at deploy time.

Guidance: quick question-and-answer agents 300s; interactive coding assistants 1800s; long-running analysis 3600s.

4. SESSION ISOLATION

Every hosted agent session runs in its own VM-isolated sandbox with a persistent filesystem. Files written on turn one survive scale-to-zero and are present on turn twenty. This is why git worktrees work inside an agent session.