

```
[root@b7813260c369 ~]# diff /var/log/anaconda/syslog ~/mydir/securecopy.txt
241,245c241,245
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [io 0x0000-0x0cf7 window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [io 0x0d00-0xffff window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [mem 0x000a0000-0x000bffff window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [mem 0xc0000000-0xfebffffff window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [bus 00-ff]
---
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Ruba bus resource [io 0x0000-0x0cf7 window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Ruba bus resource [io 0x0d00-0xffff window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Ruba bus resource [mem 0x000a0000-0x000bffff window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Ruba bus resource [mem 0xc0000000-0xfebffffff window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Ruba bus resource [bus 00-ff]
519c519
< 14:16:38,726 WARNING rpc.statd:Running as root. chown /var/lib/nfs/statd to choose different user
---
> 14:16:38,726 WARNING rpc.statd:Running as Ruba. chown /var/lib/nfs/statd to choose different user
584c584
< 14:16:39,385 INFO NetworkManager:<info> [1631715399.3855] auth[0x557aa18666a0]: create auth-manager: D-Bus connection not available. Polkit
is disabled and only root will be authorized.
---
> 14:16:39,385 INFO NetworkManager:<info> [1631715399.3855] auth[0x557aa18666a0]: create auth-manager: D-Bus connection not available. Polkit
is disabled and only Ruba will be authorized.
662c662
< 14:16:50,382 INFO systemd:Starting Plymouth switch root service...
---
> 14:16:50,382 INFO systemd:Starting Plymouth switch Ruba service...
691c691
< 14:16:50,394 INFO systemd:Started Plymouth switch root service.
---
> 14:16:50,394 INFO systemd:Started Plymouth switch Ruba service.
739c739
< 14:16:50,449 NOTICE systemd:Switching root.
---
> 14:16:50,449 NOTICE systemd:Switching Ruba.
755c755
< 14:16:52,110 INFO systemd:initrd-switch-root.service: Succeeded.
---
> 14:16:52,110 INFO systemd:initrd-switch-Ruba.service: Succeeded.
1197c1197
< 14:16:55,288 DEBUG NetworkManager:<debug> [1631715415.2863] dhcp4 (ens3): option requested_root_path => '1'
---
```

```
ning... mount --rbind /mnt/sysimage /mnt/sysRuba
14:17:41,915 WARNING org.fedoraproject.Anaconda.Modules.Security:ERROR:anaconda.
modules.security.installation:SELinux configuration failed: [Errno 2] No such fi
le or directory: '/mnt/sysRuba/etc/selinux/config'
14:17:42,937 WARNING org.fedoraproject.Anaconda.Modules.Timezone:INFO:program:Ru
nning... systemctl list-unit-files chronyd.service --no-legend --Ruba /mnt/sysRu
ba
14:17:43,957 WARNING org.fedoraproject.Anaconda.Modules.Services:INFO:anaconda.m
odules.services.installation:Writing out user interaction config at /mnt/sysRub
/etc/sysconfig/anaconda
14:17:47,016 WARNING org.fedoraproject.Anaconda.Modules.Users:INFO:anaconda.core
.users:user account Ruba locked
14:17:47,016 WARNING org.fedoraproject.Anaconda.Modules.Users:INFO:program:Runni
ng... chpasswd -R /mnt/sysRuba -e
14:17:47,279 WARNING org.fedoraproject.Anaconda.Modules.Users:INFO:program:Runni
ng... chage -R /mnt/sysRuba -d Ruba
14:17:48,035 WARNING org.fedoraproject.Anaconda.Modules.Users:DEBUG:anaconda.mod
ules.users.installation:Adding an override allowing Ruba login with password via
SSH.
14:17:48,062 WARNING org.fedoraproject.Anaconda.Modules.Network:DEBUG:anaconda.m
odules.network.network:/mnt/sysRuba/etc/sysconfig/network-scripts/ifcfg-ens3:
[root@b7813260c369 mydir]# cksum securecopy.txt
3087018273 488142 securecopy.txt
[root@b7813260c369 mydir]#
```

```
[root@b7813260c369 mydir]# cksum securecopy.txt  
2766876939 488142 securecopy.txt  
[root@b7813260c369 mydir]# █
```



```
[root@b7813260c369 ~]# find -name Ruba.txt  
./mydir/mydir2/Ruba.txt  
./mydir/Ruba.txt  
[root@b7813260c369 ~]# █
```

```
[root@b7813260c369 mydir]# man useradd 1> useradd-man.txt
```

```
[root@b7813260c369 mydir]# ls
```

```
mydir2  Ruba.txt  securecopy.txt  useradd-man.txt
```

```
[root@b7813260c369 mydir]# ls -a | grep password useradd-man.txt
```

The number of days after a **password** expires until the account is the **password** has expired, and a value of -1 disables the feature. account to turn off **password** aging, even though system account has no **password** at all. Multiple -K options can be specified, e.g.:

-p, --**password** PASSWORD

The encrypted **password**, as returned by crypt(3). The default is to disable the **password**.

Note: This option is not recommended because the **password** (or encrypted **password**) will be visible by users listing the processes.

You should make sure the **password** respects the system's **password**

The number of days after a **password** has expired before the account same **password**, and same GID).

The maximum number of days a **password** may be used. If the **password** is older than this, a **password** change will be forced. If not

The minimum number of days allowed between **password** changes. Any **password** changes attempted sooner than this will be rejected. If

The number of days warning given before a **password** expires. A zero Shadow **password** suite configuration.

can't update **password** file

```
[root@b7813260c369 mydir]#
```