Ex No: 9 Date: 04/10/2021	AUTOMATION TESTING ON WEB PAGES USING SELENIUM
Video Link:	

OBJECTIVE

The objective of the experiment is to perform automation testing on a web page using selenium framework on different browsers using Java/Python/C#

DESCRIPTION:

A webpage is to be exhaustively tested using different browsers using selenium framework. A webpage with multiple form fields (Text box, radio button, drop down buttons, buttons, hyperlink) is created and uploaded in to a webserver (IIS/Apache). The content and the form fields in the webpage is individually checked. Also, the client-side validation performed using JavaScript is also to be evaluated. The evaluation is to be carried out by developing various test cases for every individual web component. To this end, an extensive software testing framework is required. Selenium is a free opensource automating and testing framework that supports C#, Java, Perl, PHP, Python and Ruby. Selenium Webdriver provides the functionality of conducting various testcases.

PROCEDURE:

Server side:

• Load the designed Webpage to be tested in the server.

```
(IIS Server- C:\inetpub\wwwroot)
(Apache Server- .....)
```

Client side

- Download all the necessary selenium packages based on the host machine requirement (windows/mac/linux, x86/x64)
- Download the corresponding browser's (Chrome/opera/firefox) web driver to integrate the IDE & browser.

- Using the IDE (Eclipse/Jupyter) create a new Java/Python program.
- Import all the required selenium packages in the java program.
- Using setProperty(), provide the name and location of the browser's webdriver.
- And a WebDriver class instances of the browser is created and it is used to access the webpage.
- The method navigate().to("URL") launches the website in the test browser.
- Every component in a webpage is accessed by the method findElement() and specific entities using the following
 - findElement(By.id("identifier value"))
 - findElement(By.name("name"))nd
 - findElement(By.linkText("Link text"))
 - findElement(By.className("class name"))
- Values are passed on using the method sendKeys("value").
- Inner HTML values are obtained using the method getText().
- Values from forms are obtained using the method getAttribute("value").
- Browser events such as click, clear, back, forward, refresh, and close are performed using the methods click(), clear(), back(), forward(), refresh(), quit() respectively.
- Also, moving between windows and frames are performed using the methods switchTo().window("windowName") and switchTo().frame("frameName");
- Javascript method is invoked by the method executeScript() of the class
 JavascriptExecuter

SOURCE CODE (Chrome):

//Selenium packages

import org.openqa.selenium.By;

import org.openga.selenium.JavascriptExecutor;

import org.openqa.selenium.WebDriver;

import org.openqa.selenium.WebElement;

// Chrome packages

 ${\color{blue} import\ org. open qa. selenium. chrome. Chrome Driver;}$

```
import org.openqa.selenium.chrome.ChromeOptions;
import com.sun.org.apache.bcel.internal.generic.Select;
public class chrome {
       public static void main(String args[])
       //
              System.out.print("hi");
       System.setProperty("webdriver.chrome.driver",
"C:\\Users\\Titus\\Documents\\KITS\\2021-22\\01 odd sem\\20CS2050 L-Software Engineering
Lab-2021-1-BIV\\09 Ex\\chromedriver.exe"):
       // WebDriver driver=new ChromeDriver();
        ChromeOptions opt = new ChromeOptions();
        opt.addArguments("disable-extensions");
        opt.addArguments("--start-maximized");
        WebDriver driver = new ChromeDriver(opt);
       // Launch website
       driver.navigate().to("http://localhost/test.html");
       //Test case 1
       System.out.print("\n\n Test Case 1: Content checking");
        String o1 = driver.findElement(By.id("HText")).getText();
   System.out.print("\n Test Outcome:"+o1);
   System.out.print("\n Desired Outcome:"+"Online Banking solution");
   if (o1.equals("Online Banking solution"))
        System.out.print("\n Summary Test case 1 status: Success ");
   }else
        System.out.print("\n Summary Test case 1 status: Fail");
 //Test case 2:
```

System.*out*.print("\n\n Test Case 2: Checking for null elements");


driver.findElement(By.id("fname")).sendKeys("");

```
System.out.print("\n Given input for textbox (Name):"+"");
 JavascriptExecutor jse = (JavascriptExecutor) driver;
 jse.executeScript("tbox()");
 String o2=driver.findElement(By.id("efname")).getAttribute("value");
 System.out.print("\nTest Outcome:"+o2);
 System.out.print("\n Desired Outcome:"+"Name field cant be empty");
 if (o2.equals("Name field cant be empty"))
        System.out.print("\n Summary: Test case 2 status: Success ");
 }else
        System.out.print("\n Summary: Test case 2 status: Fail ");
//Test case 3:
 System.out.print("\n\n\n Test case 3");
 driver.findElement(By.id("fname")).sendKeys("1234567890000");
 System.out.print("\n Given input for textbox (Name):"+"1234567890000");
 jse.executeScript("tbox()");
 String o3=driver.findElement(By.id("efname")).getAttribute("value");
 System.out.print("\n Test Outcome:"+o3);
 System.out.print("\n Desired Outcome:"+"First name cannot be more than 10 chars");
 if (o3.equals("First name cannot be more than 10 chars"))
        System.out.print("\n Summary Test case 2 status: Success");
 }else
        System.out.print("\n Summary Test case 2 status: Fail");
//Close the Browser
 driver.close();
```

OUTPUT(Chrome):

18CS2009 – 20CS2050 L-Software Engineering

URK20CS



Browser: Chrome/Opera/Firefox/Safari

18CS2009 – 20CS2050 L-Software Engineering

URK20CS

SOURCE CODE(Browser 2):

Browser: Chrome/Opera/Firefox/Safari

OUTPUT (Browser 2):

Browser: Chrome/Opera/Firefox

RESULT:

A web page was tested in the Chrome & Opera Browsers by creating various testcases using java and selenium framework.