



MEDAC

Instituto Oficial de Formación Profesional

Introducción a Angular



He subido la práctica a GitHub.

Enlace al repositorio:

<https://github.com/Ruben0202/todo-angular-Rub-n-Mart-n-2-DAW>

```
PS C:\xampp\htdocs\CosasClase\DEC\2º Trimestre\Introducion_angular> node --version
v24.13.0
11.6.2
PS C:\xampp\htdocs\CosasClase\DEC\2º Trimestre\Introducion_angular>
PS C:\xampp\htdocs\CosasClase\DEC\2º Trimestre\Introducion_angular> npm install -g @angular/cli
added 298 packages in 19s

69 packages are looking for funding
  run `npm fund` for details
PS C:\xampp\htdocs\CosasClase\DEC\2º Trimestre\Introducion_angular> ng version

Angular CLI : 21.1.2
Node.js      : 24.13.0
Package Manager : npm 11.6.2
Operating System : win32 x64
```

```
PS C:\xampp\htdocs\CosasClase\DEC\2º Trimestre\Introducion_angular> ng new todo-angular

Would you like to share pseudonymous usage data about this project with the Angular Team
at Google under Google's Privacy Policy at https://policies.google.com/privacy. For more
details and how to change this setting, see https://angular.dev/cli/analytics.

  No
Global setting: disabled
Local setting: No local workspace configuration file.
Effective status: disabled
✓ Which stylesheet system would you like to use? CSS [ https://developer.mozilla.org/docs/Web/CSS ]
✓ Do you want to enable Server-Side Rendering (SSR) and Static Site Generation (SSG/Prerendering)? No
✓ Which AI tools do you want to configure with Angular best practices? https://angular.dev/ai/develop-with-ai None
CREATE todo-angular/angular.json (1994 bytes)
CREATE todo-angular/package.json (959 bytes)
```



```
PS C:\xampp\htdocs\CosasClase\DEC\2º Trimestre\Introducion_angular> cd todo-angular
PS C:\xampp\htdocs\CosasClase\DEC\2º Trimestre\Introducion_angular\(todo-angular)> ng serve --open
Initial chunk files | Names           | Raw size
main.js              | main            | 48.36 kB |
styles.css           | styles           | 95 bytes |
                                         | Initial total | 48.46 kB

Application bundle generation complete. [2.576 seconds] - 2026-01-28T11:27:51.331Z
Watch mode enabled. Watching for file changes...
NOTE: Raw file sizes do not reflect development server per-request transformations.
  → Local: http://localhost:4200/
  → press h + enter to show help
```

```
JS app.js          ◊ app.html      # app.css      TS app.ts      X   ◊ index.html ...\\src
DEC > 2º Trimestre > Introducion_angular > todo-angular > src > app > TS app.ts > ...
1  import { Component, signal } from '@angular/core';
2  import { RouterOutlet } from '@angular/router';
3
4  @Component({
5    selector: 'app-root',
6    imports: [RouterOutlet],
7    templateUrl: './app.html',
8    styleUrls: ['./app.css']
9  })
10 export class App {
11   protected readonly title = signal('todo-angular');
12 }
```



```
import { Component } from '@angular/core';
import { CommonModule } from '@angular/common';
import { FormsModule } from '@angular/forms';

interface Todo {
  id: number;
  text: string;
  completed: boolean;
}

@Component({
  selector: 'app-root',
  standalone: true,
  imports: [CommonModule, FormsModule],
  templateUrl: './app.html',
  styleUrls: ['./app.css']
})
```

Initial chunk files	Names	Raw size
main.js	main	50.59 kB
styles.css	styles	95 bytes
Initial total		50.68 kB

Application bundle generation complete. [0.143 seconds] - 2026-01-28T11:54:24.647Z



```
export class App {
  title = 'TODO List Angular';

  todos: Todo[] = [];
  nextId = 1;
  newTodoText = '';
  currentFilter = 'all';

  addTodo() {
    if (this.newTodoText.trim() === '') return;

    this.todos.push({
      id: this.nextId,
      text: this.newTodoText.trim(),
      completed: false
    });

    this.nextId++;
    this.newTodoText = '';
  }

  deleteTodo(id: number) {
    this.todos = this.todos.filter(t => t.id !== id);
  }

  toggleTodo(id: number) {
    const todo = this.todos.find(t => t.id === id);
    if (todo) {
      todo.completed = !todo.completed;
    }
  }

  clearCompleted() {
    this.todos = this.todos.filter(t => !t.completed);
  }
}
```



```
clearCompleted() {
  this.todos = this.todos.filter(t => !t.completed);
}

getFilteredTodos(): Todo[] {
  if (this.currentFilter === 'active') {
    return this.todos.filter(t => !t.completed);
  } else if (this.currentFilter === 'completed') {
    return this.todos.filter(t => t.completed);
  } else {
    return this.todos;
  }
}

getActiveCount(): number {
  return this.todos.filter(t => !t.completed).length;
}
```

```
<div class="container">
  <h1>{{ title }}</h1>
```

```
<!-- Input -->
<div class="input-section">
  <input
    type="text"
    [(ngModel)]="newTodoText"
    (keyup.enter)="addTodo()"
    placeholder="Nueva tarea...">

  <button (click)="addTodo()">Añadir</button>
</div>
```



```
<!-- Filtros -->
<div class="filters">
  <button
    [class.active]="currentFilter === 'all'"
    (click)="currentFilter = 'all'>
    Todas
  </button>

  <button
    [class.active]="currentFilter === 'active'"
    (click)="currentFilter = 'active'>
    Activas
  </button>

  <button
    [class.active]="currentFilter === 'completed'"
    (click)="currentFilter = 'completed'>
    Completadas
  </button>
</div>
```

```
<!-- Lista -->
<ul class="todo-list">
  <li
    *ngFor="let todo of getFilteredTodos()"
    [class.completed]="todo.completed"
    class="todo-item">

    <input
      type="checkbox"
      [checked]="todo.completed"
      (change)="toggleTodo(todo.id)"
      class="todo-checkbox">

    <span class="todo-text">{{ todo.text }}</span>

    <button
      (click)="deleteTodo(todo.id)"
      class="delete-btn">
      Eliminar
    </button>
  </li>
</ul>
```



```
<!-- Footer -->
<div class="footer">
  <span>{{ getActiveCount() }} tareas pendientes</span>
  <button (click)="clearCompleted()">Limpiar completadas</button>
</div>
</div>
```

```
body {
  margin: 0;
  font-family: Arial, sans-serif;
  background: linear-gradient(135deg, #667eea 0%, #764ba2 100%);
  min-height: 100vh;
}
```



```
.container {  
    max-width: 600px;  
    margin: 50px auto;  
    padding: 20px;  
    background: #white;  
    border-radius: 8px;  
    box-shadow: 0 2px 10px rgba(0,0,0,0.1);  
}  
  
h1 {  
    text-align: center;  
    color: #333;  
}  
  
.input-section {  
    display: flex;  
    gap: 10px;  
    margin: 20px 0;  
}  
  
input[type="text"] {  
    flex: 1;  
    padding: 10px;  
    border: 2px solid #ddd;  
    border-radius: 4px;  
    font-size: 16px;  
}  
  
button {  
    padding: 10px 20px;  
    border: none;  
    border-radius: 4px;  
    cursor: pointer;  
    font-size: 16px;  
}  
  
.input-section button {  
    background: #4CAF50;  
    color: white;
```



```
.filters {  
  display: flex;  
  gap: 10px;  
  margin: 20px 0;  
}  
  
.filters button {  
  flex: 1;  
  background: #f0f0f0;  
  color: #333;  
}  
  
.filters button.active {  
  background: #2196F3;  
  color: white;  
}  
  
.todo-list {  
  list-style: none;  
  padding: 0;  
  margin: 20px 0;  
}  
  
.todo-item {  
  display: flex;  
  align-items: center;  
  gap: 10px;  
  padding: 12px;  
  border-bottom: 1px solid #eee;  
}  
  
.todo-item.completed .todo-text {  
  text-decoration: line-through;  
  color: #999;  
}
```



```
.todo-checkbox {  
    width: 20px;  
    height: 20px;  
}  
  
.todo-text {  
    flex: 1;  
}  
  
.delete-btn {  
    background: #f44336;  
    color: white;  
}  
  
.footer {  
    display: flex;  
    justify-content: space-between;  
    align-items: center;  
    margin-top: 20px;  
}  
  
.footer button {  
    background: #ff9800;  
    color: white;  
}
```

```
PS C:\xampp\htdocs\CosasClase\DEC\2º Trimestre\Introducion_angular\todo-angular> ng serve  
Initial chunk files | Names | Raw size  
main.js | main | 13.73 kB |  
styles.css | styles | 261 bytes |  
| Initial total | 13.99 kB  
  
Application bundle generation complete. [2.197 seconds] - 2026-01-28T12:03:38.649Z  
  
Watch mode enabled. Watching for file changes...  
NOTE: Raw file sizes do not reflect development server per-request transformations.  
→ Local: http://localhost:4200/  
→ press h + enter to show help
```



```
<!-- Input -->
<div class="input-section">
  <input
    type="text"
    [(ngModel)]="newTodoText"
    [class.error]="newTodoText.length > 100"
    placeholder="Nueva tarea...">

  <span *ngIf="newTodoText.length > 100" class="error-msg">
    Máximo 100 caracteres
  </span>

  <button (click)="addTodo()">Añadir</button>
</div>
```

```
.error {
  border-color: red;
}

.error-msg {
  color: red;
  font-size: 14px;
}
```

```
<small>{{ newTodoText.length }} / 100</small>
```

```
<div *ngIf="todos.length === 0" class="empty-state">
  No hay tareas. ¡Añade una para empezar!
</div>

<!-- Lista -->
<ul *ngIf="todos.length > 0" class="todo-list">
  <li
    *ngFor="let todo of getFilteredTodos()"
    [class.completed]="todo.completed"
    class="todo-item">
```



```
<button  
  (click)="addTodo()"  
  [disabled]="newTodoText.trim() === ''">  
  Añadir  
</button>
```

```
PS C:\xampp\htdocs\CosasClase\DEC\2º Trimestre\Introducción Angular\todo-angular\src\app> ng generate component todo-item  
CREATE src/app/todo-item/todo-item.spec.ts (569 bytes)  
CREATE src/app/todo-item/todo-item.ts (208 bytes)  
CREATE src/app/todo-item/todo-item.css (0 bytes)  
CREATE src/app/todo-item/todo-item.html (25 bytes)
```



```
④ index.html ...\\todo-mvc    # style.css    ④ app.html M    TS todo-item.ts U X    ④ tc D
DEC > 2º Trimestre > Introducion Angular > todo-angular > src > app > todo-item > TS todo-item.ts > ...
1 import { Component, Input, Output, EventEmitter } from '@angular/core';
2 import { CommonModule } from '@angular/common';
3
4
5 interface Todo {
6   id: number;
7   text: string;
8   completed: boolean;
9 }
10
11 @Component({
12   selector: 'app-todo-item',
13   standalone: true,
14   imports: [CommonModule],
15   templateUrl: './todo-item.html',
16   styleUrls: ['./todo-item.css'
17 })
18 export class TodoItem {
19   @Input() todo!: Todo;
20
21   @Output() toggle = new EventEmitter<number>();
22   @Output() removeTodo = new EventEmitter<number>();
23
24
25   onToggle() {
26     this.toggle.emit(this.todo.id);
27   }
28
29   onDelete() {
30     this.removeTodo.emit(this.todo.id);
31   }
32
33 }
34
```



```
style.css      ⌂ app.html M ●  TS todo-item.ts U  ⌂ todo-item.html U X +  
DEC > 2º Trimestre > Introducion_angular > todo-angular > src > app > todo-item > ⌂ todo-item.html  
1   <li  
2     class="todo-item"  
3     [class.completed]="todo.completed">  
4  
5     <input  
6       type="checkbox"  
7       [checked]="todo.completed"  
8       (change)="onToggle()"  
9       class="todo-checkbox">  
10  
11    <span class="todo-text">{{ todo.text }}</span>  
12  
13    <button  
14      class="delete-btn"  
15      (click)="onDelete()">  
16      Eliminar  
17    </button>  
18  </li>  
19
```



The screenshot shows a code editor interface with four tabs at the top: 'app.html M' (modified), 'todo-item.ts U' (untracked), 'todo-item.html U' (modified), and '# todo-item.css U' (modified). The '# todo-item.css' tab is active. Below the tabs, a breadcrumb navigation path is displayed: DEC > 2º Trimestre > Introducion_angular > todo-angular > src > app > todo-item > # todo-item.css. The main area of the editor contains the following CSS code:

```
DEC > 2º Trimestre > Introducion_angular > todo-angular > src > app > todo-item > # todo-item.css >
1  .todo-item {
2    display: flex;
3    align-items: center;
4    gap: 10px;
5    padding: 12px;
6    border-bottom: 1px solid #eee;
7  }
8
9  .todo-item.completed .todo-text {
10   text-decoration: line-through;
11   color: #999;
12 }
13
14 .todo-checkbox {
15   width: 20px;
16   height: 20px;
17 }
18
19 .todo-text {
20   flex: 1;
21 }
22
23 .delete-btn {
24   background: #f44336;
25   color: white;
26 }
```



```
import { Component } from '@angular/core';
import { CommonModule } from '@angular/common';
import { FormsModule } from '@angular/forms';
import { TodoItem } from './todo-item/todo-item';

interface Todo {
  id: number;
  text: string;
  completed: boolean;
}

@Component({
  selector: 'app-root',
  standalone: true,
  imports: [CommonModule, FormsModule, TodoItem],
  templateUrl: './app.html',
  styleUrls: ['./app.css']
})
```

```
<!-- Lista -->
<ul class="todo-list">
  <app-todo-item
    *ngFor="let todo of getFilteredTodos()"
    [todo]="todo"
    (toggle)="toggleTodo($event)"
    (removeTodo)="deleteTodo($event)">
  </app-todo-item>
</ul>
```

```
PS C:\xampp\htdocs\CosasClase\DEC\2º Trimestre\Introducion_angular\todo-angular\src\app> ng serve
Initial chunk files | Names           | Raw size
main.js             | main            | 19.46 kB |
styles.css          | styles          | 261 bytes |
                                         | Initial total | 19.72 kB

Application bundle generation complete. [2.196 seconds] - 2026-01-28T12:32:47.556Z

Watch mode enabled. Watching for file changes...
NOTE: Raw file sizes do not reflect development server per-request transformations.
→ Local: http://localhost:4200/
→ press h + enter to show help
```