

LIB cathode production processes designed for "direct recycling"

F. Soavi^{a,b,c}, A. Staffolani^{a,b}, M. Giovannucci^a, E. Petri^a, F. Mascetti^a, F. Capodarca^a,
S. Mojtahedi^a, S. Xierzati^a, A. Gregucci^a

^aDepartment of Chemistry "Giacomo Ciamician", Alma Mater Studiorum University of Bologna, Via F. Selmi 2, Bologna (BO), 40126 Italy.

^bENERCube lab, Centro Ricerche Energia, Ambiente e Mare, Centro Interdipartimentale per la Ricerca Industriale Fonti Rinnovabili, Ambiente, Mare ed Energia (CIRI-FRAME) —Alma Mater Studiorum University of Bologna, Viale Ciro Menotti, 48, 48122 Marina di Ravenna, Italy

^cNational Reference Center for Electrochemical Energy Storage (GISEL)—INSTM, Via G. Giusti 9, 50121 Firenze, Italy

francesca.soavi@unibo.it

Lithium-ion batteries (LIB) continue to dominate the energy storage landscape and as the demand and use continues to arise, the need for effective recycling methods becomes increasingly important. Recycling of spent LIBs closes the loop of electrodes materials due to the direct use of spent active material as secondary raw materials to produce fresh electrodes. The recovery processes generally include four phases: i) pre-treatment of the LIBs for their safe management (state of charge 0%); ii) separation of the active material from the current collector; iii) leaching; and iv) separation of precious metals in leaching solutions. Physical separation is one of the most advantageous methods for pre-treating and separating valuable components from both an economic and environmental perspective. For physical separation, organic solvents with great affinity for the binder such as NMP, DMAC, DMF and DMSO are generally used which weaken the adhesion between the current collector and the active material. Therefore, for the design of a sustainable recovery of the electrodes and the definition of a reuse platform, two interesting approaches are: i) the use of green solvents for the physical separation of the active materials, ii) the use of soluble binders in water or non-toxic solvents, to produce electrodes, hence to define a production process designed for direct recycling. This study aims to demonstrate the possibility to design electrodes in view of their recovery from production scraps. To this end, the use of water processable and/or bifunctional binder like pullulan or Poly(3,4-ethylenedioxythiophene) polystyrene sulfonate (PEDOT:PSS), and graphitic conductive additive is explored to process LNMO cathodes.

References:

- [1] D. Marchese et al., Batter. 2024, Vol. 10, Page 27. 10 (2024) 27.
- [2] A. Brilloni, F. Poli, G. E. Spina, C. Samorì, E. Guidi, C. Gualandi, M. Maisuradze, M. Giorgetti, F. Soavi, Easy recovery of Li-ion cathode powders by the use of water-processable binders, Electrochim. Acta, 418 (2022) 140376
- [3] A. Brilloni, F. Marchesini, F. Poli, E. Petri, F. Soavi, Performance Comparison of LMNO Cathodes Produced with Pullulan or PEDOT:PSS Water-Processable Binders, Energies 15 (2022) 2608.

Acknowledgments

This work has been financed by the Research Fund for the Italian Electrical System under the Three-Year Research Plan 2022-2024 (DM MITE n. 337, 15.09.2022), in compliance with the Decree of April 16th, 2018”.