



Numerical experiments in glacial inceptions in Northern Europe

ESPELETA BOLIVAR, Ruben Dario

Research project

Presented in partial fulfillment of the requirements for the degree of
Master applied mechanics

Université Grenoble Alpes
May 1, 2023

Project advisor(s):
Ph.D. Cruz García Molina

Contents

1	Introduction	3
2	Glacier dynamics	4
2.1	Mass and movement balance equations	4
2.2	Grounding line stability	6
3	Systems and domains	7
3.1	Physical constants	7
3.2	Boundary conditions	7
3.2.1	Numerical parameters	8
3.2.2	External forcing	8
3.2.3	Initial condition	8
3.2.4	Time step	8
3.3	Cone domain	9
3.4	Thule domain	9
4	Numerical model	9
4.1	The Elmer/Ice finite element method	9
5	Set-up of the simulations data	11
6	Results	11
6.1	Cone configuration	11
6.2	Thule configuration	12
6.3	Comparison of parameters for each resolution for the different configurations . . .	14
7	Discussion	16
8	Conclusion	19
9	Acknowledgments	20

1 Introduction

Ice sheets are important components of global climate systems [Zhang et al., 2017]. The impacts of the perturbation of these climate systems are most acutely changes in global sea level, as ice sheets grow or decay in response to climate forcing and internally controlled dynamics. While the rate of present-day sea-level rise is dominated by ocean steric changes and eustatic changes due to shrinking mountain glaciers, the eustatic contribution from the large ice sheets (Greenland and Antarctic) has increased in recent decades and it is expected to continue increasing in coming decades and centuries [Clark et al., 2015]. To have a better idea, if all the ice were to melt completely, the sea level would rise by an estimated 65m [Morlighem et al., 2017, Haywood et al., 2011] and force populations to emigrate their land submerged by water.

In order to understand these impacts on the dynamics and melting of ice sheets and glaciers, numerical models are developed. Through these models, some of them which are based on finite elements, we can have simulations that can make better predictions of future ice sheets' behavior and rate of sea level rise, and ultimately provide policymakers with improved estimates of future change.




Figure 1: Schematic simplified diagram of the model domain of a glacier [Parizek and Walker, 2010]

There are different variables that play an important role in the dynamics of the glaciers. There is, for example, the grounding line. Its location is still a topic of discussion in the literature surrounding ice sheet dynamics [Goldberg et al., 2018].




Figure 2: Schematic of a tributary glacier where we can observe the different parts denoting the grounding zone [Fricker et al., 2009].

Glaciers that end in the ocean are called tidewater glaciers. Glaciers that flow into an ice shelf are called tributary glaciers as the one shown in figure 1 by [Parizek and Walker, 2010]. The line

that divides the part of the glacier that is in contact with the solid bedrock and the ice shelf floating on water driven by buoyancy, is called the grounding line [Cheng et al., 2019]. The location of the grounding line is important because the mass loss from glaciers is strongly linked to changes in the ice shelves and their grounding lines [Brunt et al., 2010, Pritchard et al., 2012]. Its long-term horizontal position is very susceptible to temporal and spatial changes in ice thickness and sea level, as well as bedrock and ice surface slopes. Ice thinning and rising sea levels can cause grounding lines to retreat while thickening or declining sea levels can cause an advance [Friedl et al., 2020]. It is important to know the grounding line position to be able to quantify the ice discharge into the sea and as an indicator, if the ice sheet is advancing or retreating [Konrad et al., 2018].

Grounding lines are actually more of a zone. The grounding zone is the region where ice transitions from a grounded ice sheet to a freely floating ice shelf, typically over several kilometers. The grounding zone is the region between point F in figure 2 by [Fricker et al., 2009], where there is no tidal movement, and point H, which is the seaward limit of ice flexure, where the ice is free-floating. The floating ice shelf changes in elevation in response to tides, atmospheric air, pressure, and oceanic processes. Grounding occurs when the ice shelf comes into contact with the bedrock below [Fricker et al., 2009]. The transition from grounded ice sheets to floating ice shelves plays an important role in controlling marine ice sheet dynamics, as it determines the rate at which ice flows out of the grounded part of the ice sheet [Schoof, 2007a]. This is because ice flux through the grounding line increases sharply with ice thickness at the grounding line. This means that grounding lines are unstable on reverse-bed slopes, such as those under Pine Island glaciers, because recession into deeper water increases ice flux and further encourages more glacier recession [Schoof, 2007b].

This project aims to understand the direct impact of changes in the position of the grounding line on the flow dynamics of ice sheet glaciers. We will use the finite element model Elmer/Ice to explore the spatial resolution impact on the grounding line position. We will compare the changes in the position of the grounding line for two different idealized topographies. This will let us understand the behavior of real present and past glaciers such as the Northern European glacier.

2 Glacier dynamics

2.1 Mass and movement balance equations

An ice sheet is a continuous sheet of land ice that covers a very large area of several thousand to millions of square meters. It is formed by an accumulation of snow which will densify under its own weight until it becomes ice. This ice will then flow downhill under its weight, and can eventually reach the sea. If it does, and the ice propagates above the sea, this part of the ice sheet is called an ice shelf [Hutter, 1982]. Figure 1 shows a diagram of an ice sheet showing different parts of it, such as the ice shelf, and some phenomena happening inside of it, such as the ice flow or the snow accumulation.

For large time scales the ice is considered a very viscous fluid. The ice flow equations are then derived from the Stokes equation [Hutter, 1982]:

$$\operatorname{div}\sigma + \rho g = \operatorname{div}\tau - \operatorname{grad}p + \rho g = 0; \quad (1)$$

with σ the stress tensor, ρ the density of the ice, g the gravity vector, τ the deviatoric stress tensor, with $\sigma = \tau - pI$ and $p = \frac{\operatorname{tr}\sigma}{3}$.

And the mass conservation:

$$\frac{dh}{dt} + \operatorname{div}(uH) = M_s + M_b; \quad (2)$$

With u the velocity, H the ice thickness, M_s and M_b the mass balance at the surface and at the bottom respectively. M_s will be defined, and M_b is considered as 0 for convenience purposes.

The stresses are related to the viscosity and the strain by Glen's law [Glen, 1958]:

$$\tau = 2\eta\dot{\epsilon}, \quad (3)$$

with the viscosity given by:

$$\eta = \frac{1}{2}(EA)^{\frac{-1}{n}}\dot{\epsilon}_e^{\frac{(1-n)}{n}}. \quad (4)$$

Where:

- The strain rate $\dot{\epsilon}$.
- Glen's constant $n=3$.
- The enhancement factor to account for an anisotropic effect $E=1$.
- The rheological parameter $A=15,46$.

For an ice sheet, the ratio of the vertical length over the horizontal length is more than $1 : 10^3$. Indeed, the thickness of an ice sheet goes from 0 m to a few thousand of meters (e.g. the ice sheet in Greenland is 3300 m thick at most [Bamber et al., 2001,]) and the typical horizontal length of an ice sheet is of the order of magnitude of 1000 km. This allows us to apply the shallow ice approximation. It assumes a large ratio of horizontal to vertical length, that the basal shear stress is balanced by the gravitational driving stress, and a large vertical to horizontal stress ratio. That represents a slow flow in the interior of an ice sheet (blue regions in Figure 3). The approximation makes the method computationally cheaper than the Full-Stokes model with good accuracy over long simulations.




Figure 3: Ice velocities in Antarctica and Greenland topographies, where we can see in red the highest velocity profiles in the glaciers and as a consequence we consider the basal shear stress as 0 and the longitudinal stress dominates, which allows using a Shallow Shelf approximation [Allison et al., 2009,].

Figure 3 shows a map of velocities in Antarctica and Greenland topographies. Where this velocity is the highest, the basal shear stress cannot be considered balanced by gravity anymore. Instead, it is taken as 0 and the longitudinal stress dominates. This is the Shallow Shelf approximation, initially developed for ice shelves, but which has been extended to dragging ice streams. It is a 2D vertically integrated model, the ice velocity being depth-averaged.

But these approximations are not mandatory: the Full Stokes model is still the most precise, it accounts for all nine stress components. It is useful around the parts that are at the limits of the other models or over complex topographies, but not needed for the interior of ice sheets, where the improvement would be minimal but the computational cost way higher [Larour et al., 2012].

The factors such as sensitivity, long time intervals, and long distances require careful treatment of the groundline neighborhood by the numerical method to discretize the model equations [Cheng et al., 2019]. The most accurate ice model is the Full Stokes (FS) equations [Cheng et al., 2019].

However, a simplification of these FS equations by integrating into the depth of the ice is the shallow shelf approximation [MacAyeal, 1989]. The computational advantage with Shallow Shelf approximation is that the dimension of the problem is reduced by one, it is often used for simulations of the interaction between a grounded ice sheet and a marine ice shelf [Cheng et al., 2019]. In this project, only the Shallow Shelf approximation is made, as this is how future projections of Greenland and Antarctica are done with the Elmer/Ice model.

2.2 Grounding line stability

A long debate on the dynamics of such ice sheets was initiated in the 1970s when [Weertman, 1974] proposed that a marine ice sheet that lies on an upward-sloping bed is unstable. Recently, the instability hypothesis has been strongly reinforced, based on a boundary-layer theory due to [Schoof, 2007a]. Moreover, [Viel and Payne, 2005] showed the poor ability of marine ice-sheet models to give consistent prognostic results and, more particularly, they highlighted the influence of the grid size on model results. One of their main conclusions was that no reliable model was able to predict grounding line dynamics at the time of their study.

There is a need to improve marine ice-sheets models in order to corroborate recent theoretical predictions and to obtain confident simulations of the grounding line dynamics. [Durand et al., 2009a] proposed a full-Stokes solution of the ice-sheet/ice-shelf transition. This approach has been built on literature dealing with the coupling between a grounded ice sheet and a floating ice shelf and identifying this transition zone as a crucial control of the marine ice sheet dynamics, like the studies carried out by [Weertman, 1974], [Van der Veen, 1985], [Schoof, 2007a], and [Schoof, 2007b]. Also, [Chugunov and Wilchinsky, 1996] presented a model for the behavior of a marine glacier and ice-sheet-ice-shelf transition zone based on asymptotic analysis, which involves breaking down the equations into simpler components and analyzing their behavior as certain variables approach infinity or zero, to derive a set of simplified equations that can be used to predict the behavior of the glacier and ice-sheet-ice-shelf transition zone. [Hindmarsh, 1996] presents a mathematical model of ice rise stability, which takes into account the effects of ice flow, ice shelf melt, and ocean circulation. He uses this model to analyze the stability of several ice rises and uncoupled marine ice sheets in Antarctica, finding that some of these features may be more stable than previously thought. On the other hand, [Viel and Payne, 2005] evaluate the ability of numerical ice sheet models to simulate grounding line migration. They concluded that while numerical ice sheet models have made significant progress in simulating grounding line migration, there is still much work to be done to improve their accuracy and reliability.

[Durand et al., 2009b] showed, using the finite element code Elmer/Ice, that the full-Stokes modeling of the ice-sheet/ice-shelf transition gives a consistent prediction of grounding-line migration. However, their approach is highly sensitive to the chosen mesh resolution. For a grid size smaller than $5km$ in the grounding-line vicinity, predictions start to be consistent. For any finer resolution than $5km$, the steady-state grounding-line position is the same ($6km$ is the standard deviation). If a sub-grid refinement of $200m$ in the vicinity of the grounding line is applied the steady-state position is stable.

In order to study and test the behavior of the different components of the models, idealized systems are studied and, based on the results that are obtained from these idealized cases, the hypothesis, models, and numerical methods used to solve the problems are improved. For this reason, within the framework of this project, we will analyze the behavior of the Elmer/Ice method to solve idealized systems and topographies. The framework in which the present project is focused is on the study of the Northern Europe glacier. But, since this glacier does not exist anymore, idealized cases simulations of North Europe glaciers, such as Greenland can be analyzed as mentioned before, and their results can be used to improve the numerical models, hypothesis, and parameters of the models, and this way we can better understand the behavior of ancient glaciers such as the Northern Europe glacier.

3 Systems and domains

3.1 Physical constants

Table 1 shows the constants parameters that were set up for the experiment by the Calvin MIP project.

Table 1: Physical constants

Variable	Description	Units
$g = 9.81$	Gravitational acceleration	ms^{-2}
$a_s = 0.3$	Surface mass balance (SMB)	ma^{-1}
$a_b = 0$	Basal mass balance (BMB)	ma^{-1}
$\rho_i = 917$	Ice density	kgm^{-3}
$\rho_w = 1028$	Sea water density	kgm^{-3}
$A = 2.9377 \times 10^{-9}$	Ice rate factor	$KPa^{-3}a^{-1}$
$n = 3$	Flow law stress exponent	
$C = 0.001$	basal slipperiness	$ma^{-1}Kpa^{-3}$
$m = 3$	Sliding law stress exponent	
$s2a = 31556926$	Seconds in a year	seconds

These constants parameters were modified by the Calvin MIP intercomparisson project after the current project was proposed. The water density and the time equivalence from year to seconds was changed from $1030 kg/m^3$ to $1028 kg/m^3$ and from 365.2422 days in a year to 31556926 seconds in a year, respectively. All the rest of the parameters remained the same as listed in table 1.

For the computation of $u_b = 2$, we used the Weertman style sliding law:

$$u_b = C\tau_b^m \quad (5)$$

where C is the basal slipperiness and τ_b is the basal shear stress. In order to enter these values into the Elmer code, we need to convert all units to Elmer units, namely: MPa, meter, and years. It means that all units that are derivated from time in seconds, must be converted to time in years using the time equivalence proposed in the project and all units or values expressed in terms of KPa must be multiplied by a factor of 10^{-3} to be converted to MPa. Also, to compute the basal sliding velocity u_b , Elmer uses the term β that is related to u_b by:

$$\tau = \beta u_b^{\frac{1}{m}} \quad (6)$$

So, we have:

$$u_b = \left(\frac{\tau}{\beta}\right)^m; \quad (7)$$

$$u_b = \frac{1}{\beta^m} \tau^m \quad (8)$$

Using the notation from equation (1), we can say that $C = \frac{1}{\beta^m}$. So, we can compute β as:

$$\beta = \left(\frac{1}{C}\right)^{\frac{1}{m}} \quad (9)$$

If we replace C by its value given in table 1, we get $\beta = 10^4 Pam^{-\frac{1}{3}} a^{\frac{1}{3}}$ which converted to Mpa will give us a value of 10.

3.2 Boundary conditions

Boundary conditions are needed in order to solve differential equations. It will be assumed that:

- The bedrock is impermeable (The vertical component of the ice flow velocity is 0):

$$v = 0 \quad (10)$$

- The flow follows the Weertman friction law:

$$u_b = C\tau_b^m \quad (11)$$

- Mass accumulation is a constant parameter.
- The simulation will be performed on a quarter of the domain since the geometry of the topography is symmetric, which allows having free slip boundary conditions at the left and downsides of the topography, and open boundary conditions at the right and top sides of the domain.

3.2.1 Numerical parameters

The numerical resolution will be our variable physical parameter, which we will vary from 10 km, 5 km, 2 km, 1 km, 500 m, and 250 m.

3.2.2 External forcing

We will assume that the only external force acting are gravity ($g = 9.81m/s^2$), which is translated to the weight of the ice sheet and the flotation force of this in the ocean water, as well as the ice friction with the bedrock.

3.2.3 Initial condition

The simulation departs from no iced configuration. As stated before, the flow will follow the linear Weertman friction law at the base of the ice sheet:

$$u_b = C\tau_b^m; \quad (12)$$

Where τ is the friction shear stress, C is the basal slipperiness coefficient, and u is the velocity. Comparisons were made using friction coefficients ranging from $C = 10^{-8}$ to simulate a friction close to 0, to $C = 10^{-2}$. This coefficient is also the one chosen to perform the simulations. The simulations will start from a topography with no ice, namely $h_0 = 0$. However, the Elmer/Ice code uses a notation where at least a minimum value should be enter in order to avoid convergence problems, so a very small value of $h_0 = 0,01$ is introduced as initial ice thickness.

3.2.4 Time step

The Courant-Friedrichs-Lewy (CFL) condition is a necessary condition to solve numerical partial differential equations. It states that the distance a variable travels between two-time steps must be smaller than the distance between two points of the mesh [Courant et al., 1967,]. It is needed that:

$$C = \frac{u\Delta t}{\Delta x} < Cmax; \quad (13)$$

With C the courant number, u the magnitude of the velocity, Δt the time step, Δx the horizontal resolution, and $Cmax = 1$. This implies then, for a given mesh:

$$\Delta t < \frac{\Delta x}{u}; \quad (14)$$

This is a safe approximation. $Cmax$ then has to be estimated by running different parameters in the simulation and seeing if it converges or not. In order to satisfy the CFL condition, a good starting point is 1 year, since it works properly and converges even for a resolution of 1km. However, in this experiment, it is asked to report the results every 10 years, and for this reason, we will save the results of the simulation with a frequency of 10 years.

This numerical experiment uses two different topographic profiles. A cone and a more realistic topography (Thule).

3.3 Cone domain

The idealized model consists of a circular bedrock configuration (Figure 4) given by:

$$\theta = \arctan2(y, x); \quad (15)$$

$$I = R - \cos(2\theta) \frac{R}{2} \quad (16)$$

$$Bed_0 = Bc - (Bc - BI) \frac{|x^2 + y^2|}{R^2}; \quad (17)$$

Where $R = 800 \times 10^3 m$, $Bc = 0.9 \times 10^3 m$, and $BI = -2 \times 10^3 m$.




Figure 4: Circular bedrock topography. On the left side top view and on the right side, lateral view.

3.4 Thule domain

The Thule bedrock configuration is shown in Figure 5 and is given by:

$$\theta = \arctan2(y, x); \quad (18)$$

$$I = R - \cos(2\theta) \frac{R}{2}; \quad (19)$$

$$Bed_0 = Bc - (Bc - BI) \frac{|x^2 + y^2|}{R^2}; \quad (20)$$

$$Bed = Ba \cos(3\pi \frac{\sqrt{x^2 + y^2}}{I}) + Bed_0; \quad (21)$$

With $R = 800 \times 10^3 m$, $Bc = 0.9 \times 10^3 m$, $BI = -2 \times 10^3 m$, and $Ba = 1.1 \times 10^3$.

4 Numerical model

4.1 The Elmer/Ice finite element method

Most of the time analytical solutions are challenging or even impossible to obtain. In order to model ice sheets, both the finite difference method (FDM) and the finite element method (FEM) are used. The finite difference method consists in converting ordinary and partial differential equations into a system of linear equations by approximating derivatives as finite differences. Elmer/Ice, on the other hand, uses the finite element method.

The ice sheet/ice flow model Elmer/Ice includes developments related to glaciological problems and a large number of dedicated solvers and user functions that solve the Full-Stokes equations for various ice rheologies (classical, Glenn's flow law, anisotropic laws, and porous compressible




Figure 5: Thule bedrock topography 3D. On the left side the top view, and on the right side a lateral view.




Figure 6: a) 10km resolution non-structured mesh used in Elmer/Ice. b) Regular structured mesh for 10km resolution.

firms/snow law). It includes solvers for the classical asymptotical expansions of the Stokes equations, namely the shallow ice approximation and the shallow and shallow shelf approximation (SSA). All these equations can be solved diagnostically or transiently, allowing the displacement of the boundaries.

Elmer/Ice considers a continuum as an assembly of non-overlapping elements forming the same geometry, which makes the modeling of complex geometries possible. Each element is made of at least two points, which are applied to the forces and computed the displacements. To solve the equations, Elmer/Ice uses subroutines or solvers. Each equation corresponds to one solver to be referenced in the input file, together with the different parameters of the problem. They each compute the evolution of given variables, such as the ice thickness or the velocity, to give at each time step a picture of the flow. All combined, it allows us to visualize the evolution of the flow through time.

As mentioned before, the simulations using Elmer/Ice use unstructured meshes, as shown in the left-hand side of figure 6 for a 10km resolution mesh. This is very helpful in terms of simulating complex geometries, for example, the thule configuration.

However, once the simulation is done and to better interpret the results obtained, it is needed to build a structured mesh, because it is ideal for these time-domain simulations this it can easily identified elements and nodes when plotting time-dependent or spacial-dependent graphics. In this case, the objective of interest will be the spacial behaviour or dynamic of the glacier since we will

analyse the position of the grounding line after the steady state is reached. To build the structured mesh, an interpolation made from the unstructured mesh values of the nodes is performed, namely an interpolation per each node of the value of the variables of interest with the values of these same variables in the non-structured mesh. This way it can be known which position the node is in, and the spacial dependent variables can be plot; for example, the velocity components as a function of the horizontal position.

5 Set-up of the simulations data

Once both results for both experiments are obtained, for the domain complete and the quarter domain, the grounding line position per each resolution along the profiles proposed will be quantified. For this, a function that can be denominated grounding line needs to be created, and this function is defined as the product of the bedrock position and a grounding mask. This grounded mask is a step function created, which a value of -1 is assigned to the grounded ice, and 1 to the part of the ice that is no longer in contact with the bedrock, namely:

$$\begin{cases} -1 & \text{bedrock} = z_b \\ 1 & z_b \leq \text{bedrock} \end{cases}$$

Using this mask, the grounding line function is defined as the negative product of this mask and the bedrock (the negative sign is only implemented for convention). From the fact that this grounding line function is an increasing function, it must have a unique maximum, namely, the point where the function changes sign. This maximum means the point where z_b is no longer equal to bedrock position, so starting from this point, the lower part of the ice sheet is not grounded any more. This maximum value of the grounding line function corresponds, physically, to the point where the grounding line or zone is along an x-profile. Knowing this point, the distance from the origin of our coordinate system to that point can be computed, knowing the x and y coordinates of this point, as the norm of this vector, this distance determines the grounding line position, in meters, along an x axis. The results are calculated in two parts: along three profiles A,B and C for the quarter of the domain, and along all the profiles from A to H for the domain complete, in the case of the Cone domain experiment. For the thule experiment, in the first part the grounding line position along Caprona B and Halbrane B needs to be calculated for the quarter domain, and then along all Capronas and Halbranes profiles for the complete domain. For both cases, per each resolution the mean, maximum and minimum value of the grounding line position was calculated.

6 Results

6.1 Cone configuration

For this first experiment proposed, the simulations were run varying the resolution from 10km and up to 1km. In figure 7 we show a qualitative representation of the simulation results for the different resolutions, where we also run 50 and 20km resolution just to have a better idea of how this change in the resolution has an impact in the results. In these figures, the blue part represents the grounded part of the domain, and the grey part represent the floating part. This way we can identify the changes in the transition from grounded to not grounded, namely the grounding zone. We can see also how, as we go closer to a minimum resolution, the differences start to be not that notorious.

In figure 8, we see an schematic representation of the results for the cone circular domain experiment. For the analysis of these results, the ice thickness of the profile was analysed along 8 linear profiles, namely A,B,C,D,E,F,G and H for the domain complete, as shown in figure 8a, and in figure 8b we see all the positions and the ice thickness along the different profiles in the same figure. The point or zone where the lower part of the ice sheet stops being in contact with the bedrock is the grounding line. In this figure it is also highlighted the quarter of the domain in figure 8a and its three profiles A,B,C since, as mentioned before, both simulations for the domain complete and the quarter domain were run to compare the results.




Figure 7: Impact of the resolution in the grounded area for the cone circular domain.

To have a better idea of the simulations convergence, in figure 9 it is shown on the left sides all the values of ice thickness in meters per each resolution, and on the left sides the values of the ice thickness velocity obtained, namely the rate of change of the ice thickness in meters per year. The range of these values, maximum and minimum per resolution are very low (less than 0,001 m/y), which is a brief image that shows that the simulations reached a steady state with a low estimation error.

The mean, maximum and minimum value of the grounding line position per resolution is shown in figure 10 for both case studies, the quarter and complete domain. In the y-axis we have the grounding line position in meters, that is the distance calculated from an origin to the grounding line or zone computed before using the function. This distance is computed as the norm of a vector (x,y) that defines this grounding line position.

For both cases, the complete and quarter of the domain results, it is associated an error bar for the mean values of the grounding line position. The yellow bar corresponds to the quarter domain mean value error bar, and the blue bar corresponds to the complete domain mean value error bar. The error associated was determined as half of the value for each resolution (5km for the 10km resolution, 2.5km for 5km, 1km for 2km and 500m for 1km resolution).

It can be observed how, for greater resolutions as 10km, the results have a difference of around 20km for the grounding line position between the quarter of the domain and the complete domain results, but for lower resolutions these difference starts to be lower.

6.2 Thule configuration

For the second part of the experiments, the results for the thule configuration were obtained for a quarter of the domain and the domain complete, and following the Calving MIP inter comparison project, the simulations using this topography were run using 10,5,2 and 2 km meshes. The figure 11 shows the schematic representation of the thule domain experiment results. Similar to the Cone




Figure 8: Schematic representation of the circular domain ice sheet showing the ice thickness results along the profiles proposed.

domain experiment, here it is proposed to analyse the results along profiles called Caprona and Halbrane. The figure 11a highlights the quarter of the domain, since the simulations were also run for this part of the domain to compare it with the complete system. In this case the results were analysed for Caprona profiles and separately for the Halbrane profiles. In figures 11b and 11c it can be observed the ice thickness along each one of the profiles and so the position of the grounding line.

In figure 12 a qualitative representation of the simulations results can be observed as well to have a visualization of the impact of the resolution on the grounded area of the domain. Similar to the results for the Cone circular domain, the blue part represents the grounded part and the grey part represents the part of the ice that is floating in water.

For the analysis of these results the same procedure was followed; the simulations were run using a quarter of the domain and the complete one, and the results for the grounding line position were analysed along the profile of Halbrane B and Caprona B for the quarter of the domain. A grounding line function is created and computed as the product of the grounded mask function and the negative of the bedrock position. The negative sign is introduced for the same reason as for the cone domain procedure, since the grounding line is an increasing function and as long as z_b is equal to the bedrock position (namely, the ice sheet is grounded) this product will be negative, so if a negative sign is introduced, it will turn positive, making the inflexion point a unique maximum. This point that represents the position of the grounding line is identified per each resolution and the distance to the origin is calculated, along each one of the profiles Capronas and Halbranes.

The figure 13 shows the comparison of the grounding line position along the two types of profiles, Caprona and Halbrane for the quarter and complete domain.

For this experiment, for the quarter of the domain there are only two profiles Caprona B and Halbrane B. For both profiles there is only a value of grounding line position, that is shown in figure 13a and 13b respectively. To compare these positions obtained for the quarter domain, the grounding line positions along Halbrane A,B, C and D are computed for the complete domain following the procedure described previously, and the mean, maximum and minimum value per each resolution are listed in figure 13b. The exact same procedure is applied using the results along the Capronas profiles. For both, the mean value of the grounding line position for the complete domain, and the grounding line position for the quarter domain, the associated error bars are also shown.

It can be observed that as the mesh resolution starts to decrease, the differences between the results for the grounding line positions along both profiles for the complete and quarter domain start to decrease, a similar behaviour observed in the cone circular domain results.




Figure 9: Ice thickness and ice sheet thickness rate of change for quarter domain per each resolution after steady state.

6.3 Comparison of parameters for each resolution for the different configurations

An important parameter to take into account for the results for both experiments, is the computation time spent to complete all the simulations of the experiments. The figure 14 shows the relation between the number of nodes for each one of the mesh resolutions and the time.

Figure 14a shows the time spent using the 32 processors to run all the simulations, while in the figure 14b it is shown the expected time for a 50000 years of simulation if 1 processor was used.

In figure 15 it can be observed also a comparison of the ice thickness variation in time, for each one of the resolutions for the cone circular domain experiment and the error graph associated to this ice thickness as a function of the number of nodes per each resolution.

As it can be observed, the ice thickness does not vary nor oscillates around each value for each




Figure 10: Grounding line positions as a function of the resolution for quarter and complete circular cone domain.




Figure 11: Schematic representation of thule ice sheet showing ice thickness along Caprona and Halbrane profiles.

resolution, which shows the convergence of the system.

The same figures can be plot for the thule experiment, where in figure X it can be observed the ice thickness variation as a function of time and the error or variation of the ice thickness as a function of the number of nodes per each resolution. In both cases, for the computation of ϵ_H the reference value of H it is assumed to be the one corresponding to 1km resolution.

A similar procedure can be done for the volume of the ice sheet. In the figure 17 it is shown the volume as a function of time and the relative variation associated taking into account the 1km resolution volume as the reference for the computation of ϵ_V . It can be observed how the differences start to decrease as long as the resolution decreases until the 1 km reference resolution is reached.

In figure 18, the evolution in time for the volume is also computed for the thule domain per each resolution, as well as the relative variation having the 1km resolution volume as reference.





Figure 12: Impact of the resolution in the grounded area



(a) Grounding line positions along Capronas profiles. (b) Grounding line positions along Halbrane profiles

Figure 13: Grounding line positions as a function of the resolution for quarter and complete thule domain along the Caprona and Halbrane profiles.

7 Discussion

The outcomes of this research have provided insight into the importance of the mesh resolution in the prediction of important parameters like the grounding line position for the glaciers dynamics. The results obtained for the grounding line position for both experiments were consistent with the ones carried out by [Durand et al., 2009b] were they could show that the grounding line position results start to be consistent for a grid size smaller than 5km. In that case, a Full-Stokes model was implemented, while in this case a Shallow-Shelf approximation was carried out, decreasing the simulation time and the computational resources. For the complete domains, as well as for the quarter domains, the results start to be consistent after 5 km resolution meshes.

However, this prediction should be interpreted with caution due to the limitations of the current research. As it can be observed in figure 14, the time spent by simulations as a function of the number of nodes in the mesh was obtained, showing a linear behaviour. This expected computational time is calculated based on 50000 years of simulation, and shows that for example, to complete a




Figure 14: Simulation time as a function of the number of nodes for each resolution mesh.




Figure 15: Ice thickness variation in time for the Cone circular domain experiment.

simulation of a 1 km mesh (3×10^6 nodes), on 50,000 years of simulation, the computing time would be around 2222 hours with the maximum computational time allowed in the laboratory using the 32 processors, as showed in figure 14a. This time would be 32 times greater if 1 processor is used, instead of using all, as shown in figure 14b. This is the main limitation of the project, due to the amount of time required for further simulations of mesh resolutions lower than 1km that could not be carried out for these reason. Besides, even that it has been shown according to the results that a shallow shelf approximation of the Full-Stokes equations can be a good approximation for the prediction of the grounding line position, further experiments with lower mesh resolutions need to be implemented to conclude a robust prediction of these result.

On the other hand, with respect to the convergence of the simulations, figure 9 shows the range of values for the ice thickness rate of change after the steady state was reached, results that are later detailed on figure 15a and 16a for both configurations. In these last figures, it can be observed how after several iterations for different time steps, the ice thickness starts to converge to a constant value. Due to the large computation times discussed before, the implementation of this research was to perform each simulation starting from the previous one as a restart point, and that is the reason why it can be observed that each simulation for each resolution mesh starts from the previous value, (except for the 1km resolution simulation that was performed at the same time with the 2km one, starting from the 5km result, for both configurations.) The fact that the 1 km simulations were run starting from the 5km resolution result, may explain the reason why




Figure 16: Ice thickness variation in time for the Thule domain experiment.




Figure 17: Volume variation in time for the cone domain experiment.

this simulation did not stabilized completely to a constant value, since it can be observed that it did not converged fully to a constant line. Also, the values of convergence were increasing as the resolution mesh decreased (from a very small close to 0 value for ice thickness for the 10km resolution, to around 1,77 m/y for the thule domain and 2,5 m/y for the cone domain).

For these reasons, the convergence of the ice thickness can not be fully concluded after these results obtained. further simulations beyond 1km resolution mesh could be needed in order to evaluate the convergence to an specific value of ice thickness for a certain configuration domain. In figure 9 it can be observed in the right hand side the zones where the variation of the ice thickness was the lowest and the highest, and as stated before, since the simulations were run using the previous results as a restart point, the iterations started from these values and not from 0. For these reasons, for a certain time of simulation, it converged faster for the zones of the domain where the variables (in this case, the high thickness velocity) did not change too much with respect to one resolution or another, due to the simplicity of the zone or the geometry.

However, even if the convergence of the ice thickness can not be fully concluded as stated before, figures 17a and 18a show a different behaviour for the convergence of the domains volume. For




Figure 18: Volume variation in time for the thule domain experiment.

both configurations, the volume variation in time converges to a constant value. The behaviour of convergence is similar to the one for the ice thickness, but in this case for both configuration the value of the volume starts to reach the same constant value as the resolution mesh decreases. For this case as well the 1 km resolution is taken as the reference for the computation of the relative variation and it can be observed in figure 17b and 18b that the differences decrease as a function of the number of nodes, with a slight difference for the 2 km resolution for both configurations. This difference in the convergence of the volume and the convergence of the ice thickness can be explained, by the fact that the volume not only depends of the ice thickness but also on the surface area. The computation of the volume stands for the summary of each volume per element, and each element surface area is greater than its thickness and ends up being the determinant quantity at the time of computing the complete domain volume.

For these reasons, even if the results obtained show that the position of the grounding line can be well predicted using the SSA model for resolution meshes lower than 5km, these results may not indicate enough information about the convergence of variables as the ice thickness when varying the resolution. However, as it was shown, using only a quarter domain can reduce the computation time of further simulations and researches, and these way further simulations beyond 1km resolution meshes can be performed in order to reach to a convergence for these kind of variables.

8 Conclusion

In this project an approach using a shallow shelf approximation (SSA) model was proposed to simulate the motion of glaciers with two different configuration topography. The ice flow is determined by solving the Stokes problem implemented in finite element code Elmer/Ice with the SSA assumptions. This problem was solved by taking into account the complete domain and also solving only a quarter of the domain, due to the symmetry of the system. The position of the grounding line was studied for different resolution meshes starting from 10km and up to 1km, and it was shown that despite the sensitivity of the grounding line to the mesh resolution, it started to converge for resolutions lower to 5km, despite the configuration or the topography as well. The results for the quarter domain for both topographies showed consistency with the results for the complete domain for the prediction of the grounding line position. However, further simulations need to be performed with resolution meshes lower than 1km to fully conclude the convergence of all the variable results. According to the results obtained in this research project, it can be a good path for future researches to run simulation experiments with a quarter of the domain to save computational time, as the results are consistent due to the symmetry, and it can be possible to model more realistic glacier topographies using SSA models. Developing approaches to model

more realistic glacier topographies, can allowed to better understand and predict the dynamics of the glaciers along time, and this way it can be better understood its impact on the formation and changes of the ice sheets and their behaviour.

9 Acknowledgments

This research is part of the Calvin MIP intercomparison project proposed as part of the PROTECT (projecting sea-level rise: from ice sheet to local implications), an EU project funded to assess and project changes in the land-based cryosphere, with fully quantified uncertainties to produce robust global, regional and local projections on a range of timescales. All the computations and simulations run and presented in this project were performed in the Institut des géosciences de l'environnement (IGE) and the Observatoire des sciences de l'univers de Grenoble (OSUG-B).

References

- [Allison et al., 2009] Allison, I., Alley, R., Fricker, H., Thomas, R., and Warner, R. (2009). Ice sheet mass balance and sea level. *Antarctic Science*, 21(5):413–426.
- [Bamber et al., 2001] Bamber, J. L., Layberry, R. L., and Gogineni, S. (2001). A new ice thickness and bed data set for the greenland ice sheet: 1. measurement, data reduction, and errors. *Journal of Geophysical Research: Atmospheres*, 106(D24):33773–33780.
- [Brunt et al., 2010] Brunt, K. M., Fricker, H. A., Padman, L., Scambos, T. A., and O’Neel, S. (2010). Mapping the grounding zone of the ross ice shelf, antarctica, using icesat laser altimetry. *Annals of Glaciology*, 51(55):71–79.
- [Cheng et al., 2019] Cheng, G., Lötstedt, P., and von Sydow, L. (2019). A full stokes subgrid model for simulation of grounding line migration in ice sheets. *arXiv preprint arXiv:1908.10751*.
- [Chugunov and Wilchinsky, 1996] Chugunov, V. A. and Wilchinsky, A. V. (1996). Modelling of a marine glacier and ice-sheet-ice-shelf transition zone based on asymptotic analysis. *Annals of Glaciology*, 23:59–67.
- [Clark et al., 2015] Clark, P. U., Church, J. A., Gregory, J. M., and Payne, A. J. (2015). Recent progress in understanding and projecting regional and global mean sea level change. *Current Climate Change Reports*, 1(4):224–246.
- [Courant et al., 1967] Courant, R., Friedrichs, K., and Lewy, H. (1967). On the partial difference equations of mathematical physics. *IBM journal of Research and Development*, 11(2):215–234.
- [Durand et al., 2009a] Durand, G., Gagliardini, O., De Fleurian, B., Zwinger, T., and Le Meur, E. (2009a). Marine ice sheet dynamics: Hysteresis and neutral equilibrium. *Journal of Geophysical Research: Earth Surface*, 114(F3).
- [Durand et al., 2009b] Durand, G., Gagliardini, O., Zwinger, T., Le Meur, E., and Hindmarsh, R. C. (2009b). Full stokes modeling of marine ice sheets: influence of the grid size. *Annals of Glaciology*, 50(52):109–114.
- [Fricker et al., 2009] Fricker, H. A., Coleman, R., Padman, L., Scambos, T. A., Bohlander, J., and Brunt, K. M. (2009). Mapping the grounding zone of the amery ice shelf, east antarctica using insar, modis and icesat. *Antarctic Science*, 21(5):515–532.
- [Friedl et al., 2020] Friedl, P., Weiser, F., Fluhrer, A., and Braun, M. H. (2020). Remote sensing of glacier and ice sheet grounding lines: A review. *Earth-Science Reviews*, 201:102948.
- [Glen, 1958] Glen, J. (1958). The flow law of ice: A discussion of the assumptions made in glacier theory, their experimental foundations and consequences. *IASH Publ*, 47(171):e183.
- [Goldberg et al., 2018] Goldberg, D., Snow, K., Holland, P., Jordan, J., Campin, J.-M., Heimbach, P., Arthern, R., and Jenkins, A. (2018). Representing grounding line migration in synchronous coupling between a marine ice sheet model and a z-coordinate ocean model. *Ocean Modelling*, 125:45–60.
- [Haywood et al., 2011] Haywood, A., Dowsett, H. J., Robinson, M. M., Stoll, D. K., Dolan, A., Lunt, D., Otto-Bliesner, B., and Chandler, M. (2011). Pliocene model intercomparison project (pliomip): experimental design and boundary conditions (experiment 2). *Geoscientific Model Development*, 4(3):571–577.
- [Hindmarsh, 1996] Hindmarsh, R. (1996). Stability of ice rises and uncoupled marine ice sheets. *Annals of Glaciology*, 23:105–115.
- [Hutter, 1982] Hutter, K. (1982). A mathematical model of polythermal glaciers and ice sheets. *Geophysical & Astrophysical Fluid Dynamics*, 21(3-4):201–224.

- [Konrad et al., 2018] Konrad, H., Shepherd, A., Gilbert, L., Hogg, A. E., McMillan, M., Muir, A., and Slater, T. (2018). Net retreat of antarctic glacier grounding lines. *Nature Geoscience*, 11(4):258–262.
- [Larour et al., 2012] Larour, E., Seroussi, H., Morlighem, M., and Rignot, E. (2012). Continental scale, high order, high spatial resolution, ice sheet modeling using the ice sheet system model (issm). *Journal of Geophysical Research: Earth Surface*, 117(F1).
- [MacAyeal, 1989] MacAyeal, D. R. (1989). Large-scale ice flow over a viscous basal sediment: Theory and application to ice stream b, antarctica. *Journal of Geophysical Research: Solid Earth*, 94(B4):4071–4087.
- [Morlighem et al., 2017] Morlighem, M., Williams, C. N., Rignot, E., An, L., Arndt, J. E., Bamber, J. L., Catania, G., Chauché, N., Dowdeswell, J. A., Dorschel, B., et al. (2017). Bedmachine v3: Complete bed topography and ocean bathymetry mapping of greenland from multibeam echo sounding combined with mass conservation. *Geophysical research letters*, 44(21):11–051.
- [Parizek and Walker, 2010] Parizek, B. R. and Walker, R. T. (2010). Implications of initial conditions and ice–ocean coupling for grounding-line evolution. *Earth and Planetary Science Letters*, 300(3-4):351–358.
- [Pritchard et al., 2012] Pritchard, H., Ligtenberg, S. R., Fricker, H. A., Vaughan, D. G., van den Broeke, M. R., and Padman, L. (2012). Antarctic ice-sheet loss driven by basal melting of ice shelves. *Nature*, 484(7395):502–505.
- [Schoof, 2007a] Schoof, C. (2007a). Ice sheet grounding line dynamics: Steady states, stability, and hysteresis. *Journal of Geophysical Research: Earth Surface*, 112(F3).
- [Schoof, 2007b] Schoof, C. (2007b). Marine ice-sheet dynamics. part 1. the case of rapid sliding. *Journal of Fluid Mechanics*, 573:27–55.
- [Van der Veen, 1985] Van der Veen, C. (1985). Response of a marine ice sheet to changes at the grounding line. *Quaternary Research*, 24(3):257–267.
- [Vieli and Payne, 2005] Vieli, A. and Payne, A. J. (2005). Assessing the ability of numerical ice sheet models to simulate grounding line migration. *Journal of Geophysical Research: Earth Surface*, 110(F1).
- [Weertman, 1974] Weertman, J. (1974). Stability of the junction of an ice sheet and an ice shelf. *Journal of Glaciology*, 13(67):3–11.
- [Zhang et al., 2017] Zhang, T., Price, S., Ju, L., Leng, W., Brondex, J., Durand, G., and Gagliardini, O. (2017). A comparison of two stokes ice sheet models applied to the marine ice sheet model intercomparison project for plan view models (mismip3d). *The Cryosphere*, 11(1):179–190.