CSC/CPE 138 - Computer Network Fundamentals

Network Layer: Control Plane

The presentation was adapted from the textbook: *Computer Networking: A Top-Down Approach* 8th edition Jim Kurose, Keith Ross, Pearson, 2020

Redefine the Possible℠

Network layer: “control plane” roadmap

- introduction
- routing protocols
- intra-ISP routing: OSPF
- routing among ISPs: BGP
- SDN control plane
- Internet Control Message Protocol

- network management, configuration
  - SNMP
  - NETCONF/YANG

Making routing scalable

our routing study thus far - idealized

- all routers identical
- network "flat"

… not true in practice

scale: billions of destinations:

- can't store all destinations in routing tables!
- routing table exchange would swamp links!

administrative autonomy:

- Internet: a network of networks
- each network admin may want to control routing in its own network

Internet approach to scalable routing

aggregate routers into regions known as "autonomous systems" (AS) (a.k.a. "domains")

intra-AS (aka "intra-domain"): routing among *within same AS ("network")*

- all routers in AS must run same intra-domain protocol
- routers in different AS can run different intra-domain routing protocols
- gateway router: at "edge" of its own AS, has link(s) to router(s) in other AS'es

inter-AS (aka "inter-domain"): routing *among* AS'es

- gateways perform inter-domain routing (as well as intra-domain routing)

Interconnected ASes



forwarding table configured by intra- and inter-AS routing algorithms

- intra-AS routing determine entries for destinations within AS
- inter-AS & intra-AS determine entries for external destinations

Inter-AS routing: routing within an AS

most common intra-AS routing protocols:

- RIP: Routing Information Protocol [RFC 1723]
  - classic DV: DVs exchanged every 30 secs
  - no longer widely used
- EIGRP: Enhanced Interior Gateway Routing Protocol
  - DV based
  - formerly Cisco-proprietary for decades (became open in 2013 [RFC 7868])
- OSPF: Open Shortest Path First [RFC 2328]
  - link-state routing
  - IS-IS (intermediate system) protocol (ISO standard, not RFC standard) is essentially same as OSPF

OSPF (Open Shortest Path First) routing

- “open”: publicly available
- classic link-state
  - each router floods OSPF link-state advertisements (directly over IP rather than using TCP/UDP) to all other routers in entire AS
  - multiple link costs metrics possible: bandwidth, delay
  - each router has full topology, uses Dijkstra’s algorithm to compute forwarding table
- *security:* all OSPF messages authenticated (to prevent malicious intrusion)

Hierarchical OSPF

- **two-level hierarchy:** local area, backbone.
  - link-state advertisements flooded only in area, or backbone
  - each node has detailed area topology; only knows direction to reach other destinations



Network layer: “control plane” roadmap

- introduction
- routing protocols
- intra-ISP routing: OSPF
- routing among ISPs: BGP (Border Gateway Protocol)
- SDN control plane
- Internet Control Message Protocol

- network management, configuration
  - SNMP
  - NETCONF/YANG

Interconnected ASes



- intra-AS (aka "intra-domain"): routing among routers *within same AS ("network")*
- inter-AS (aka "inter-domain"): routing *among* AS'es

Internet inter-AS routing: BGP

- BGP (Border Gateway Protocol): *the* de facto inter-domain routing protocol
  - "glue that holds the Internet together"
- allows subnet to advertise its existence, and the destinations it can reach, to rest of Internet: *"I am here, here is who I can reach, and how"*
- BGP provides each AS a means to:
  - obtain destination network reachability info from neighboring ASes (eBGP)
  - determine routes to other networks based on reachability information and *policy*
  - propagate reachability information to all AS-internal routers (iBGP)
  - advertise (to neighboring networks) destination reachability info

eBGP, iBGP connections



gateway routers run both eBGP and iBGP protocols

BGP basics

- BGP session: two BGP routers ("peers") exchange BGP messages over semi-permanent TCP connection:
  - advertising *paths* to different destination network prefixes (BGP is a "path vector" protocol)
- when AS3 gateway 3a advertises path AS3,X to AS2 gateway 2c:
  - AS3 *promises* to AS2 it will forward datagrams towards X



BGP protocol messages

- BGP messages exchanged between peers over TCP connection
- BGP messages [RFC 4371]:
  - OPEN: opens TCP connection to remote BGP peer and authenticates sending BGP peer
  - **UPDATE:** advertises new path (or withdraws old)
  - KEEPALIVE: keeps connection alive in absence of UPDATES; also ACKs OPEN request
  - NOTIFICATION: reports errors in previous msg; also used to close connection

Path attributes and BGP routes

- BGP advertised route: prefix + attributes
  - prefix: destination being advertised
  - two important attributes:
    - AS-PATH: list of ASes through which prefix advertisement has passed
    - NEXT-HOP: indicates specific internal-AS router to next-hop AS
- policy-based routing:
  - gateway receiving route advertisement uses *import policy* to accept/decline path (e.g., never route through AS Y).
  - AS policy also determines whether to *advertise* path to other other neighboring ASes

BGP path advertisement



- AS2 router 2c receives path advertisement AS3,X (via eBGP) from AS3 router 3a
- based on AS2 policy, AS2 router 2c accepts path AS3,X, propagates (via iBGP) to all AS2 routers
- based on AS2 policy, AS2 router 2a advertises (via eBGP) path AS2, AS3, X to AS1 router 1c

BGP path advertisement: multiple paths



gateway router may learn about multiple paths to destination:

- AS1 gateway router 1c learns path *AS2,AS3,X* from 2a
- AS1 gateway router 1c learns path *AS3,X* from 3a
- based on *policy,* AS1 gateway router 1c chooses path *AS3,X* and advertises path within AS1 via iBGP

BGP: achieving policy via advertisements





ISP only wants to route traffic to/from its customer networks (does not want to carry transit traffic between other ISPs – a typical "real world" policy)

- A advertises path Aw to B and to C
- B *chooses not to advertise* BAw to C!
  - B gets no "revenue" for routing CBAw, since none of C, A, w are B's customers
  - C does *not* learn about CBAw path
- C will route CAw (not using B) to get to w

BGP: achieving policy via advertisements (more)



ISP only wants to route traffic to/from its customer networks (does not want to carry transit traffic between other ISPs – a typical "real world" policy)

- A,B,C are provider networks
- x,w,y are customer (of provider networks)
- x is dual-homed: attached to two networks
- *policy to enforce:* x does not want to route from B to C via x
  - .. so x will not advertise to B a route to C

BGP: populating forwarding tables



dest	interface
…	…
1c	1
X	1
…	…

- recall: 1a, 1b, 1d learn via iBGP from 1c: "path to X goes through 1c"
- at 1d: OSPF intra-domain routing: to get to 1c, use interface 1
- at 1d: to get to X, use interface 1

BGP: populating forwarding tables



dest	interface
…	…
1c	2
X	2
…	…

- recall: 1a, 1b, 1d learn via iBGP from 1c: “path to X goes through 1c”
- at 1d: OSPF intra-domain routing: to get to 1c, use interface 1
- at 1d: to get to X, use interface 1
- at 1a: OSPF intra-domain routing: to get to 1c, use interface 2
- at 1a: to get to X, use interface 2

Hot potato routing



- 2d learns (via iBGP) it can route to X via 2a or 2c
- hot potato routing: choose local gateway that has least *intra-domain* cost (e.g., 2d chooses 2a, even though more AS hops to *X*): don't worry about inter-domain cost!

Why different Intra-, Inter-AS routing ?

policy:

- inter-AS: admin wants control over how its traffic routed, who routes through its network
- intra-AS: single admin, so policy less of an issue

scale:

- hierarchical routing saves table size, reduced update traffic

performance:

- intra-AS: can focus on performance
- inter-AS: policy dominates over performance

SACRAMENTO STATE

CSC/CPE 138 - Computer Network Fundamentals

The Link Layer and LANs

The presentation was adapted from the textbook: *Computer Networking: A Top-Down Approach* 8th edition Jim Kurose, Keith Ross, Pearson, 2020

Redefine the Possible™

Link layer and LANs: our goals

- understand principles behind link layer services:
  - error detection, correction
  - sharing a broadcast channel: multiple access
  - link layer addressing
  - local area networks: Ethernet, VLANs
- datacenter networks

- instantiation, implementation of various link layer technologies

Link layer, LANs: roadmap

- introduction
- error detection, correction
- multiple access protocols
- LANs
  - addressing, ARP
  - Ethernet
  - switches
  - VLANs
- link virtualization: MPLS
- data center networking

- a day in the life of a web request

Link layer: introduction

terminology:

- hosts and routers: nodes
- communication channels that connect adjacent nodes along communication path: links
  - wired
  - wireless
  - LANs
- layer-2 packet: *frame*, encapsulates datagram



> *link layer has responsibility of transferring datagram from one node to physically adjacent node over a link*

Link layer: context

- datagram transferred by different link protocols over different links:
  - e.g., WiFi on first link, Ethernet on next link
- each link protocol provides different services
  - e.g., may or may not provide reliable data transfer over link

transportation analogy:

- trip from Princeton to Lausanne
  - limo: Princeton to JFK
  - plane: JFK to Geneva
  - train: Geneva to Lausanne
- tourist = datagram
- transport segment = communication link
- transportation mode = link-layer protocol
- travel agent = routing algorithm

Link layer: services

- **framing, link access:**
  - encapsulate datagram into frame, adding header, trailer
  - channel access if shared medium
  - “MAC” addresses in frame headers identify source, destination (different from IP address!)
- **reliable delivery between adjacent nodes**
  - we already know how to do this!
  - seldom used on low bit-error links
  - wireless links: high error rates
    - *Q:* why both link-level and end-end reliability?



Link layer: services (more)

- flow control:
  - pacing between adjacent sending and receiving nodes
- error detection:
  - errors caused by signal attenuation, noise.
  - receiver detects errors, signals retransmission, or drops frame
- error correction:
  - receiver identifies *and corrects* bit error(s) without retransmission
- half-duplex and full-duplex:
  - with half duplex, nodes at both ends of link can transmit, but not at same time





Where is the link layer implemented?

- in each-and-every host
- link layer implemented in *network interface card* (NIC) or on a chip
  - Ethernet, WiFi card or chip
  - implements link, physical layer
- attaches into host's system buses
- combination of hardware, software, firmware



Interfaces communicating



sending side:

- encapsulates datagram in frame
- adds error checking bits, reliable data transfer, flow control, etc.

receiving side:

- looks for errors, reliable data transfer, flow control, etc.
- extracts datagram, passes to upper layer at receiving side