

© 2026 THIS DOCUMENT IS THE PROPERTY OF AZOTEQ, AND MAY NOT BE COPIED OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SUPPLIED WITHOUT PERMISSION IN WRITING FROM THE OWNER.

ERRATA - REVISION HISTORY NOTES:

DATE	ENGINEER	REVISION	NOTES:
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*
*	*	*	*

- GROUND STAR - use NETTIES
- ESD GND
- DGND & AGND
- LOAD 1 & LOAD 2 (ETC) GND RETURNS
- BOOST or BUCK GND RETURNS
- VBAT STAR

ALIGNMENT HOLES FOR TESTER
DELETE IF NOT NEEDED
SPECIAL LAYOUT REQUIREMENTS:
*
*
*
*

IMPORTANT STEPS AND INSTRUCTIONS

- ERC report to confirm no errors
- Component placement positions
- Star Position / Component Group
- LEDS - position sensitive? Mask or copper alignment

LAYOUT CONSIDERATIONS

Current Ratings :	
Thick Wires	xxAmps
Medium Wires	xxAmps
Thin Wires	xxAmps
Thermistor Position	Centre
Testpoint Layer	XXX Layer

- Noise Considerations
- Noise sensitive tracks :
- RX , TX , Feedback tracks
- Noise producing tracks or Components :
- PWM tracks , Inductors

PCB INFORMATION

MNFPCB

PCB TYPE	FR4
PCB THICKNESS (MM)	1.6 mm
PCB SIZE - WIDTH (MM)	60 mm
PCB SIZE - LENGTH (MM)	60.18 mm
PCB LAYER QTY	2
PCB COLOUR - SOLDER MASK	GREEN
PCB COLOUR - SILKSCREEN	WHITE
PCB PLATING FINISH	ENIG
PCB PLATING THICKNESS	0.05
PCB COPPER THICKNESS (um)	35

ASSEMBLY - MANUFACTURE - LOGISTICS

WIRES	*
TERMINALS	*
BONDING POINTS	*
PCB SEPERATION	*
DOUBLE SIDED ASSY	*
TEST STEPS	*
INSPECTION STEPS	*
PLASTIC ASSEMBLY	*
PACKAGING	*
WASHING	*
TRANSPORT	*
CONFORMAL COATING	*
REVISION PCB	A1
REVISION SCH	A1
PCB SPECIAL OPERATIONS	*

DATESTAMP OF THIS PRINT:
2026/04/16 09:56:41

			DESIGNER
			RvT
			DRAWN
			JR
REV	DATE	ECP #	

	
PCB FILENAME: DT_AZP1524A1_PCB1_00A.PCB	SCH FILENAME: DT_AZP1524A1_SCH1[SHEET1]_00A.SchDoc

TITLE: Logic Analyzer Sheet 1	SHEET: 1 OF 2
DOCUMENT: AZP1524A1	REVISION: 1

