

Homework6

Tianru Zhang (PID: A15432834)

10/19/2021

Load the library for bio3d:

```
#load the packages  
library("bio3d")
```

First, let's look at what the given code does:

```
# this is the demo code provided in the pdf  
#first of all, specify the protein file to be read  
s1 <- read.pdb("4AKE") # kinase with drug
```

```
## Note: Accessing on-line PDB file
```


```
s2 <- read.pdb("1AKE") # kinase no drug
```

```
## Note: Accessing on-line PDB file  
## PDB has ALT records, taking A only, rm.alt=TRUE
```

```
s3 <- read.pdb("1E4Y") # kinase with drug
```

```
## Note: Accessing on-line PDB file
```


```
#get the chain information by trimming the protein sequence  
#set the chain identifier as A, and the element type as CA  
s1.chainA <- trim.pdb(s1, chain="A", elety="CA")  
s2.chainA <- trim.pdb(s2, chain="A", elety="CA")  
s3.chainA <- trim.pdb(s3, chain="A", elety="CA")  
#I modified the line above because there's a paste mistake s1>>s3  
  
#access the atom data for each amino acid residue on A chain of the proteins  
s1.b <- s1.chainA$atom$b  
s2.b <- s2.chainA$atom$b  
s3.b <- s3.chainA$atom$b  
#generate the plot information on the protein sequence  
plotb3(s1.b, sse=s1.chainA, typ="l", ylab="Bfactor")
```



```
plotb3(s2.b, sse=s2.chainA, typ="l", ylab="Bfactor")
```



```
plotb3(s3.b, sse=s3.chainA, typ="l", ylab="Bfactor")
```



The code above takes in protein names, and generate graphs indicate the mobility of different amino acid residues on a protein chain

Based on the given information, my function's inputs are the protein names with quotes, so that specifies it to ****read in the *files on that specific kind of protein, and trims the sequence by looking at the atom data of its A chain, then uses the data to generate graphs as outputs on residue mobility. This is the function that takes in a random protein name in quotes and do the same analysis as above, and outputs a graph**** that indicates the interaction between different residues with the binding factor and the mobility of different residues.


```
#input x is the protein name
proteinP<-function(x){
  #first of all, specify the protein file to be read
  s<-read.pdb(x)
  #get the chain information by trimming the protein sequence
  #set the chain identifier as A, and the element type as CA
  s.chainA <- trim.pdb(s, chain="A", elety="CA")
  #access the atom data for each amino acid residue on A chain of the proteins
  s.b <- s.chainA$atom$b
  #generate the plot information on the protein sequence
  plotb3(s.b, sse=s.chainA, typ="l", ylab="Bfactor")
}
```

Now test the function on the three proteins:

```
#this is generating the graph for the first protein kinase with drug  
proteinP("4AKE")
```

```
## Note: Accessing on-line PDB file
```

```
## Warning in get.pdb(file, path = tempdir(), verbose = FALSE): C:  
## \Users\zhang\AppData\Local\Temp\Rtmpu4avcK\4AKE.pdb exists. Skipping download
```




```
#this generates the graph for the second protein with no drug  
proteinP("1AKE")
```

```
## Note: Accessing on-line PDB file
```

```
## Warning in get.pdb(file, path = tempdir(), verbose = FALSE): C:  
## \Users\zhang\AppData\Local\Temp\Rtmpu4avcK\1AKE.pdb exists. Skipping download
```

```
## PDB has ALT records, taking A only, rm.alt=TRUE
```




```
#this generates the graph for the third protein with drug
proteinP("1E4Y")
```

```
## Note: Accessing on-line PDB file
```

```
## Warning in get.pdb(file, path = tempdir(), verbose = FALSE): C:
```

```
## \Users\zhang\AppData\Local\Temp\Rtmpu4avcK\1E4Y.pdb exists. Skipping download
```



#the graphs indicate the mobility of different residues on the protein chain

Hooray! The graphs are generated as shown above. :) They are the same as the graphs generated by the separate analysis.