b1ac6280-2730-459b-9555-58857d6d4

<current>

<request>

You are working on an issue in the 'franklesniak/PSStyleGuide' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/PSStyleGuide/PSStyleGuide (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-13T05:01:12.557Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section details on the original issue you should resolve

<issue_title>Add file encoding rule (UTF-8 without BOM) to STYLE_GUIDE.md</issue_title>
<issue_description>In `STYLE_GUIDE.md`, add a new subsection under "Code Layout and Formatting" titled "File Encoding" with the following rule:

- **[All]** PowerShell `.ps1` source files **MUST** be saved as UTF-8 **without** a Byte Order Mark (BOM, `U+FEFF`).
- **Editor configuration:** Editors used for PowerShell development **SHOULD** be configured to save `.ps1` files as UTF-8 without BOM. If tool-specific examples are included, they **SHOULD** be presented as examples rather than assumptions that all environments behave identically.

Also add a corresponding checklist item in the "Code Layout and Formatting (Quick Reference)" section:

- **<a>All]** Source `.ps1` files **MUST** be UTF-8 without BOM → [File Encoding

````
In `STYLE_GUIDE_RATIONALE.md`, add a corresponding rationale
section with the following guidance:

- UTF-8 does not require a BOM. A leading BOM is an invisible
character that can cause practical problems, including
interfering with regex-based text processing, breaking shebang
(`#!`) handling on Linux/macOS, and creating unnecessary cross-
tool inconsistencies or diff noise. Saving `.ps1` files as BOM-
less UTF-8 avoids these issues and aligns with modern editor and
automation behavior.

The rationale section **SHOULD** also include VS Code
configuration guidance as an example:

- VS Code defaults to UTF-8 without BOM (`files.encoding:
utf8`), so no change is typically needed. To verify, check the
encoding shown in the status bar at the bottom-right of the
window. To make the intent explicit in a workspace, add
`"files.encoding": "utf8"` to `.vscode/settings.json`. The value
`"utf8"` means no BOM; `"utf8bom"` would add one. To scope the
setting to PowerShell files only, use a `"[powershell]"`
language-specific override:

  ```json
  {
      "[powershell]": {
          "files.encoding": "utf8"
      }
  }
  ```

After making the above changes, advance the `STYLE_GUIDE.md`
version number (in the `**Version:**` field at the top of the
file) per the versioning rules in the "Function and Script
Versioning" section (increment the Minor version and update the
Build date to the current date in YYYYMMDD format).</
issue_description>

## Comments on the Issue (you are @copilot in this section)

<comments>
</comments>
</problem_statement>
````

Implement the necessary changes to the repository so that the requirements specified in the <problem_statement> are met.