051bdc10-e1a4-4d84-a7ae-ec76726d4d04

<prev_user>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'stegripe/rawon' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/rawon/rawon (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2025-12-24T09:32:22.748Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
feat: implement browser-based YouTube cookie extraction
</pr_title>

<pr_description>
Browser-Based YouTube Cookie Extraction

This PR implements a browser-based approach to extract YouTube cookies automatically, eliminating the need for manual cookie export.

How It Works

1. **Start login session**: Run `ytcookies login` in Discord
2. **Connect remotely**: Open `chrome://inspect` in Chrome, add

server:port, and click inspect
3. **Login to Google**: Complete the Google login in the remote browser window
4. **Save cookies**: Run `ytcookies save` to extract and save cookies to file

New Files
- `src/utils/handlers/YouTubeCookieManager.ts` - Manages browser sessions and cookie extraction
- `src/commands/developers/YTCookiesCommand.ts` - Discord command for cookie management
- `.dockerignore` - Reduces Docker build context size by excluding node_modules, dist, cache, etc.

Modified Files
- `Dockerfile` - Added Chromium and dependencies for headless browser
- `src/config/env.ts` - Added `enableBrowserLogin` config
- `optional.env_example` - Added browser login environment variables (all ports now configurable)
- `docker-compose.yaml` - Updated port mappings to use env variables

New Environment Variables
- `ENABLE_BROWSER_LOGIN` - Enable/disable browser login feature (default: no)
- `BROWSER_DEBUG_PORT` - Port for Chrome remote debugging (default: 9222)
- `BROWSER_INSTRUCTIONS_PORT` - Port for the instructions page (default: 9223)
- `PUBLIC_HOST` - Public hostname/IP for accessing remote browser

Commands
- `ytcookies status` - Show current cookie status
- `ytcookies login` - Start browser login session
- `ytcookies save` - Save cookies from active session
- `ytcookies cancel` - Cancel active login session
- `ytcookies clear` - Clear all stored cookies

Security
- Feature is disabled by default
- Users are warned to use throwaway Google accounts
- Browser data is stored in `cache/browser-data/`
- Login sessions auto-expire after 10 minutes
- URL validation uses proper hostname parsing to prevent URL substring attacks

- Port validation ensures valid port range (1-65535)

Docker Setup (if using browser login)
1. Add to your `.env`:
   ```
   ENABLE_BROWSER_LOGIN=yes
   BROWSER_DEBUG_PORT=9222
   BROWSER_INSTRUCTIONS_PORT=9223
   PUBLIC_HOST=your-server-ip
   ```
2. Uncomment ports in docker-compose.yaml:
   ```yaml
   ports:
     - "${BROWSER_DEBUG_PORT:-9222}:${BROWSER_DEBUG_PORT:-9222}"
     - "${BROWSER_INSTRUCTIONS_PORT:-9223}:$
{BROWSER_INSTRUCTIONS_PORT:-9223}"
   ```

</pr_description>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

ruksi (default: 9223)

2. **docker-compose.yaml** sudah diupdate untuk pakai env variables:
   ```yaml
   ports:
     - "${BROWSER_DEBUG_PORT:-9222}:${BROWSER_DEBUG_PORT:-9222}"
     - "${BROWSER_INSTRUCTIONS_PORT:-9223}:${BROWSER_INSTRUCTIONS_PORT:-9223}"
   ```

3. **optional.env_example** sudah lengkap dengan dokumentasi semua env variables.

Build sebelumnya di-cancel (bukan error) - coba build ulang sekarang.
</comment_old>

<comment_old>
<author>@Fab1o0107</author>
@copilot ADDUHHH ERROR APASIH INI DARI TADI BUKANNYA LU FIXXX

PS C:\Users\mozartrafi\Nextcloud\Coding\stegripe\rawon> docker compose build

```
Compose can now delegate builds to bake for better performance.
 To do so, set COMPOSE_BAKE=true.
[+] Building 204.9s
(16/27)
                docker:desktop-linux
 =&gt; [rawon internal] load build definition from
Dockerfile
    0.1s
 =&gt; =&gt; transferring dockerfile:
2.20kB
                     0.0s
 =&gt; [rawon internal] load metadata for ghcr.io/hazmi35/
node:24-alpine
2.3s
 =&gt; [rawon internal] load metadata for ghcr.io/hazmi35/
node:24-dev-alpine
2.2s
 =&gt; [rawon internal]
load .dockerignore
                                0.1s
 =&gt; =&gt; transferring context:
442B
                       0.0s
 =&gt; [rawon build-stage  1/11] FROM ghcr.io/hazmi35/node:24-
dev-alpine@sha256:1318c7745e4e66c13b2a0636dff90c9d362d  136.3s
 =&gt; =&gt; resolve ghcr.io/hazmi35/node:24-dev-
alpine@sha256:1318c7745e4e66c13b2a0636dff90c9d362d1cc8c036268677
fbf81d4c  0.1s
 =&gt; =&gt;
sha256:4ef4916cde0575eba6f5aa2a24f80bbbce8590d235b602fffe71422d4
e28fa40 117.73MB / 117.73MB                 133.3s
 =&gt; =&gt; extracting
sha256:4ef4916cde0575eba6f5aa2a24f80bbbce8590d235b602fffe71422d4
e28fa40                                2.2s
 =&gt; =&gt; extracting
sha256:46c19f1be3b92fea9782ea21f3e05e942d6bec13f2f3f69d798e0a108
fa28d4f                                0.0s
 =&gt; =&gt; extracting
sha256:f69916d4651fe236a508d54e0a63d280a99aaabfef5b0c4b87474750b
c2bb66a                                0.0s
 =&gt; [rawon stage-1  1/11] FROM ghcr.io/hazmi35/node:24-
alpine@sha256:ff75a1ed9eb8ae9b1809ae415acca2a7cc3a25cc523768
1.5s
 =&gt; =&gt; resolve ghcr.io/hazmi35/node:24-alp...
</comment_old>

<comment_old>
```

<author>@copilot</author>

> @copilot ADDUHHH ERROR APASIH INI DARI TADI BUKANNYA LU FIXXX
>
> PS C:\Users\mozartrafi\Nextcloud\Coding\stegripe\rawon> docker compose build...

Log yang ditampilkan tidak menunjukkan error - build masih berjalan. `Building 204.9s (16/27)` artinya sedang di step 16 dari 27.

Proses yang terlihat:
- Download base image (117.73MB) ✓
- Extracting layers ✓
- Stage-1 starting...

Ini normal untuk build pertama kali karena harus download Chromium dan dependencies (~200MB+). Tunggu sampai selesai. Kalau ada error, akan muncul `ERROR` dengan pesan merah.

Kalau build gagal dengan actual error message, tolong kirim log lengkapnya termasuk pesan error-nya.
</comment_old>

<comment_new>
<comment_id>3689244271</comment_id>
<author>@Fab1o0107</author>
@copilot ITU ERROR BENGAKKKK!!! LANGSUNG EXITED PROCESSSNYAA BUTA!!
</comment_new>

</pr_comments>

</comments>

The last **14** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement>

Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.

```
* For each new comment, determine:
    - If it a request for changes, a question on the code or a
suggestion.
    - Is it addressed to you or someone else, e.g. "Hey
@username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can
stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and
ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>
```

```
A **CI/Build Failure** has been mentioned in the problem statement,
make sure to follow your instructions for addressing CI/Build
Failures.
```

<prev_assistant>

I've asked the user for more details about the actual error since the build log they shared was truncated and didn't show the actual error message. The log showed the build was at step 16/27 which indicates it was still in progress, not that it had failed with an error. Without seeing the actual error message (which would be prefixed with `ERROR` in Docker build output), I cannot determine what needs to be fixed.

<current>

<request>

```
You have been given comments on the previous commits you made in the
repository.

You are working on an issue in the 'stegripe/rawon' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/rawon/
rawon (not in /tmp/inputs). Always use absolute paths when referring
to files in the repository.
</repository_context>
```

<current_datetime>2025-12-24T09:34:25.760Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
feat: implement browser-based YouTube cookie extraction
</pr_title>

<pr_description>
Browser-Based YouTube Cookie Extraction

This PR implements a browser-based approach to extract YouTube cookies automatically, eliminating the need for manual cookie export.

How It Works

1. **Start login session**: Run `ytcookies login` in Discord
2. **Connect remotely**: Open `chrome://inspect` in Chrome, add server:port, and click inspect
3. **Login to Google**: Complete the Google login in the remote browser window
4. **Save cookies**: Run `ytcookies save` to extract and save cookies to file

New Files
- `src/utils/handlers/YouTubeCookieManager.ts` - Manages browser sessions and cookie extraction
- `src/commands/developers/YTCookiesCommand.ts` - Discord command for cookie management
- `.dockerignore` - Reduces Docker build context size by excluding node_modules, dist, cache, etc.

Modif...
</pr_description>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

ke rawon lalu rawon memanfaatkannya untuk acting seakan buka youtube di browser dan grab cookiesnya.
</comment_old>

<comment_old>
<author>@copilot</author>

> @copilot iya, bisa gak implementasi bikin browser agent dalam rawon biar orang bisa login googlenya ke rawon lalu rawon memanfaatkannya untuk acting seakan buka youtube di browser dan grab cookiesnya.

Secara teknis **bisa**, tapi ada beberapa masalah:

Pros:
- User bisa login Google sekali, cookies di-extract otomatis
- Tidak perlu extension browser/export manual

Cons:
1. **Docker Alpine** - Image saat ini pakai Alpine, susah install Chromium. Perlu ganti ke Debian-based image (ukuran lebih besar)
2. **Resource berat** - Headless browser butuh ~200-500MB RAM tambahan
3. **Security risk** - Menyimpan session Google di bot berisiko. Kalau bot di-hack, akun Google juga kena
4. **Google anti-bot** - Google punya deteksi bot yang ketat. Headless browser sering di-block, apalagi dari IP data center (OVH)
5. **2FA/CAPTCHA** - Kalau akun pakai 2FA atau kena CAPTCHA, flow-nya jadi kompleks

Mau tetap diimplementasikan? Saya bisa buat, tapi perlu:
- Ubah Dockerfile ke Debian-based
- Install Puppeteer + Chromium
- Buat web interface untuk login flow
- Handle cookies extraction dan auto-renewal

Konfirmasi dulu apakah trade-off di atas acceptable.
</comment_old>

<comment_old>
<author>@Fab1o0107</author>
@copilot bodoamat, bikin aja seluruh fitur ini togglable di env file. kita kan juga udah warn untuk orang makek akun tumbal aja, persetan lah kalau soal keamanan.
</comment_old>

<comment_old>
<author>@copilot</author>

> @copilot bodoamat, bikin aja seluruh fitur ini togglable di env file. kita kan juga udah warn untuk orang makek akun tumbal aja, persetan lah kalau soal keamanan.

Sudah diimplementasikan di commit `8b44bcb`.

Fitur baru:
- Command `ytcookies` untuk manage cookies via Discord
- Browser-based login via Chrome DevTools remote debugging
- Auto-extract cookies setelah login berhasil

Cara pakai:
1. Set `ENABLE_BROWSER_LOGIN=yes` di .env
2. Uncomment ports di docker-compose.yaml

```
3. Jalankan `ytcookies login` di Discord
4. Buka `chrome://inspect` di browser, tambahkan `server-
ip:9222`
5. Klik "inspect", login Google di remote browser
6. Jalankan `ytcookies save` untuk simpan cookies

**Commands:**
- `ytcookies status` - Cek status cookies
- `ytcookies login` - Mulai browser session
- `ytcookies save` - Simpan cookies
- `ytcookies cancel` - Batalkan session
- `ytcookies clear` - Hapus cookies

Feature disabled by default. Butuh Chromium di Docker (sudah
ditambahkan ke Dockerfile).
</comment_old>

<comment_old>
<author>@Fab1o0107</author>
@copilot PS C:
\Users\mozartrafi\Nextcloud\Coding\stegripe\rawon&gt; docker
compose build
Compose can now delegate builds to bake for better performance.
 To do so, set COMPOSE_BAKE=true.
[+] Building 18.5s
(9/27)
                 docker:desktop-linux
 =&gt; [rawon internal] load build definition from
Dockerfile
    0.0s
 =&gt; =&gt; transferring dockerfile:
2.20kB
                    0.0s
 =&gt; WARN: FromAsCasing: 'as' and 'FROM' keywords' casing do
not match (line 1)                                      0.0s
 =&gt; [rawon internal] load metadata for ghcr.io/hazmi35/
node:24-alpine
1.1s
 =&gt; [rawon internal] load metadata for ghcr.io/hazmi35/
node:24-dev-alpine
1.1s
 =&gt; [rawon internal]
load .dockerignore
                                0.0s
 =&gt; =&gt; transferring context:
2B
                       0.0s
```

=> [rawon build-stage 1/11] FROM ghcr.io/hazmi35/node:24-dev-alpine@sha256:1318c7745e4e66c13b2a0636dff90c9d362d1 16.8s
=> => resolve ghcr.io/hazmi35/node:24-dev-alpine@sha256:1318c7745e4e66c13b2a0636dff90c9d362d1cc8c036268677fbf81d4c 0.1s
=> => sha256:4ef4916cde0575eba6f5aa2a24f80bbbce8590d235b602fffe71422d4e28fa40 40.89MB / 117.73MB 17.1s
=> ERROR [rawon internal] load build context
16.6s
=> => transferring context: 367.60MB
16.5s
=> CACHED [rawon stage-1 1/11] FROM ghcr.io/hazmi35/node:24-alpine@sha256:ff75a1ed9eb8ae9b1809ae415acca2a7cc3a25c 0.1s
=> => resolve ghcr.io/hazmi35/node:24-alpine@sha256:ff75a1ed9eb8ae9b1809ae415acca2a7cc3a25cc5...
</comment_old>

<comment_old>
<author>@copilot</author>

> @copilot PS C:\Users\mozartrafi\Nextcloud\Coding\stegripe\rawon> docker compose build
> Compose can now delegate builds to bake for better performance.
> To do so, set COMPOSE_BAKE=true....

Fixed di commit `f495261`:

1. **FromAsCasing warning** - Fixed `as` → `AS` di Dockerfile line 1
2. **Build context 367MB** - Ditambahkan `.dockerignore` untuk exclude `node_modules`, `dist`, `cache`, dll. Build context sekarang harusnya jauh lebih kecil.

Coba build ulang.
</comment_old>

<comment_old>
<author>@Fab1o0107</author>
@copilot PS C:\Users\mozartrafi\Nextcloud\Coding\stegripe\rawon> docker compose build

```
Compose can now delegate builds to bake for better performance.
 To do so, set COMPOSE_BAKE=true.
[+] Building 3.3s
(16/27)
                  docker:desktop-linux
 =&gt; [rawon internal] load build definition from
Dockerfile
    0.0s
 =&gt; =&gt; transferring dockerfile:
2.20kB
                     0.0s
 =&gt; [rawon internal] load metadata for ghcr.io/hazmi35/
node:24-alpine
1.0s
 =&gt; [rawon internal] load metadata for ghcr.io/hazmi35/
node:24-dev-alpine
1.0s
 =&gt; [rawon internal]
load .dockerignore
                                0.0s
 =&gt; =&gt; transferring context:
442B
                       0.0s
 =&gt; [rawon internal] load build
context
                     0.1s
 =&gt; =&gt; transferring context:
45.55kB
                       0.1s
 =&gt; [rawon build-stage  1/11] FROM ghcr.io/hazmi35/node:24-
dev-alpine@sha256:1318c7745e4e66c13b2a0636dff90c9d362d1c  0.1s
 =&gt; =&gt; resolve ghcr.io/hazmi35/node:24-dev-
alpine@sha256:1318c7745e4e66c13b2a0636dff90c9d362d1cc8c036268677
fbf81d4c  0.1s
 =&gt; CACHED [rawon stage-1  1/11] FROM ghcr.io/hazmi35/
node:24-alpine@sha256:ff75a1ed9eb8ae9b1809ae415acca2a7cc3a25c
0.1s
 =&gt; =&gt; resolve ghcr.io/hazmi35/node:24-
alpine@sha256:ff75a1ed9eb8ae9b1809ae415acca2a7cc3a25cc5237684ba8
dcd3563ae0bd  0.1s
 =&gt; CANCELED [rawon stage-1  2/11] RUN apk add --no-cache
ffmpeg     python3     deno     chromium     nss       2.0s
 =&gt; CACHED [rawon build-stage  2/11] RUN corepack enable
&amp;&amp; corepack prepare pnpm@latest      ...
</comment_old>

<comment_old>
```

<author>@Fab1o0107</author>
@copilot itu ada error bengak. udah gitu ini lu bikin tutornya jelas jelas lah, kok port nya cuma 1 aja yg bisa dicustom, sisanya malah jadi kek port bawaan, env nya lengkap lengkap lah.
</comment_old>

<comment_old>
<author>@copilot</author>

> @copilot itu ada error bengak. udah gitu ini lu bikin tutornya jelas jelas lah, kok port nya cuma 1 aja yg bisa dicustom, sisanya malah jadi kek port bawaan, env nya lengkap lengkap lah.

Fixed di commit `edff6dd`:

1. **Kedua port sekarang bisa dikonfigurasi via env:**
   - `BROWSER_DEBUG_PORT` - Port untuk Chrome DevTools (default: 9222)
   - `BROWSER_INSTRUCTIONS_PORT` - Port untuk halaman instruksi (default: 9223)

2. **docker-compose.yaml** sudah diupdate untuk pakai env variables:
   ```yaml
   ports:
     - "${BROWSER_DEBUG_PORT:-9222}:${BROWSER_DEBUG_PORT:-9222}"
     - "${BROWSER_INSTRUCTIONS_PORT:-9223}:${BROWSER_INSTRUCTIONS_PORT:-9223}"
   ```

3. **optional.env_example** sudah lengkap dengan dokumentasi semua env variables.

Build sebelumnya di-cancel (bukan error) - coba build ulang sekarang.
</comment_old>

<comment_old>
<author>@Fab1o0107</author>
@copilot ADDUHHH ERROR APASIH INI DARI TADI BUKANNYA LU FIXXX

PS C:\Users\mozartrafi\Nextcloud\Coding\stegripe\rawon> docker compose build
Compose can now delegate builds to bake for better performance.
 To do so, set COMPOSE_BAKE=true.
[+] Building 204.9s

```
(16/27)
                docker:desktop-linux
 =&gt; [rawon internal] load build definition from
Dockerfile
    0.1s
 =&gt; =&gt; transferring dockerfile:
2.20kB
                    0.0s
 =&gt; [rawon internal] load metadata for ghcr.io/hazmi35/
node:24-alpine
2.3s
 =&gt; [rawon internal] load metadata for ghcr.io/hazmi35/
node:24-dev-alpine
2.2s
 =&gt; [rawon internal]
load .dockerignore
                               0.1s
 =&gt; =&gt; transferring context:
442B
                      0.0s
 =&gt; [rawon build-stage  1/11] FROM ghcr.io/hazmi35/node:24-
dev-alpine@sha256:1318c7745e4e66c13b2a0636dff90c9d362d  136.3s
 =&gt; =&gt; resolve ghcr.io/hazmi35/node:24-dev-
alpine@sha256:1318c7745e4e66c13b2a0636dff90c9d362d1cc8c036268677
fbf81d4c  0.1s
 =&gt; =&gt;
sha256:4ef4916cde0575eba6f5aa2a24f80bbbce8590d235b602fffe71422d4
e28fa40 117.73MB / 117.73MB                133.3s
 =&gt; =&gt; extracting
sha256:4ef4916cde0575eba6f5aa2a24f80bbbce8590d235b602fffe71422d4
e28fa40                            2.2s
 =&gt; =&gt; extracting
sha256:46c19f1be3b92fea9782ea21f3e05e942d6bec13f2f3f69d798e0a108
fa28d4f                            0.0s
 =&gt; =&gt; extracting
sha256:f69916d4651fe236a508d54e0a63d280a99aaabfef5b0c4b87474750b
c2bb66a                            0.0s
 =&gt; [rawon stage-1  1/11] FROM ghcr.io/hazmi35/node:24-
alpine@sha256:ff75a1ed9eb8ae9b1809ae415acca2a7cc3a25cc523768
1.5s
 =&gt; =&gt; resolve ghcr.io/hazmi35/node:24-alp...
</comment_old>

<comment_old>
<author>@copilot</author>

&gt; @copilot ADDUHHH ERROR APASIH INI DARI TADI BUKANNYA LU
```

FIXXX
>
> PS C:\Users\mozartrafi\Nextcloud\Coding\stegripe\rawon> docker compose build...

Log yang ditampilkan tidak menunjukkan error - build masih berjalan. `Building 204.9s (16/27)` artinya sedang di step 16 dari 27.

Proses yang terlihat:
- Download base image (117.73MB) ✓
- Extracting layers ✓
- Stage-1 starting...

Ini normal untuk build pertama kali karena harus download Chromium dan dependencies (~200MB+). Tunggu sampai selesai. Kalau ada error, akan muncul `ERROR` dengan pesan merah.

Kalau build gagal dengan actual error message, tolong kirim log lengkapnya termasuk pesan error-nya.
</comment_old>

<comment_old>
<author>@Fab1o0107</author>
@copilot ITU ERROR BENGAKKKK!!! LANGSUNG EXITED PROCESSSNYAA BUTA!!
</comment_old>

<comment_old>
<author>@copilot</author>

> @copilot ITU ERROR BENGAKKKK!!! LANGSUNG EXITED PROCESSSNYAA BUTA!!

Log yang ditampilkan terpotong di tengah - tidak ada error message yang terlihat. Tolong jalankan build lagi dan kirim **full output** termasuk baris yang menunjukkan `ERROR` atau pesan merah.

Jalankan: `docker compose build 2>&1 | tee build.log` lalu share isi `build.log` atau screenshot yang menunjukkan error-nya.
</comment_old>

<comment_new>
<comment_id>3689248724</comment_id>
<author>@Fab1o0107</author>
@copilot buta map lu bgst, jelas jelas ini errornya

```
=&gt; ERROR [rawon build-stage  9/11] RUN pnpm run
build
       1.6s
------
 &gt; [rawon build-stage  9/11] RUN pnpm run build:
0.890
0.890 &gt; rawon@4.2.0 build /tmp/build
0.890 &gt; pnpm run lint &amp;&amp; pnpm run compile
0.890
1.382
1.382 &gt; rawon@4.2.0 lint /tmp/build
1.382 &gt; biome check .
1.382
1.482 /tmp/build internalError/fs
━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━
━━━━━━━━━━
1.482
1.482   × Biome couldn't find an ignore file in the
following folder: /tmp/build
1.482
1.482
1.483 configuration
━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━
━━━━━━━━━━━━━━━━━━━━━━━━
1.483
1.483   × Biome exited because the configuration resulted in
errors. Please fix them.
1.483
1.483
1.503  ELIFECYCLE  Command failed with exit code 1.
1.536  ELIFECYCLE  Command failed with exit code 1.
------
failed to solve: process "/bin/sh -c pnpm run build" did not
complete successfully: exit code:
</comment_new>
```

```
</pr_comments>

</comments>

----
The last **14** git commits in this branch are the changes you
have made so far. Use those as your change commit history.
</problem_statement>
```

```
Analyze and determine if action or explanation is needed
<rules_for_making_changes>
```

```
* Start by fully understanding <problem_statement> and the
<comments> before making any changes. You will only address the
<comment_new> comments. Reply to new comments as you address them.
Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a
suggestion.
    - Is it addressed to you or someone else, e.g. "Hey
@username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can
stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and
ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>




A **CI/Build Failure** has been mentioned in the problem statement,
make sure to follow your instructions for addressing CI/Build
Failures.
```