112570fd-33dd-4b73-91df-7523fed7ef

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'atusy/treesitter-ls' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/treesitter-ls/treesitter-ls (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-01-03T05:51:50.446Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the stacked pull request you are creating to address the problem above.

<pr_title>
[WIP] Address feedback on timeout controls for auto-install metadata checks
</pr_title>

<pr_description>
Thanks for the feedback on #32. I've created this new PR, which merges into #32, to address your comment. I will work on the changes and keep this PR's description up to date as I make progress.

Original PR: #32
Triggering review: https://github.com/atusy/treesitter-ls/pull/32#discussion_r2658740909
> @copilot open a new pull request to apply changes based on this feedback

```
</pr_description>

----
This stacked PR was created to address a specific review comment
on a different pull request.
Focus on addressing the feedback in the review thread below.

## Comments on the PR (you are @copilot in this section)

<comments>

<comment_thread>
<file>src/lsp/auto_install.rs:238-240</file>
<original_commit>9da3ac9b48d9d438fdeb54a3e34607371f73382c</
original_commit>

<comment_old>
<author>copilot-pull-request-reviewer[bot]</author>
The variable name `language_for_check` is redundant since
`owned_language` already exists and could be cloned directly in
the closure. The intermediate variable doesn't add clarity and
makes the code slightly more verbose. Consider cloning
`owned_language` directly in the `spawn_blocking` closure
instead.
</comment_old>

  <comment_new>
  <comment_id>2658740909</comment_id>
  <author>@atusy</author>
  @copilot open a new pull request to apply changes based on
  <a href="https://github.com/atusy/treesitter-ls/pull/
  32#discussion_r2658739015">this feedback</a>
  </comment_new>

</comment_thread>

</comments>

----
The last **5** git commits in this branch are the changes you
have made so far. Use those as your change commit history.
</problem_statement>


Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the
<comments> before making any changes. You will only address the
```

```
<comment_new> comments. Reply to new comments as you address them.
Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a
suggestion.
    - Is it addressed to you or someone else, e.g. "Hey
@username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can
stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and
ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>
```