17da01e1-62f7-4e26-b2cd-2c93d40078ff

<current>

<request>

You are working on an issue in the 'intrafind/ihub-apps' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/ihub-apps/ihub-apps (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-05-29T09:06:29.256+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>

This section details on the original issue you should resolve

<issue_title>Clarify what "add selected mails" does.</issue_title>
<issue_description>Clarify what "add selected mails" does. it feels duplicated with the "add this mail"</issue_description>

Comments on the Issue (you are @claude[agent] in this section)

<comments>
</comments>
</problem_statement>

Implement the necessary changes to the repository so that the requirements specified in the <problem_statement> are met.

<system_reminder>You have the capability to call multiple tools in a single response.

For maximum efficiency, whenever you need to perform multiple independent operations, ALWAYS call tools simultaneously whenever the actions can be done in parallel rather than sequentially (e.g. multiple reads/edits to different files). Especially when exploring repository, searching, reading files, viewing directories, validating changes. For example, you can read 3 different files in parallel, or edit different files in parallel. However, if some tool calls depend on previous calls to inform dependent values like the parameters, do NOT call these tools in parallel and instead call them sequentially (e.g. reading shell output from a previous command should be sequential as it requires the sessionID).</system_reminder>