204d7fb5-72e2-4b22-9a34-a3482717d85c

<prev_user>

<request>

You are working on a task in the 'wiresock/amneziawg-install' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/amneziawg-install/amneziawg-install (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-16T13:59:27.699Z</current_datetime>

Consider the following problem statement:

<problem_statement>
apply changes based on the comments in this thread https://github.com/wiresock/amneziawg-install/pull/42#pullrequestreview-4119129200
</problem_statement>

First, determine whether the <problem_statement> requires code changes, an explanation, a plan, or analysis. Then follow the appropriate path:

If the task requires code changes:

If the task is a question or only requires creating a plan or analysis: respond directly without making code changes.

<prev_assistant>

All 3 changes from review `4119129200` were already applied in the previous session:

- **Bracketed IPv4 rejection** — `_is_valid_ip_literal()` now rejects `[127.0.0.1]`-style inputs since brackets are IPv6-only in SocketAddr; passing one through would produce `[127.0.0.1]:port` which fails Rust `SocketAddr` parsing at runtime (lines 940–945).
- **Regression tests** — 3 tests asserting `[127.0.0.1]`, `[0.0.0.0]`, and `[192.168.1.1]` are rejected (lines 352–355).
- **Path `"` / `\` rejection** — `non_interactive_validate()` now rejects quotes and backslashes in `--install-dir`, `--config-file`, `--data-dir`, and `--awg-dir` to prevent systemd unit parsing breakage and sed substitution failures (lines 1108–1110).

119/119 tests pass.

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'wiresock/amneziawg-install' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/amneziawg-install/amneziawg-install (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-16T19:26:25.098Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
Copilot/add udp proxy install script

</pr_title>

<pr_description>

</pr_description>

<stacked_pr_context>
The pull request you are currently working on is a stacked pull request on top of another pull request. The base branch is `copilot/add-udp-proxy-for-amneziawg`, not the default branch `main`. A pull request has already been created for your branch. Do not attempt to create a new pull request. If you are asked to fix CI, build, test, or workflow failures, check the GitHub Actions workflow runs for the original branch (`copilot/add-udp-proxy-for-amneziawg`) first. If you don't find relevant failures there, then check your branch (`copilot/add-udp-proxy-install-script`).
</stacked_pr_context>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_old>
<author>@copilot-pull-request-reviewer</author>
Pull request overview

Adds an install/uninstall + management entrypoint for `amneziawg-proxy` (UDP obfuscation proxy), along with CI-backed unit tests and a systemd service template to support safe deployment on systemd-based Linux hosts.

Changes:
- Introduces `amneziawg-proxy-install.sh` and `amneziawg-proxy-uninstall.sh` scripts (including systemd unit installation and safe purge/restore helpers).
- Adds `amneziawg-proxy.sh` as a single entrypoint that installs or shows a management menu when already installed.
- Adds a dedicated proxy script unit-test suite and wires it into GitHub Actions test + lint workflows.

Reviewed changes

Copilot reviewed 7 out of 7 changed files in this pull request

```
and generated 3 comments.




---

💡 <a>Add Copilot custom instructions</a> for smarter, more
guided reviews. <a href="https://docs.github.com/en/copilot/
customizing-copilot/adding-repository-custom-instructions-for-
github-copilot">Learn how to get started</a>.
</comment_old>

</pr_comments>

<pr_reviews>

<comment_thread>
<file>amneziawg-proxy/scripts/amneziawg-proxy-
uninstall.sh:96-118</file>
<original_commit>5b9557d</original_commit>

<comment_old>
<author>@copilot-pull-request-reviewer</author>
Argument parsing runs at top-level, so sourcing this script will
consume/shift the caller’s positional parameters and potentially
alter behavior. Since the test suite (and possibly other
tooling) sources this file to call helper functions, move the
`while [[ $# -gt 0 ]]` parsing into `main()` (or guard it with
`if [[ "${BASH_SOURCE[0]}" == "${0}" ]]`) to avoid side effects
when sourced.
```suggestion
if [[ "${BASH_SOURCE[0]}" == "${0}" ]]; then
    while [[ $# -gt 0 ]]; do
        case "$1" in
            --install-dir)
                [[ $# -ge 2 ]] || die "Missing value for option:
$1  (use --help for usage)"
                INSTALL_DIR="$2"; shift 2 ;;
            --config-file)
                [[ $# -ge 2 ]] || die "Missing value for option:
$1  (use --help for usage)"
                CONFIG_FILE="$2"; CONFIG_DIR="$(dirname "$
```
```

```
{CONFIG_FILE}")"; shift 2 ;;
            --data-dir)
                [[ $# -ge 2 ]] || die "Missing value for option:
$1  (use --help for usage)"
                DATA_DIR="$2"; shift 2 ;;
            --awg-dir)
                [[ $# -ge 2 ]] || die "Missing value for option:
$1  (use --help for usage)"
                AWG_DIR="$2"; shift 2 ;;
            --purge-config)     PURGE_CONFIG="true"; shift ;;
            --purge-data)       PURGE_DATA="true"; shift ;;
            --restore-awg)      RESTORE_AWG="true"; shift ;;
            --force)            FORCE="true"; shift ;;
            --non-interactive)  FORCE="true"; shift ;;
            --help|-h)          usage; exit 0 ;;
            *) die "Unknown option: $1  (use --help for
usage)" ;;
        esac
    done
fi
```
</comment_old>

</comment_thread>

<comment_thread>
<file>amneziawg-proxy/scripts/amneziawg-proxy-
uninstall.sh:638-643</file>
<original_commit>5b9557d</original_commit>

<comment_old>
<author>@copilot-pull-request-reviewer</author>
For the exact default data directory purge case, the safety boundary passed to `safe_rm_dir` is widened to `/var/lib/` via `$(dirname "${DEFAULT_DATA_DIR}")/`. This weakens the defense-in-depth of `safe_rm_dir` compared to the config purge path (which uses the narrow default dir as prefix). Use `${DEFAULT_DATA_DIR}` (or `${DEFAULT_DATA_DIR}/`) as the prefix here as well so an accidental/bypassed validation can’t result in removing unrelated directories under `/var/lib`.
</comment_old>

</comment_thread>

<comment_thread>
<file>tests/test-proxy-scripts.sh:465</file>
<original_commit>5b9557d</original_commit>

<comment_old>
<author>@copilot-pull-request-reviewer</author>
`run_niv_with` sets `AWG_DIR` to `/etc/amnezia/awg`, but the installer’s actual default AWG directory is `/etc/amnezia/amneziawg`. Using a non-default path in the “sane defaults” block makes the test harder to interpret and can drift from real-world behavior; set this default to match the installer constant unless the difference is intentional (in which case add a short comment explaining why).
```suggestion
        AWG_DIR="/etc/amnezia/amneziawg"
```
</comment_old>

</comment_thread>

</pr_reviews>

<pr_comments>

<comment_new>
<comment_id>4262823483</comment_id>
<author>@wiresock</author>
@copilot apply changes based on the comments in this thread
</comment_new>

</pr_comments>

</comments>

The last **51** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement><rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.
    - Is it addressed to you or someone else, e.g. "Hey @username, ..." or "@username can you ...".
    - Is it a general comment or praise.

```
* If there are no comments you need to address or reply to, you
can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment
and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>




A **CI/Build Failure** has been mentioned in the problem
statement, make sure to follow your instructions for addressing
CI/Build Failures.
```