# 2d9fa852-a7d6-44b3-9783-ec75c83c0d1d

**<current>**

**<request>**

```
You are working on an issue in the 'Kong/kongctl' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/
kongctl/kongctl (not in /tmp/inputs). Always use absolute paths when
referring to files in the repository.
</repository_context>

<current_datetime>2026-02-26T16:34:30.463Z</current_datetime>

Consider the following problem statement:

  <problem_statement>

  ----

  *This section details on the original issue you should resolve*

  <issue_title>[simplifier] Code Simplification - 2026-02-26</
  issue_title>
  <issue_description>This issue recommends code simplification to
  recently modified code to improve clarity, consistency, and
  maintainability while preserving all functionality.

  ### Files to Simplify

  - `internal/cmd/root/products/konnect/declarative/
  declarative.go` — Extract duplicated stdin/TTY conflict-check
  block into a shared helper function

  ### Improvements Recommended

  #### 1. Eliminate Triple-Duplicated stdin Detection Block

  The following 27-line block appears **identically** in three
  functions — `runApply` (line ~1083), `runDelete` (line ~1579),
```

````
and `runSync` (line ~1821):

```go
// Early check for stdin usage without auto-approve
// Only fail if we can't access /dev/tty for interactive input
var usingStdinForInput bool
if !dryRun && !autoApprove {
    // Check if stdin will be used for plan or configuration
    if planFile == "-" {
        usingStdinForInput = true
    } else if planFile == "" {
        // Check if stdin will be used for configuration
        for _, filename := range filenames {
            if filename == "-" {
                usingStdinForInput = true
                break
            }
        }
    }

    // If using stdin, ensure we can get interactive input via /
dev/tty
    if usingStdinForInput {
        tty, err := os.Open("/dev/tty")
        if err != nil {
            return fmt.Errorf("cannot use stdin for input
without --auto-approve flag " +
                "(no terminal available for interactive
confirmation). " +
                "Use --auto-approve to skip confirmation when
piping commands")
        }
        tty.Close()
    }
}
```

**Proposed helper function** (add to `declarative.go` alongside
other helpers):

```go
// checkStdinApprovalConflict returns an error if stdin is being
used as input
// while interactive confirmation is required (no auto-approve
or dry-run).
// planFile is the --plan flag value; filenames are the --
filename flag values.
````
````

```
func checkStdinApprovalConflict(planFile string, filenames
[]string) error {
    usingStdin := planFile == "-" || (planFile == "" &&
slices.Contains(filenames, "-"))
    if !usingStdin {
        return nil
    }
    tty, err := os.Open("/dev/tty")
    if err != nil {
        return fmt.Errorf("cannot use stdin for input without --
auto-approve flag " +
            "(no terminal available for interactive
confirmation). " +
            "Use --auto-approve to skip confirmation when piping
commands")
    }
    tty.Close()
    return nil
}
```

**Replacement at each of the three call sites** (inside `if !
dryRun && !autoApprove`):

```go
if !dryRun && !autoApprove {
    if err := checkStdinApprovalConflict(planFile, filenames);
err != nil {
        return err
    }
}
```

Also add `"slices"` to the import block for the
`slices.Contains` call.

> Note: `usingStdinForInput` is also used later in each
function (e.g. to gate interactive confirmation prompts). The
`checkStdinApprovalConflict` helper only replaces the **early
TTY availability check**; the boolean itself is still needed
later and should be computed separately — or
`checkStdinApprovalConflict` can be extended to also return the
bool if desired.

#### 2. Apply project-standard `slices.Contains` for the
filename check (within the same block)

While extracting the helper, replace the manual loop:

```go
for _, filename := range filenames {
    if filename == "-" {
        usingStdinForInput = true
        break
    }
}
```

with the idiomatic:

```go
usingStdinForInput = slices.Contains(filenames, "-")
```

This is consistent with the modernization already applied across the codebase in recent PRs (#481–#483, Kong/kongctl#488).

### Changes Based On

Recent changes from:
- Kong/kongctl#475 — Task: code simplification consolidate duplicate patterns in lint, listen, and flag parsing
- Kong/kongctl#485 — fix: resolve QF1003 staticcheck linting errors in declarative commands
- Kong/kongctl#479 — Task: Upgrade go to 1.26.0 and `go fix` modernization
- Kong/kongctl#481, Kong/kongctl#482, Kong/kongctl#483, Kong/kongctl#488 — Modernize: Applied codebase-wide modernizations (any, rangeint, slices, mapsloop)

### Implementor Must Ensure

- ✅ Format passes (`make format` produces no changes)
- ✅ Build succeeds (`make build`)
- ✅ Linting passes (`make lint`)
- ✅ All tests pass (`make test-all`)
- ✅ No functional changes — behavior is identical

### Review Focus

Please verify:
- Functionality is preserved (all three commands — apply, delete, sync — still reject stdin input when TTY is unavailable and auto-approve is not set)

```
- The `usingStdinForInput` bool used **later** in each function
is still correctly set (it is separate from the early TTY check)
- Simplifications improve code quality
- Changes align with project conventions (slices stdlib, helper
extraction patterns)
- No unintended side effects

---

*Recommended by Code Simplifier Agent*









&gt; Generated by <a href="https://github.com/Kong/kongctl/
actions/runs/22429088636">Code Simplifier</a>
&gt;
&gt; To install this workflow, run `gh aw add githubnext/
agentics/workflows/code-
simplifier.md@eb7950f37d350af6fa09d19827c4883e72947221`. View
source at <a href="https://github.com/githubnext/agentics/tree/
eb7950f37d350af6fa09d19827c4883e72947221/workflows/code-
simplifier.md">https://github.com/githubnext/agentics/tree/
eb7950f37d350af6fa09d19827c4883e72947221/workflows/code-
simplifier.md</a>.
&gt; - [x] expires  on Feb 27, 2026, 4:06 PM UTC



</issue_description>

## Comments on the Issue (you are @copilot in this section)

<comments>
</comments>

</problem_statement>
```

Implement the necessary changes to the repository so that the requirements specified in the <problem_statement> are met.

A **CI/Build Failure** has been mentioned in the problem statement, make sure to follow your instructions for addressing CI/Build Failures.