38ecc22b-d256-45d2-ad77-1bde42aa1045

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'gtapps/claude-code-hermit' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/claude-code-hermit/claude-code-hermit/gtapps/claude-code-hermit (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-06-13T20:59:35.487+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
fix(claude-code-hermit): gate session-start startup ping when watchdog clears context (#385)
</pr_title>

<pr_description>
Summary

When the watchdog sends `/clear` to refresh a hermit's context mid-session (post-close-clear or context-size-clear), a scheduled task could re-invoke `session-start` from scratch, which re-sent the "Hermit online" channel ping even though the session was never actually stopped. This was confirmed via a

```
live operator log showing the exact re-invocation path.

The fix is a consume-on-read boolean in `state/runtime.json`:
the watchdog writes `context_cleared: true` before sending `/
clear`, and session-start step 3 detects and consumes it (sets
to `false`) before deciding whether to send the step-8 startup
ping.

Closes #385

## Changes

- **`hermit-watchdog.ts`**: Both clear paths
(`maybePostCloseClear`, `maybeContextClear`) write
`context_cleared: true` via `writeRuntimeJson` inside the
lifecycle lock, before the `sendKeys('/clear')` call — ensuring
the marker is durable before session-start can race the
watchdog.
- **`skills/session-start/SKILL.md`**: Step 3 gains a "Context-
refresh detection" sub-bullet as its first action: reads
`context_cleared`, sets local `suppress_startup_ping = true` if
the marker is set, then unconditionally writes `context_cleared:
false` (consumes on every path including fast-path and recovery
branches that stop early). Step 8 adds `suppress_startup_ping`
as an additional skip condition.
- **`agents/session-mgr.md`**: `context_cleared` registered in
the field-ownership table as a dual-writer field with consume-
on-read semantics documented.
- **`tests/watchdog.test.ts`**: `writeFakeTmux` extended with an
optional `runtimeSnapshotPath` param; the bash stub snapshots
`runtime.json` at the moment it receives a `/clear` send-keys.
Both happy-path clear tests assert `context_cleared: true` in
the snapshot, proving write-before-send (not just write-before-
exit).

## Test plan

- `bun test tests/watchdog.test.ts` from inside `plugins/claude-
code-hermit/` — 49/49 pass, including the new write-before-send
assertions.
- `bun test` (full suite) — 986/986 pass.
</pr_description>

## Comments on the PR (you are @copilot in this section)

<comments>
```

<pr_comments>

<comment_new>
<comment_id>4699773401</comment_id>
<author>@gtapps</author>
@copilot resolve the merge conflicts in this pull request
</comment_new>

</pr_comments>

</comments>

The last **1** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement><rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. Treat <comment_old> comments as context only and do not make changes solely to satisfy them.
* Only act on <comment_new> comments that explicitly mention you (@copilot). To understand the context of comments that explicitly mention you, you may use other comments that do not explicitly mention you. Do not act on comments that don't explicitly mention you or reply to them, even if they are marked as <comment_new>.
* If the PR author has pushed back on or rejected a suggestion in a thread, do not act on that thread.
* For each comment you decide to act on, determine:
    - If it is a request for changes, a question on the code, or a suggestion.
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>

<system_reminder>

</system_reminder>

<prompt>

```
@copilot resolve the merge conflicts in this pull request
```