5a07500f-55b0-469c-ae80-58a62068b107

<prev_user>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'camunda/camunda' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/camunda/camunda (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-30T11:48:34.223+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
[WIP] Fix candidate group filter resolution to group names after migration
</pr_title>

<pr_description>
Thanks for asking me to work on this. I will get started on it and keep this PR's description up to date as I form a plan and make progress.

> ----
>
> *This section details on the original issue you should resolve*
>

><issue_title>Tasklist V2 candidateGroup filter does not resolve Group IDs to Group Names after 8.8 migration</issue_title>
><issue_description>###
>
>
>
> ###
>
>
>
> ###
>
>
>
> ###
>
>
>
> ### Description
>
> After the 8.7 → 8.8 migration, the Tasklist V2 UI's "Candidate group" filter no longer returns any tasks when a user selects one of their groups from the dropdown, even though tasks with that candidate group exist and are visible to them.
>
> The Tasklist V2 UI dropdown is populated from currentUser.groups (via GET `/v2/authentication/me`), which after 8.8 returns Group IDs (e.g. `front_support_retail_ch`). The selected value is then passed as filter.candidateGroup to POST `/v2/user-tasks/search`, where it is matched as an exact string against the indexed candidateGroups field of the task. That field contains whatever was modelled in the BPMN, which per Camunda's own documentation in 8.7 — was the Group Name (e.g. Front Support Retail CH). The two no longer match, so the filter returns zero results.
>
> This is the V2 counterpart of the V1 regression already fixed by @koevskinikola in camunda/camunda#38515. That fix translated groupIds → groupNames server-side in the Tasklist V1 controller before evaluating user-task access. The same translation has not been applied to the V2 search path.
>
> ###the value being passed to the API, once the backend can resolve either form. This avoids the UI also confusing the user, who today sees the slug instead of the human-readable name they modelled with.

>
> ### Dev -> QA handover
>
>
>
>
> ### Links
>
> camunda/camunda#38515 — V1 equivalent fix in 8.9.0.
> Jira Ticket: SUPPORT-32424
> Slack Incident channel: #inc-support-32424-cannot-filter-tasklist-in-ui-with-group-filter
>
> ### Automated Test Impact
>
> _No response_</issue_description>
>
><agent_instructions>Let's fix this in a TDD (test-driven development) fashion:
> 1. Create a test in the Camunda QA acceptance-tests module that reproduces the issue.
> 2. Adjust the `UserTaskController` to fix the `candidateGroups` resolution.</agent_instructions>
>
> ## Comments on the Issue (you are @claude[agent] in this section)
>
><comments>
><comment_new><author>@marcosgvieira</author>
> ### □ Triage Assessment
>
> | Field | Value |
> |------|-------|
> | **Work type** | BUG |
> | **Severity** | 🔥 High |
> | **Likelihood** | 🔥 High |
> | **Confidence** | 0.88 |
>
> ---
>
> ### 📝 Rationale
>
> Tasklist V2 candidate-group filtering is regressed after

8.8 so that the core filter no longer returns tasks when selecting a user’s group, impacting normal production usage with no simple UI-level workaround and likely affecting many environments where group IDs differ from group names.
>
> ---
>
> 🤖 _This issue was automatically triaged by an AI-based system as part of the Core Features triage workflow._
>
> ✋ **Want a human review?**
> If you believe this assessment is incorrect or needs adjustment, feel free to update the details or request a manual triage by adding the **`triage:manual`** label.</comment_new>
></comments>

</pr_description>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

</pr_comments>

<pr_reviews>

<comment_thread>
<file>qa/acceptance-tests/src/test/java/io/camunda/it/auth/UserTaskCandidateGroupFilterIT.java:179-186</file>
<original_commit>7524ddf</original_commit>

</comment_thread>

<comment_thread>
<file>authentication/src/main/java/io/camunda/authentication/service/DefaultMembershipService.java:94-105</file>
<original_commit>7524ddf</original_commit>

</comment_thread>

<comment_thread>
<file>qa/acceptance-tests/src/test/java/io/camunda/it/auth/
UserTaskCandidateGroupFilterIT.java:51</file>
<original_commit>7524ddf</original_commit>

</comment_thread>

<comment_thread>
<file>qa/acceptance-tests/src/test/java/io/camunda/it/auth/
UserTaskCandidateGroupFilterIT.java:161-177</file>
<original_commit>7524ddf</original_commit>

</comment_thread>

<comment_thread>
<file>qa/acceptance-tests/src/test/java/io/camunda/it/auth/
UserTaskCandidateGroupFilterIT.java:143-159</file>
<original_commit>7524ddf</original_commit>

</comment_thread>

<comment_thread>
<file>qa/acceptance-tests/src/test/java/io/camunda/it/auth/
UserTaskCandidateGroupFilterIT.java:105-129</file>
<original_commit>7524ddf</original_commit>

</comment_thread>

</pr_reviews>

<pr_comments>

<comment_new>
<comment_id>4352184350</comment_id>
<author>@koevskinikola</author>
@claude[agent]

> GroupState extension: The current GroupState interface only has get(String groupId). Should I add a new method like findByName(String name) or findGroupIdsByName(String name) that returns all group IDs matching a name?

Add a `findByIdOrName(String value)` method. The method should first attempt to use the `GroupState#get(String groupId)` method. If the method returns `null`, it should use a new helper method, `forEachGroup` similar to the `DbTenantState#forEachTenant` (see code) to find all groups by name. Evaluate if this is the most performant implementation.

> Injecting GroupState into BpmnUserTaskBehavior: Currently BpmnUserTaskBehavior doesn't have GroupState.

Add it as a constructor parameter.

Yes, add the resolution In the `evaluateCandidateGroupsExpression` method (line 217-223)?
</comment_new>

</pr_comments>

</comments>

The last **3** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement>

Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.
    - Is it addressed to you or someone else, e.g. "Hey @username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>

<prev_assistant>

Claude Code process exited with code 1

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'camunda/camunda' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/camunda/camunda (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-05-04T13:51:42.641+00:00</current_datetime>

Consider the following problem statement:

```
<problem_statement>

----
*This section includes details on the pull request with code
changes you have already submitted to fix the problem above.*

<pr_title>
[WIP] Fix candidate group filter resolution to group names after
migration
</pr_title>

<pr_description>
Thanks for asking me to work on this. I will get started on it
and keep this PR's description up to date as I form a plan and
make progress.

&gt; ----
&gt;
&gt; *This section details on the original issue you should
resolve*
&gt;
&gt;<issue_title>Tasklist V2 candidateGroup filter does not
resolve Group IDs to Group Names after 8.8 migration</
issue_title>
&gt;<issue_description>###
&gt;
&gt;
&gt;
&gt; ###
&gt;
&gt;
&gt;
&gt; ###
&gt;
&gt;
&gt;
&gt; ###
&gt;
&gt;
&gt;
&gt; ### Description
&gt;
&gt; After the 8.7 → 8.8 migration, the Tasklist V2 UI's
"Candidate group" filter no longer returns any tasks when a user
selects one of their groups from the dropdown, even though tasks
```

with that candidate group exist and are visible to them.
>
> The Tasklist V2 UI dropdown is populated from currentUser.groups (via GET `/v2/authentication/me`), which after 8.8 returns Group IDs (e.g. `front_support_retail_ch`). The selected value is then passed as filter.candidateGroup to POST `/v2/user-tasks/search`, where it is matched as an exact string against the indexed candidateGroups field of the task. That field contains whatever was modelled in the BPMN, which per Camunda's own documentation in 8.7 — was the Group Name (e.g. Front Support Retail CH). The two no longer match, so the filter returns zero results.
>
> This is the V2 counterpart of the V1 regression already fixed by @koevskinikola in camunda/camunda#38515. That fix translated groupIds → groupNames server-side in the Tasklist V1 controller before evaluating user-task access. The same translation has not been applied to the V2 search path.
>
> ### Steps to reproduce
>
> 1. Create an 8.7 cluster.
> 2. In Identity, create a user group, e.g. Front Support Retail CH, and assign a user to it.
> 3. In the Web Modeler, create a process with a user task whose candidateGroups = Front Support Retail CH.
> 4. Deploy and start an instance of the process.
> 5. Verify in Tasklist V1 that the user from the group can see the task.
> 6. Upgrade the cluster to 8.8 (or, equivalently, on a fresh 8.8 cluster create a Group where the name and ID differ — e.g. name Front Support Retail CH, id front_support_retail_ch).
> 7. Open Tasklist V2 as the group member.
> 8. In the "Filter tasks" panel, open the "Candidate group" dropdown and select the group (the dropdown shows front_support_retail_ch).
> 9. Apply the filter.
>
>
> ### Current behavior
>
> 1. The Candidate group dropdown displays the Group ID (front_support_retail_ch).
> 2. Applying the filter results in an empty task list.
> 3. The underlying call POST `/v2/user-tasks/search` with `filter.candidateGroup = "front_support_retail_ch" `returns 0 results.

> 4. Calling the same endpoint directly with `filter.candidateGroup = "Front Support Retail CH"` (the original Group Name as written in the BPMN) returns the tasks correctly.
>
> ### Expected behavior
>
> When a user selects one of their groups in the Tasklist V2 candidate-group filter, the resulting search should return all user tasks whose BPMN candidateGroups reference that group — regardless of whether the modeller used the Group Name or the Group ID.
>
> ### Workaround
>
> Either:
>
> - Call POST `/v2/user-tasks/search` directly, passing the original Group Name (as written in the BPMN) as the candidateGroup filter value, or
> - Update all BPMN process definitions to reference the new Group ID instead of the Group Name in candidateGroups.
>
> Neither is a reasonable ask of customers with existing process definitions in production
>
>
> ### Environment
>
> SaaS & SM
>
> ### Version
>
> Tasklist - 8.8
>
>
> ### Rootcause
>
> This is the same class of regression as camunda/camunda#38515, but on the V2 search path:
>
> - Identity in 8.7: Groups were defined only by Group Names; the name was the unique identifier.
> - Identity in 8.8: Groups are defined by both groupId (immutable, unique) and name (display label). The 8.7 → 8.8 migration sets groupName = `<existing name>` and groupId = `<slugified name>`.

> - Tasklist V2 UI: The candidate-group dropdown in `FieldsModal.tsx` is sourced from `currentUser.groups`, which (after 8.8) returns Group IDs via the new `CamundaAuthentication` layer.
> - Tasklist V2 search API: UserTaskFilterTransformer builds an exact-match term query against the `CANDIDATE_GROUPS` field of the task index. That field contains whatever the BPMN modeller wrote, which per Camunda's pre-8.8 docs — is the Group Name.
> - Net effect: the UI sends an ID, the index holds a name, the strings don't match, the filter returns nothing.
>
> The V1 fix in camunda/camunda#38515 added `TaskController.resolveGroupNames(...)`, which uses `GroupServices` to translate the authenticated user's `groupIds` back to `groupNames` before querying. The V2 path needs an equivalent translation step.
>
> ### Solution ideas
>
> A couple of possible directions, in rough order of preference:
>
> - Resolve group IDs → group names at the V2 search layer. When the V2 search receives` filter.candidateGroup = <id>`, look up the corresponding Group Name via` io.camunda.service.GroupServices` and rewrite the filter to match against the name (or both, as an $in over [id, name]). This mirrors V1 fix in camunda/camunda#38515.
>
> - Make `UserTaskFilterTransformer` accept either form. Translate the incoming candidateGroup value into an $in filter containing both the Group ID and the resolved Group Name, so that BPMN process definitions referencing either form continue to work. This is robust to mixed customer data (some BPMNs may already use IDs, others still use names).
>
> - In the Tasklist V2 candidate-group dropdown, display the Group Name to the user but keep the Group ID as the value being passed to the API, once the backend can resolve either form. This avoids the UI also confusing the user, who today sees the slug instead of the human-readable name they modelled with.
>
> ### Dev -> QA handover
>
>
>

>
> ### Links
>
> camunda/camunda#38515 – V1 equivalent fix in 8.9.0.
> Jira Ticket: SUPPORT-32424
> Slack Incident channel: #inc-support-32424-cannot-filter-tasklist-in-ui-with-group-filter
>
> ### Automated Test Impact
>
> _No response_</issue_description>
>
><agent_instructions>Let's fix this in a TDD (test-driven development) fashion:
> 1. Create a test in the Camunda QA acceptance-tests module that reproduces the issue.
> 2. Adjust the `UserTaskController` to fix the `candidateGroups` resolution.</agent_instructions>
>
> ## Comments on the Issue (you are @claude[agent] in this section)
>
><comments>
><comment_new><author>@marcosgvieira</author>
> ### □ Triage Assessment
>
> | Field | Value |
> |------|-------|
> | **Work type** | BUG |
> | **Severity** | 🔥 High |
> | **Likelihood** | 🔥 High |
> | **Confidence** | 0.88 |
>
> ---
>
> ### 📝 Rationale
>
> Tasklist V2 candidate-group filtering is regressed after 8.8 so that the core filter no longer returns tasks when selecting a user’s group, impacting normal production usage with no simple UI-level workaround and likely affecting many environments where group IDs differ from group names.
>

> ---
>
> 🤖 _This issue was automatically triaged by an AI-based system as part of the Core Features triage workflow._
>
> ✋ **Want a human review?**
> If you believe this assessment is incorrect or needs adjustment, feel free to update the details or request a manual triage by adding the **`triage:manual`** label.</comment_new>
></comments>

</pr_description>

Comments on the PR (you are @claude[agent] in this section)

<comments>

<pr_comments>

</pr_comments>

<pr_reviews>

<comment_thread>
<file>qa/acceptance-tests/src/test/java/io/camunda/it/auth/UserTaskCandidateGroupFilterIT.java:179-186</file>
<original_commit>7524ddf</original_commit>

</comment_thread>

<comment_thread_resolved>
<file>authentication/src/main/java/io/camunda/authentication/service/DefaultMembershipService.java:94-105</file>
<original_commit>7524ddf</original_commit>

</comment_thread_resolved>

<comment_thread_resolved>
<file>qa/acceptance-tests/src/test/java/io/camunda/it/auth/
UserTaskCandidateGroupFilterIT.java:51</file>
<original_commit>7524ddf</original_commit>

</comment_thread_resolved>

<comment_thread_resolved>
<file>qa/acceptance-tests/src/test/java/io/camunda/it/auth/
UserTaskCandidateGroupFilterIT.java:161-177</file>
<original_commit>7524ddf</original_commit>

</comment_thread_resolved>

<comment_thread_resolved>
<file>qa/acceptance-tests/src/test/java/io/camunda/it/auth/
UserTaskCandidateGroupFilterIT.java:143-159</file>
<original_commit>7524ddf</original_commit>

</comment_thread_resolved>

<comment_thread_resolved>
<file>qa/acceptance-tests/src/test/java/io/camunda/it/auth/
UserTaskCandidateGroupFilterIT.java:105-129</file>
<original_commit>7524ddf</original_commit>

can be found by user with group ID
- Line 119-129: Tests that BPMN with group ID can be found by
user with group ID

However, both execute the same code
(`camundaClient.newUserTaskSearchRequest().send().join()`) and
make similar assertions. The first test expects to find

`PROCESS_ID_WITH_GROUP_NAME`, the second expects
`PROCESS_ID_WITH_GROUP_ID`. These are essentially testing the
same authorization mechanism but with different BPMN processes.
Both should pass with the current (unsafe) implementation but
won't work correctly once we implement the proper fix at the
engine level.
</comment_old>

</comment_thread_resolved>

</pr_reviews>

<pr_comments>

<comment_old>
<author>@claude[agent]</author>

> @claude[agent] the current solution is unsafe because group
names are not unique within the group namespace, i.e. multiple
groups can have the same name. So including them in the
authorization filter ...

You're absolutely right about the security issue. I've reverted
the unsafe DefaultMembershipService changes in d22952d3.

For the proper engine-level fix, I need guidance on the
implementation approach:

1. **GroupState extension**: The current `GroupState` interface
only has `get(String groupId)`. Should I add a new method like
`findByName(String name)` or `findGroupIdsByName(String name)`
that returns all group IDs matching a name?

2. **Injecting GroupState into BpmnUserTaskBehavior**: Currently
BpmnUserTaskBehavior doesn't have GroupState. Should I:
   - Add it as a constructor parameter?
   - Access it through BpmnStateBehavior (which already has
access to various states)?

3. **Handling multiple groups with same name**: Based on your
guidance:
   - Multiple IDs → same name: Exclude the candidate group and
log WARN
   - No IDs mapped to name: Exclude the candidate group and log
WARN
   - Single ID mapped to name: Replace name with ID

Should the resolution happen:
- In the `evaluateCandidateGroupsExpression` method (line 217-223)?
- Or as a post-processing step after line 177 when setting candidateGroupsList?

A code pointer or example would be helpful for the best place to wire GroupState into the behavior.
</comment_old>

<comment_old>
<author>@koevskinikola</author>
@claude[agent]

> GroupState extension: The current GroupState interface only has get(String groupId). Should I add a new method like findByName(String name) or findGroupIdsByName(String name) that returns all group IDs matching a name?

Add a `findByIdOrName(String value)` method. The method should first attempt to use the `GroupState#get(String groupId)` method. If the method returns `null`, it should use a new helper method, `forEachGroup` similar to the `DbTenantState#forEachTenant` (see code) to find all groups by name. Evaluate if this is the most performant implementation.

> Injecting GroupState into BpmnUserTaskBehavior: Currently BpmnUserTaskBehavior doesn't have GroupState.

Add it as a constructor parameter.

Yes, add the resolution In the `evaluateCandidateGroupsExpression` method (line 217-223)?
</comment_old>

<comment_old>
<author>@claude[agent]</author>

> @claude[agent]
>
> > GroupState extension: The current GroupState interface only has get(String groupId). Should I add a new method like findByName(String name) or findGroupIdsByName(String name) that...

Implemented in 461eb326.

Added `findByIdOrName(String value)` method to GroupState that:
1. First tries to find by ID using existing `get()` method
2. If not found, uses new `forEachGroup()` helper to search all groups by name
3. Returns list of matching groups (empty, single, or multiple)

The resolution logic in `evaluateCandidateGroupsExpression()` (line 221-268) handles all cases:
- Empty/no match: logs WARN to define the group
- Multiple matches: logs WARN to migrate to group IDs, excludes the candidate group
- Single match: replaces the name with the group's ID

GroupState was injected into BpmnUserTaskBehavior constructor and wired through BpmnBehaviorsImpl.
</comment_old>

<comment_new>
<comment_id>4220586062</comment_id>
<author>@koevskinikola</author>
👍 @claude[agent] the changes look good, we're just missing some additional test coverage for the new `GroupState` methods. Please add it. I've left a more specific comment below.
</comment_new>

</pr_comments>

<pr_reviews>

<comment_thread>
<file>zeebe/engine/src/main/java/io/camunda/zeebe/engine/state/group/DbGroupState.java:73</file>
<original_commit>461eb32</original_commit>

<comment_new>
<comment_id>3181989279</comment_id>
<author>@koevskinikola</author>
🔧 Let's add a test case for this method in the `GroupStateTest`.
</comment_new>

</comment_thread>

</pr_reviews>

```
</comments>

----
The last **4** git commits in this branch are the changes you
have made so far. Use those as your change commit history.
</problem_statement><rules_for_making_changes>
* Start by fully understanding <problem_statement> and the
<comments> before making any changes. You will only address the
<comment_new> comments. Reply to new comments as you address
them. Ignore comments that are not actionable or directed at
you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a
suggestion.
    - Is it addressed to you or someone else, e.g. "Hey
@username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you
can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment
and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>
```