62f7b94f-4850-4b9c-bdcd-2060e2f9d178

<current>

<request>

You are working on an issue in the 'owndev/Open-WebUI-Functions' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/Open-WebUI-Functions/Open-WebUI-Functions (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2025-12-13T08:27:46.520Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section details on the original issue you should resolve

<issue_title>azure_ai_foundry.py is working a treat, but I am getting too many sources</issue_title>
<issue_description>### Bug title

Only 4 or 5 sources are shown in the response but many more are added

Describe the bug

In this example I had 3 sources added (the ones mentioned in the response) but after 1 second, more got added.
The first 3 also have a high score (80%) and the rest is 50% or lower.

I tried turing off followup generation but this did not have an effect.

<img src="https://github.com/user-attachments/assets/3110f254-90af-4d30-a006-50189caa918d">

I tried analyzing this with Copilot but could not apply a fix:

> What you’re seeing
>
> During streaming, your function emits only the citations that are actually referenced in the content (e.g., [doc1], [doc2]). That’s by design in __emit_openwebui_citation_events which filters by the indices it finds in the text.
> Shortly after the stream finishes, additional citations appear that are not referenced in the generated content.
>
> Why this happens
> In the streaming path, you do not remove or filter the raw context.citations included in the final message JSON that comes from Azure. Your code only emits filtered citation events, but it leaves the provider’s full context.citations list intact in the SSE JSON that the UI also receives. The UI then renders those extra citations when it processes the final message, which looks like “more citations arriving a bit later.”
> Concretely:
>
> _emit_openwebui_citation_events(...) filters to only the referenced [docX] indices. If none are found, it falls back to all citations (for backward compatibility).
> stream_processor_with_citations(...) updates content (turning [docX] into clickable links) but does not prune choices[].message.context.citations (or choices[].delta.context...) from the SSE JSON lines it forwards.
> In the non-stream path, enhance_azure_search_response(...) converts [docX] to links but likewise does not filter the citations array in the returned response.
>
> As a result, you get two sources of citations in the UI:
>
> Your filtered OpenWebUI citation events (correct, only referenced), and
> The provider’s unfiltered context.citations included in the final message (causing extra, unreferenced cards to appear afterwards).

Steps to reproduce

1. Create new funtion

````
2. Connect with azure ai and azure ai data source
3. Chat

### Environment

OWUI latest version
Latest azure_ai_foundry.py

### Additional context

_No response_</issue_description>

<agent_instructions>During followup generation, `[]` is
sometimes used multiple times, or there are empty brackets, and
sometimes it's incomplete. See this answer, which has been run
multiple times with followup generation:

```markdown
The available environment variables (ENV) options in the n8n
Pipeline include configurations for integrating with external
tools and services, such as n8n itself, Google Gemini, and Azure
AI. Some key options are:

- **N8N Integration:**
  - `N8N_URL`: The webhook endpoint URL for n8n.
  - `N8N_BEARER_TOKEN`: Token for secure access.


These environment variables allow detailed customization of the
pipeline's behavior, including safety settings, model handling,
image processing, response streaming, and data source
configurations [[doc3]](https://xxx.blob.core.windows.net/xxx/
xxx/n8n-integration.md)[[doc4]](https://
xxx.blob.core.windows.net/xxx/xxx/google-gemini-integration.md)
[[doc5]](https://xxx.blob.core.windows.net/xxx/xxx/azure-ai-
integration.md).The options available for environment variables
(ENV) in the n8n Pipeline include configurations for integrating
with various AI services and customizing pipeline behavior.
Based on the retrieved documents, the main options are:

### Azure AI Integration
- `AZURE_AI_PIPELINE_PREFIX`: Prefix for pipeline display names
[[[doc2]](https://xxx.blob.core.windows.net/xxx/xxx/azure-ai-
integration.md)].
- `AZURE_AI_API_KEY`: API key for Azure AI [[[doc2]](https://
xxx.blob.core.windows.net/xxx/xxx/azure-ai-integration.md)].
- `AZURE_AI_MODEL`: Model names, separated by semicolons or
````
````

commas [[[doc2]](https://xxx.blob.core.windows.net/xxx/xxx/azure-ai-integration.md)].
- `AZURE_AI_MODEL_IN_BODY`: Include model name in request body (`true`/`false`) [[[doc2]](https://xxx.blob.core.windows.net/xxx/xxx/azure-ai-integration.md)].
- `AZURE_AI_USE_AUTHORIZATION_HEADER`: Use `Authorization: Bearer` header (`true`/`false`) [[[doc2]](https://xxx.blob.core.windows.net/xxx/xxx/azure-ai-integration.md)].
- `AZURE_AI_DATA_SOURCES`: JSON configuration for Azure Search data sources [[[doc2]](https://xxx.blob.core.windows.net/xxx/xxx/azure-ai-integration.md)].
- `AZURE_AI_ENHANCE_CITATIONS`: Enable enhanced citation display (`true`/`false`) [[[doc2]](https://xxx.blob.core.windows.net/xxx/xxx/azure-ai-integration.md)]].

These environment variables allow detailed customization of the pipeline, including safety settings, model handling, image processing, response streaming, and data source configurations [[[doc1]](https://xxx.blob.core.windows.net/xxx/xxx/google-gemini-integration.md)](https://xxx.blob.core.windows.net/xxx/xxx/google-gemini-integration.md)[[[doc2]](https://xxx.blob.core.windows.net/xxx/xxx/azure-ai-integration.md)](https://xxx.blob.core.windows.net/xxx/xxx/azure-ai-integration.md).The options available for environment variables (ENV) in the n8n Pipeline include configurations for integrating with n8n itself, Google Gemini, and Azure AI, among others. Based on the retrieved documents, here are the key options:

Azure AI Integration
- `AZURE_AI_PIPELINE_PREFIX`: Prefix for pipeline display names [].
- `AZURE_AI_API_KEY`: API key for Azure AI [[[doc1]](https://xxx.blob.core.windows.net/xxx/xxx/n8n-integration.md)].
- `AZURE_AI_MODEL`: Model names, separated by semicolons or commas [].
- `AZURE_AI_MODEL_IN_BODY`: Include model name in request body (`true`/`false`) [].
- `AZURE_AI_USE_AUTHORIZATION_HEADER`: Use `Authorization: Bearer` header (`true`/`false`) [].
- `AZURE_AI_DATA_SOURCES`: JSON configuration for data sources like Azure Search [[]].
- `AZURE_AI_ENHANCE_CITATIONS`: Enable enhanced citation display (`true`/`false`) [[]].

These environment variables allow detailed customization of the pipeline's behavior, including safety settings, model handling, image processing, response streaming, and data source

````
configurations [[[doc1]](https://xxx.blob.core.windows.net/xxx/xxx/n8n-integration.md)] [[[doc5]](https://xxx.blob.core.windows.net/xxx/xxx/google-gemini-integration.md)].
```

Check for both errors and implement a solution that works. Test thoroughly to verify that it functions correctly.</agent_instructions>

## Comments on the Issue (you are @copilot in this section)

<comments>
</comments>

</problem_statement>
````

Implement the necessary changes to the repository so that the requirements specified in the <problem_statement> are met.

A **CI/Build Failure** has been mentioned in the problem statement, make sure to follow your instructions for addressing CI/Build Failures.
````