702210dd-99fa-45bd-acaf-34531bff7c7c

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'microsoft/Agents-for-js' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/Agents-for-js/Agents-for-js (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-02-05T20:11:26.237Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
Refactor authority handling in MsalTokenProvider for improved compatibility and clarity
</pr_title>

<pr_description>
This pull request updates authentication logic to improve flexibility and compatibility in how authority URLs are constructed for MSAL token acquisition, and simplifies JWT verification options.

Authentication authority handling improvements:

* Enhanced authority URL construction logic in

`MsalTokenProvider` to better support custom authorities and ensure correct tenant ID handling, including improved backward compatibility for authorities not containing "common" or a GUID. (`packages/agents-hosting/src/auth/msalTokenProvider.ts`)

JWT verification simplification:

* Removed the `issuer` field from the JWT verification options, which may simplify configuration and reduce potential mismatches during token validation. (`packages/agents-hosting/src/auth/jwt-middleware.ts`)

Fixes #906

</pr_description>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_old>
<author>copilot-pull-request-reviewer[bot]</author>
Pull request overview

This pull request refactors authentication authority handling in the MSAL token provider and simplifies JWT verification to better support multi-tenant, blueprint-based identity scenarios. The changes address issue #906, which identified problems with issuer validation and authority URL construction for blueprint identities that can be acquired in unpredictable tenant contexts.

Changes:
- Removed issuer validation from JWT verification options to accommodate blueprint-based identities where the issuer tenant cannot be predetermined
- Refactored authority URL resolution logic to support dynamic tenant ID replacement for both "common" and GUID-based tenant identifiers in authority URLs
- Added backward compatibility support for authority configurations that don't include "common" or a GUID

Reviewed changes

Copilot reviewed 2 out of 2 changed files in this pull request

and generated 7 comments.

File	Description
packages/agents-hosting/src/auth/jwt-middleware.ts	Removed issuer field from JWT verification options to enable token validation for blueprint identities across multiple tenants
packages/agents-hosting/src/auth/msalTokenProvider.ts	Refactored `resolveAuthority` method to support tenant ID replacement in authority URLs beyond just "common" tenant, with backward compatibility for incomplete authority configurations

---

💡 <a>Add Copilot custom instructions for smarter, more guided reviews. Learn how to get started.
</comment_old>

</pr_comments>

<pr_reviews>

<comment_thread_resolved>
<file>packages/agents-hosting/src/auth/msalTokenProvider.ts:180</file>
<original_commit>0508859</original_commit>

<comment_old>
<author>copilot-pull-request-reviewer[bot]</author>
Use `const` instead of `var` for the `resultAuthority` variable. The variable is not reassigned after its initial assignment, so it should be declared with `const` to follow modern JavaScript best practices.
</comment_old>

</comment_thread_resolved>

<comment_thread_resolved>
<file>packages/agents-hosting/src/auth/msalTokenProvider.ts:174-177</file>
<original_commit>0508859</original_commit>

<comment_old>
<author>copilot-pull-request-reviewer[bot]</author>
The logic on lines 174-177 has a potential issue. When `this.connectionSettings?.authority` is defined and doesn't end with '/common' or a GUID, the code sets `workingAuthority` to include the tenant ID from `this.connectionSettings.tenantId`. However, this tenant ID might not be the same as the `tenantId` parameter passed to the function, which is intended to override the default tenant. This could result in using the wrong tenant ID in certain scenarios. Consider whether this backwards compatibility path should also use the passed-in `tenantId` parameter instead of `this.connectionSettings.tenantId`.
</comment_old>

<comment_old>
<author>@MattB-msft</author>
This is intentional to support BluePrint/AgentID scenarios.
</comment_old>

</comment_thread_resolved>

<comment_thread>
<file>packages/agents-hosting/src/auth/msalTokenProvider.ts:187</file>
<original_commit>0508859</original_commit>

<comment_old>
<author>copilot-pull-request-reviewer[bot]</author>
The type cast `as string` on line 187 is unnecessary because `resultAuthority` is already of type `string` due to the ternary operator's type resolution. The condition ensures that either the result of `workingAuthority.replace(...)` (which returns a string) or the literal string `'https://login.microsoftonline.com/${tenantId}'` is assigned, both of which are strings. Removing the redundant cast improves code clarity.
</comment_old>

</comment_thread>

<comment_thread>
<file>packages/agents-hosting/src/auth/msalTokenProvider.ts:180</file>
<original_commit>0508859</original_commit>

<comment_old>

<author>copilot-pull-request-reviewer[bot]</author>
The condition `workingAuthority && workingAuthority.length > 0` is redundant. Line 171 initializes `workingAuthority` with either `this.connectionSettings?.authority` or the fallback string `'https://login.microsoftonline.com/'`, which is never empty. Even if `this.connectionSettings?.authority` is undefined, `workingAuthority` will always be the non-empty fallback string. Therefore, the check `workingAuthority.length > 0` will always be true and can be simplified to just checking truthiness or removed entirely.
</comment_old>

</comment_thread>

<comment_thread_resolved>
<file>packages/agents-hosting/src/auth/jwt-middleware.ts:63-64</file>
<original_commit>0508859</original_commit>

<comment_old>
<author>copilot-pull-request-reviewer[bot]</author>
Removing the issuer validation from JWT verification removes an important security check. While this change addresses the blueprint identity issue mentioned in #906, it weakens token validation by allowing tokens from any issuer as long as they have the correct audience and valid signature. This could potentially allow tokens from unexpected or malicious issuers to be accepted. Consider implementing an alternative validation mechanism, such as allowing developers to provide custom issuer validation logic while maintaining some baseline security checks, or using a more permissive issuer pattern that still validates against expected issuer formats.
</comment_old>

<comment_old>
<author>@MattB-msft</author>
Token validation needs to be moved out of core JS and into customer realm.
we should only validate the minimal requirements and track the claims required for future proactive requests.
</comment_old>

</comment_thread_resolved>

<comment_thread>
<file>packages/agents-hosting/src/auth/msalTokenProvider.ts:172-173</file>

<original_commit>0508859</original_commit>

<comment_old>
<author>copilot-pull-request-reviewer[bot]</author>
The comment on lines 172-173 contains a grammatical error. It should read: "if authority is defined and it does not contain 'common' or a guid, create the authority and append the tenantId" (removing "use it as is" which doesn't fit the logic, or restructuring for clarity).
</comment_old>

</comment_thread>

<comment_thread_resolved>
<file>packages/agents-hosting/src/auth/msalTokenProvider.ts:171</file>
<original_commit>0508859</original_commit>

<comment_old>
<author>copilot-pull-request-reviewer[bot]</author>
Use `const` instead of `var` for the `workingAuthority` variable. The variable is not reassigned conditionally in a way that requires `var`, and using `const` or `let` provides better scoping and follows modern JavaScript best practices.
</comment_old>

</comment_thread_resolved>

</pr_reviews>

<pr_comments>

<comment_new>
<comment_id>3855951917</comment_id>
<author>@MattB-msft</author>
@copilot Please create a PR and run tests on this repo, fixing any failing tests. then run lint to make sure there are no syntactical errors.

</comment_new>

</pr_comments>

</comments>

The last **4** git commits in this branch are the changes you

have made so far. Use those as your change commit history.
</problem_statement>

Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.
    - Is it addressed to you or someone else, e.g. "Hey @username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>

A **CI/Build Failure** has been mentioned in the problem statement, make sure to follow your instructions for addressing CI/Build Failures.

<prompt>

@copilot Please create a PR and run tests on this repo, fixing any failing tests. then run lint to make sure there are no syntactical errors.