86d0421a-6a62-443a-8e71-e85c7046aa93

<prev_user>

<request>

You are working on a task in the 'amadvance/snapraid-daemon' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/snapraid-daemon/snapraid-daemon (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-30T10:04:35.005+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>
Start from the tag v1.8 and analyze any commit up to the HEAD to find potential bugs. Report all the findings, commit by commit.
</problem_statement>

First, determine whether the <problem_statement> requires code changes, an explanation, a plan, or analysis. Then follow the appropriate path:

If the task requires code changes:

If the task is a question or only requires creating a plan or analysis: respond directly without making code changes.

<prev_assistant>

Now I have enough context. Let me compile the complete analysis.

Commit-by-commit bug analysis (v1.8 → HEAD)

`9f50a23` — Update CHECKSUMS
No source code changes. No bugs.

`d12e9a5` — Fix on Windows script execution failure when using the `hook_run_as_user`

Fix is correct but introduces one new issue in `os_command`.

In `os_command` (`mingw.c` ~line 1520), `bInheritHandles` was changed from `FALSE` to `TRUE` for the `CreateProcessAsUserW` call:

```c
ret = CreateProcessAsUserW(
    h_token, NULL, u8tou16(conv, command),
    NULL, NULL,
    TRUE,  /* ← changed from of potential false-positive matches grows.

---

### `7106c06` — Add optional `limit_*` to reduce network payload sizes

**No bugs.** `limit_parse` is correct. `strint` is safe (uses `strtol` with range and error checks). The countdown pattern `if (--limit_X < 0) break` works correctly: `limit=0` returns 0 entries; `limit=INT_MAX` (the default) is never exhausted in practice because `MESSAGES_MAX=5000` caps list sizes.

---

### `2d1d1c2` → `3f1fc95` — Use `limits_*` in the Commander interface

JavaScript UI change only. No bugs.

---

### `a0d6e34` — Uppercase days / `c89f25b` — Config example / `dcb9302` — TODO

Documentation and cosmetic changes only. No bugs.

---
```

```
## Summary table

| Commit | Severity | Finding |
|--------|----------|---------|
| `0b5ba37` / `d12e9a5` | Medium | `CreateEnvironmentBlock` return value
ignored in `os_command` (Windows); spawned command inherits no
environment on failure |
| `1cae4cc` | Medium | If NUL device fails to open, NULL handles are
passed with `STARTF_USESTDHANDLES`; child process will fault on any
stdout/stderr write |
| `2d1d1c2` | High | Memory leak at all 9 call sites in `parser.c`:
`file_alloc()` result is discarded (not freed) when `FILES_MAX` is
exceeded |
| `3fb8746` | Low | Removal of HTTP 403 for unknown MIME types silently
serves all web-root files; pre-existing `strstr`-based MIME matching
grows worse with new extensions |
```

<current>

<request>

You are working on a task in the 'amadvance/snapraid-daemon' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/snapraid-daemon/snapraid-daemon (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-30T10:41:42.411+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>
I changed the commits from the v1.9 tag. Recheck again starting from the v1.9 tag to HEAD
</problem_statement>

First, determine whether the <problem_statement> requires code changes, an explanation, a plan, or analysis. Then follow the appropriate path:

If the task requires code changes:

```
**If the task is a question or only requires creating a plan or
analysis:** respond directly without making code changes.
```