8bc25f95-bfad-4cde-a1b0-261ae8cc9c6e

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'devantler-tech/platform' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/platform/platform (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-03-29T16:44:25.268Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
ci(workflows): tighten workflow permissions
</pr_title>

<pr_description>
Summary
Tighten GitHub Actions workflow permissions and address zizmor findings across the platform workflows.

Changes
- move broad workflow-level write permissions to the specific jobs that need them
- add explanatory comments for non-default permissions
- add workflow and job metadata where zizmor flagged missing

```
names or concurrency controls
- avoid inline secret interpolation in `cd-deploy.yaml` by
passing secrets through environment variables

## Verification
- run `zizmor --pedantic .github/workflows/`
- confirm zizmor reports `No findings to report. Good job!`

</pr_description>

## Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_old>
<author>@copilot-pull-request-reviewer</author>
## Pull request overview

This PR hardens GitHub Actions workflow security by minimizing
default `GITHUB_TOKEN` permissions, adding concurrency controls/
metadata where flagged by zizmor, and avoiding inline secret
interpolation in the production deploy workflow.

**Changes:**
- Move broad workflow-level permissions to job-level
`permissions:` blocks and set workflow-level `permissions: {}`.
- Add workflow/job metadata (e.g., names and `concurrency`) to
address zizmor findings.
- Pass secrets via step `env:` (e.g., `KUBE_CONFIG`,
`SOPS_AGE_KEY`) instead of inline `${{ secrets.* }}`
interpolation.

### Reviewed changes

Copilot reviewed 5 out of 5 changed files in this pull request
and generated 3 comments.









</comment_old>
```

</pr_comments>

<pr_reviews>

<comment_thread>
<file>.github/workflows/ci.yaml:7-11</file>
<original_commit>f9b84a1</original_commit>

<comment_old>
<author>@copilot-pull-request-reviewer</author>
With `permissions: {}` at the workflow level, any job that doesn’t declare its own `permissions:` runs with a GITHUB_TOKEN that has no scopes. `system-test` doesn’t set job-level permissions but uses `actions/checkout`, so it will fail. Add at least `contents: read` (and any other required scopes) to the `system-test` job’s `permissions:` block.
</comment_old>

<comment_new>
<comment_id>3005382925</comment_id>
<author>@devantler</author>
@copilot apply changes based on this feedback
</comment_new>

</comment_thread>

<comment_thread>
<file>.github/workflows/sync-labels.yaml:17</file>
<original_commit>f9b84a1</original_commit>

<comment_old>
<author>@copilot-pull-request-reviewer</author>
This job checks out the repository but only grants `issues: write`. Because the workflow sets `permissions: {}`, `actions/checkout` won’t have `contents: read` and the checkout step is likely to fail. Add `contents: read` to this job’s permissions (and keep `issues: write` for label syncing).
```suggestion
    permissions:
      contents: read
```
</comment_old>

</comment_thread>

<comment_thread>

<file>.github/workflows/cd-deploy.yaml:45</file>
<original_commit>f9b84a1</original_commit>

<comment_old>
<author>@copilot-pull-request-reviewer</author>
This workflow no longer creates/updates the `flux-system/sops-age` Kubernetes Secret in the cluster, but the Flux Kustomizations in this repo are configured to decrypt with `secretRef: name: sops-age` and there’s no manifest that defines that Secret. Unless it’s guaranteed to be pre-provisioned and kept up to date out-of-band, deployments (or future cluster rebuilds/key rotations) can fail. Consider reintroducing a step that applies/updates the `sops-age` Secret using `SOPS_AGE_KEY` from env (without inline secret interpolation) or managing the Secret via GitOps/SOPS if that’s the intended approach.
```suggestion

      - name: 🔐 Ensure flux-system/sops-age Secret exists
        env:
          SOPS_AGE_KEY: ${{ secrets.SOPS_AGE_KEY }}
        run: |
          kubectl -n flux-system create secret generic sops-age \
            --from-literal=age.agekey="${SOPS_AGE_KEY}" \
            --dry-run=client -o yaml | kubectl apply -f -
```
</comment_old>

</comment_thread>

</pr_reviews>

</comments>

The last **1** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement><rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.
    - Is it addressed to you or someone else, e.g. "Hey

```
@username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you
can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment
and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>
```