8e988585-0758-49a9-bcc7-c7f41127267a

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'codeceptjs/CodeceptJS' repository.

<repository_context>
I've cloned the repository in the directory /tmp/workspace/codeceptjs/CodeceptJS (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-05-26T03:43:19.859+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
feat(webapi): saveScreenshot with custom path
</pr_title>

<pr_description>
Motivation/Description of the PR
- Description of this PR, which problem it solves
- Resolves #issueId (if applicable).

Applicable helpers:

- [x] Playwright
- [x] Puppeteer
- [x] WebDriver

```
- [ ] REST
- [ ] FileHelper
- [ ] Appium
- [ ] TestCafe

## Type of change

- [ ] :fire: Breaking changes
- [x] :rocket: New functionality
- [ ] :bug: Bug fix
- [ ] □ Chore
- [x] :clipboard: Documentation changes/updates
- [ ] :hotsprings: Hot fix
- [x] :hammer: Markdown files fix - not related to source code
- [ ] :nail_care: Polish code

## Checklist:

- [x] Tests have been added
- [x] Documentation has been added (Run `npm run docs`)
- [x] Lint checking (Run `npm run lint`)
- [x] Local tests are passed (Run `npm test`)

</pr_description>

## Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_new>
<comment_id>3900830623</comment_id>
<author>@DavertMik</author>
Can we just split filename path and create folders
automatically?

`I.saveScreenshot('custom/debug.png')` will create `output/
custom/debug.png`
</comment_new>

<comment_new>
<comment_id>4010516383</comment_id>
<author>@kobenguyent</author>
&gt; Can we just split filename path and create folders
automatically?
&gt;
&gt; `I.saveScreenshot('custom/debug.png')` will create
```

`output/custom/debug.png`

I may get it wrongly as https://github.com/codeceptjs/CodeceptJS/issues/5404 request may try to save the screenshot to custom path not inside the output folder.
</comment_new>

<comment_new>
<comment_id>4026872528</comment_id>
<author>@DavertMik</author>
@kobenguyent we can use absolute paths to handle this

if provided path is absolute -> save into it

so use could use it like this:

```
I.saveSceenshot(path.join(global.mySpecialPath, 'screenshot1'))
```

I dont see a need for another very similar method
it will be confusing to users and AI agents

Just detect global paths and provide such solution in UI
If user wants different ways they can create their own similar methods like

I.saveScreenshotToMyPath()
I.saveScreenshotToMyOtherPath()

inside custom steps file
</comment_new>

<comment_new>
<comment_id>4028547054</comment_id>
<author>@kobenguyent</author>
I see. Initially, I was thinking to reimplement the same function but I thought it may be backwards compatibility so that's why I introduced the new one.
</comment_new>

</pr_comments>

<pr_reviews>

<comment_thread_resolved>

<file>lib/utils.js:317</file>
<original_commit>8707915</original_commit>

<comment_old>
<author>@DenysKuchma</author>
Path handling depends on path.sep, so the same input behaves
differently on Windows vs POSIX. Can you fix it?

</comment_old>

</comment_thread_resolved>

<comment_thread_resolved>
<file>docs/helpers/Playwright.md:1797</file>
<original_commit>8707915</original_commit>

<comment_old>
<author>@DenysKuchma</author>
Can fix word ouput -> output , pls)
</comment_old>

</comment_thread_resolved>

<comment_thread_resolved>
<file>docs/webapi/saveScreenshot.mustache:8</file>
<original_commit>8707915</original_commit>

<comment_old>
<author>@DenysKuchma</author>
is misleading with current behavior, it will be output/
customFolder/.. . No?
</comment_old>

<comment_old>
<author>@kobenguyent</author>
this will relative to `global.codeceptjs_dir`, not
`global.codeceptjs_output`. 😄
</comment_old>

</comment_thread_resolved>

<comment_thread_resolved>
<file>test/helper/webapi.js:876</file>
<original_commit>8707915</original_commit>

<comment_old>
<author>@DenysKuchma</author>

```
“custom dir” test currently points custom_dir to output_dir, so
it does not truly validate a separate custom path.
</comment_old>

</comment_thread_resolved>

</pr_reviews>

<pr_comments>

  <comment_new>
  <comment_id>4539792441</comment_id>
  <author>@kobenguyent</author>
  @copilot resolve conflicts with main branch (4.x)
  </comment_new>

</pr_comments>

</comments>

----
The last **147** git commits in this branch are the changes you
have made so far. Use those as your change commit history.
</problem_statement>

Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the
<comments> before making any changes. Treat <comment_old> comments
as context only and do not make changes solely to satisfy them.
* Only act on <comment_new> comments that explicitly mention you
(@copilot). To understand the context of comments that explicitly
mention you, you may use other comments that do not explicitly
mention you. Do not act on comments that don't explicitly mention
you or reply to them, even if they are marked as <comment_new>.
* If the PR author has pushed back on or rejected a suggestion in a
thread, do not act on that thread.
* For each comment you decide to act on, determine:
    - If it is a request for changes, a question on the code, or a
suggestion.
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can
stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and
ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>
```

```
<system_reminder>

</system_reminder>
```