94543f3d-6959-4a09-bd5-980f06829116

<current>

<request>

You are working on an issue in the 'prettier/prettier-vscode' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/prettier-vscode/prettier-vscode (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2025-11-29T00:41:15.736Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section details on the original issue you should resolve

<issue_title>Empty lines added to the end of files when formatting MD files</issue_title>
<issue_description>- [x] Write a summary of your issue
- [x] Include a link to a github repo that can be used to reproduce the issue or exact reproduction steps.
- [x] Provide the expected result
- [x] Provide the actual result
- [x] Include extension, os, and vs code information
- [x] Include Prettier extension log

Summary

I know this issue exists here https://github.com/prettier/prettier-vscode/issues/2472 but it's marked as not related to this plugin. However, when I disable this plugin it doesn't

````
happen and when I enable it back it happens again.

### Github Repository to Reproduce Issue

https://github.com/MrAmericanMike/RemoveMouseoverHighlight

### Steps To Reproduce:

Open VSCode with Prettier installed, create a file with .md
extension. Write anything on it and do a "Format document" an
empty line gets added to the end of the document, do a "Format
document" once again and another empty line gets added to the
end (Up to 2 empty lines)

### Expected result

Expected result would be to not see empty lines been added to
the document.

### Actual result

The files gets empty lines at the end on each format. (up to 2)

### Additional information
**VS Code Version**:

Version: 1.80.1 (user setup)
Commit: 74f6148eb9ea00507ec113ec51c489d6ffb4b771
Date: 2023-07-12T17:22:07.651Z
Electron: 22.3.14
ElectronBuildId: 21893604
Chromium: 108.0.5359.215
Node.js: 16.17.1
V8: 10.8.168.25-electron.0
OS: Windows_NT x64 10.0.22623

**Prettier Extension Version**:
Prettier - Code formatter v10.1.0

**OS and version**:
Windows 11

## Prettier Log Output
This are the logs after formatting on save 2 times a MD file
that had no empty lines at the end.

```
````
````

```
["INFO" - 3:17:32 PM] Extension Name: esbenp.prettier-vscode.
["INFO" - 3:17:32 PM] Extension Version: 10.1.0.
["INFO" - 3:17:50 PM] Formatting file:///f%3A/Personal/MC/
MinecraftMods/Forge/InvisibleBarrier/1.20.2/README.md
["INFO" - 3:17:50 PM] PrettierInstance:
{
  "doc": {
    "builders": {
      "line": {
        "type": "line"
      },
      "softline": {
        "type": "line",
        "soft": true
      },
      "hardline": {
        "type": "concat",
        "parts": [
          {
            "type": "line",
            "hard": true
          },
          {
            "type": "break-parent"
          }
        ]
      },
      "literalline": {
        "type": "concat",
        "parts": [
          {
            "type": "line",
            "hard": true,
            "literal": true
          },
          {
            "type": "break-parent"
          }
        ]
      },
      "lineSuffixBoundary": {
        "type": "line-suffix-boundary"
      },
      "cursor": {
        "type": "cursor"
      },
      "breakParent": {
```

```
        "type": "break-parent"
      },
      "trim": {
        "type": "trim"
      },
      "hardlineWithoutBreakParent": {
        "type": "line",
        "hard": true
      },
      "literallineWithoutBreakParent": {
        "type": "line",
        "hard": true,
        "literal": true
      }
    },
    "printer": {},
    "utils": {},
    "debug": {}
  },
  "version": "2.8.8",
  "util": {},
  "__internal": {
    "errors": {},
    "coreOptions": {
      "CATEGORY_CONFIG": "Config",
      "CATEGORY_EDITOR": "Editor",
      "CATEGORY_FORMAT": "Format",
      "CATEGORY_OTHER": "Other",
      "CATEGORY_OUTPUT": "Output",
      "CATEGORY_GLOBAL": "Global",
      "CATEGORY_SPECIAL": "Special",
      "options": {
        "cursorOffset": {
          "since": "1.4.0",
          "category": "Special",
          "type": "int",
          "default": -1,
          "range": {
            "start": -1,
            "end": null,
            "step": 1
          },
          "description": "Print (to stderr) where a cursor at
the given position would move to after formatting.\nThis option
cannot be used with --range-start and --range-end.",
          "cliCategory": "Editor"
        },
```

```
        "endOfLine": {
          "since": "1.15.0",
          "category": "Global",
          "type": "choice",
          "default": [
            {on would move to after formatting.\nThis option
cannot be used with --range-start and --range-end.",
          "cliCategory": "Editor"
        },
        "endOfLine": {
          "since": "1.15.0",
          "category": "Global",
          "type": "choice",
          "default": [
            {
              "since": "1.15.0",
              "value": "auto"
            },
            {
              "since": "2.0.0",
              "value": "lf"
            }
          ],
          "description": "Which end of line characters to
apply.",
          "choices": [
            {
              "value": "lf",
              "description": "Line Feed only (\\n), common on
Linux and macOS as well as inside git repos"
            },
            {
              "value": "crlf",
              "description": "Carriage Return + Line Feed
characters (\\r\\n), common on Windows"
            },
            {
              "value": "cr",
              "description": "Carriage Return character only (\
\r), used very rarely"
            },
            {
              "value": "auto",
              "description": "Maintain existing\n(mixed values
within one file are normalised by looking at what's used after
the first line)"
            }
```

```
          ]
        },
        "filepath": {
          "since": "1.4.0",
          "category": "Special",
          "type": "path",
          "description": "Specify the input filepath. This will
be used to do parser inference.",
          "cliName": "stdin-filepath",
          "cliCategory": "Other",
          "cliDescription": "Path to the file to pretend that
stdin comes from."
        },
        "insertPragma": {
          "since": "1.8.0",
          "category": "Special",
          "type": "boolean",
          "default": false,
          "description": "Insert @format pragma into file's
first docblock comment.",
          "cliCategory": "Other"
        },
        "parser": {
          "since": "0.0.10",
          "category": "Global",
          "type": "choice",
          "default": [
            {
              "since": "0.0.10",
              "value": "babylon"
            },
            {
              "since": "1.13.0"
            }
          ],
          "description": "Which parser to use.",
          "choices": [
            {
              "value": "flow",
              "description": "Flow"
            },
            {
              "value": "babel",
              "since": "1.16.0",
              "description": "JavaScript"
            },
            {
```

```
      "value": "babel-flow",
      "since": "1.16.0",
      "description": "Flow"
    },
    {
      "value": "babel-ts",
      "since": "2.0.0",
      "description": "TypeScript"
    },
    {
      "value": "typescript",
      "since": "1.4.0",
      "description": "TypeScript"
    },
    {
      "value": "acorn",
      "since": "2.6.0",
      "description": "JavaScript"
    },
    {
      "value": "espree",
      "since": "2.2.0",
      "description": "JavaScript"
    },
    {
      "value": "meriyah",
      "since": "2.2.0",
      "description": "JavaScript"
    },
    {
      "value": "css",
      "since": "1.7.1",
      "description": "CSS"
    },
    {
      "value": "less",
      "since": "1.7.1",
      "description": "Less"
    },
    {
      "value": "scss",
      "since": "1.7.1",
      "description": "SCSS"
    },
    {
      "value": "json",
      "since": "1.5.0",
```

```
      "description": "JSON"
    },
    {
      "value": "json5",
      "since": "1.13.0",
      "description": "JSON5"
    },
    {
      "value": "json-stringify",
      "since": "1.13.0",
      "description": "JSON.stringify"
    },
    {
      "value": "graphql",
      "since": "1.5.0",
      "description": "GraphQL"
    },
    {
      "value": "markdown",
      "since": "1.8.0",
      "description": "Markdown"
    },
    {
      "value": "mdx",
      "since": "1.15.0",
      "description": "MDX"
    },
    {
      "value": "vue",
      "since": "1.10.0",
      "description": "Vue"
    },
    {
      "value": "yaml",
      "since": "1.14.0",
      "description": "YAML"
    },
    {
      "value": "glimmer",
      "since": "2.3.0",
      "description": "Ember / Handlebars"
    },
    {
      "value": "html",
      "since": "1.15.0",
      "description": "HTML"
    },
```

```
            {
              "value": "angular",
              "since": "1.15.0",
              "description": "Angular"
            },
            {
              "value": "lwc",
              "since": "1.17.0",
              "description": "Lightning Web Components"
            }
          ]
        },
        "plugins": {
          "since": "1.10.0",
          "type": "path",
          "array": true,
          "default": [
            {
              "value": []
            }
          ],
          "category": "Global",
          "description": "Add a plugin. Multiple plugins can be
passed as separate `--plugin`s.",
          "cliName": "plugin",
          "cliCategory": "Config"
        },
        "pluginSearchDirs": {
          "since": "1.13.0",
          "type": "path",
          "array": true,
          "default": [
            {
              "value": []
            }
          ],
          "category": "Global",
          "description": "Custom directory that contains
prettier plugins in node_modules subdirectory.\nOverrides
default behavior when plugins are searched relatively to the
location of Prettier.\nMultiple values are accepted.",
          "cliName": "plugin-search-dir",
          "cliCategory": "Config"
        },
        "printWidth": {
          "since": "0.0.0",
          "category": "Global",
```

```
          "type": "int",
          "default": 80,
          "description": "The line length where Prettier will
try wrap.",
          "range": {
            "start": 0,
            "end": null,
            "step": 1
          }
        },
        "rangeEnd": {
          "since": "1.4.0",
          "category": "Special",
          "type": "int",
          "default": null,
          "range": {
            "start": 0,
            "end": null,
            "step": 1
          },
          "description": "Format code ending at a given
character offset (exclusive).\nThe range will extend forwards to
the end of the selected statement.\nThis option cannot be used
with --cursor-offset.",
          "cliCategory": "Editor"
        },
        "rangeStart": {
          "since": "1.4.0",
          "category": "Special",
          "type": "int",
          "default": 0,
          "range": {
            "start": 0,
            "end": null,
            "step": 1
          },
          "description": "Format code starting at a given
character offset.\nThe range will extend backwards to the start
of the first line containing the selected statement.\nThis
option cannot be used with --cursor-offset.",
          "cliCategory": "Editor"
        },
        "requirePragma": {
          "since": "1.7.0",
          "category": "Special",
          "type": "boolean",
          "default": false,
```

```
          "description": "Require either '@prettier' or
'@format' to be present in the file's first docblock comment\nin
order for it to be formatted.",
          "cliCategory": "Other"
        },
        "tabWidth": {
          "type": "int",
          "category": "Global",
          "default": 2,
          "description": "Number of spaces per indentation
level.",
          "range": {
            "start": 0,
            "end": null,
            "step": 1
          }
        },
        "useTabs": {
          "since": "1.0.0",
          "category": "Global",
          "type": "boolean",
          "default": false,
          "description": "Indent with tabs instead of spaces."
        },
        "embeddedLanguageFormatting": {
          "since": "2.1.0",
          "category": "Global",
          "type": "choice",
          "default": [
            {
              "since": "2.1.0",
              "value": "auto"
            }
          ],
          "description": "Control how Prettier formats quoted
code embedded in the file.",
          "choices": [
            {
              "value": "auto",
              "description": "Format embedded code if Prettier
can automatically identify it."
            },
            {
              "value": "off",
              "description": "Never automatically format
embedded code."
            }
```

```
          ]
        }
      }
    },
    "optionsModule": {
      "hiddenDefaults": {
        "astFormat": "estree",
        "printer": {},
        "locStart": null,
        "locEnd": null
      }
    },
    "optionsNormalizer": {},
    "utils": {}
  },
  "__debug": {}
}
["INFO" - 3:17:51 PM] Using ignore file (if present) at f:
\Personal\MC\MinecraftMods\Forge\InvisibleBarrier\.prettierignor
e
["INFO" - 3:17:51 PM] File Info:
{
  "ignored": false,
  "inferredParser": "markdown"
}
["INFO" - 3:17:51 PM] No local configuration (i.e. .prettierrc
or .editorconfig) detected, falling back to VS Code
configuration
["INFO" - 3:17:51 PM] Prettier Options:
{
  "arrowParens": "always",
  "bracketSpacing": true,
  "endOfLine": "crlf",
  "htmlWhitespaceSensitivity": "css",
  "insertPragma": false,
  "singleAttributePerLine": false,
  "bracketSameLine": true,
  "jsxBracketSameLine": false,
  "jsxSingleQuote": false,
  "printWidth": 160,
  "proseWrap": "preserve",
  "quoteProps": "preserve",
  "requirePragma": false,
  "semi": true,
  "singleQuote": false,
  "tabWidth": 4,
  "trailingComma": "none",
```

````
  "useTabs": true,
  "embeddedLanguageFormatting": "auto",
  "vueIndentScriptAndStyle": false,
  "filepath": "f:\\Personal\\MC\\MinecraftMods\\Forge\
\InvisibleBarrier\\1.20.2\\README.md",
  "parser": "markdown"
}
["INFO" - 3:17:51 PM] Formatting completed in 46ms.

```
</issue_description>

## Comments on the Issue (you are @copilot in this section)

<comments>
</comments>

</problem_statement>
````

Implement the necessary changes to the repository so that the requirements specified in the <problem_statement> are met.

Ensure that you lint, build and test early and iteratively to validate each code change thoroughly.
````