96800210-a6b4-490a-b136-3837032faec3

<prev_user>

<request>

You are working on a task in the 'SuperNG6/docker-usque' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/docker-usque/docker-usque (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-10T06:59:34.299Z</current_datetime>

Consider the following problem statement:

<problem_statement>
项目上游更新了，https://github.com/Diniboy1123/usque
根据上游更新，更新这个项目的readme和代码
</problem_statement>

First, determine whether the <problem_statement> requires code changes, an explanation, a plan, or analysis. Then follow the appropriate path:

If the task requires code changes:

If the task is a question or only requires creating a plan or analysis: respond directly without making code changes.

<prev_assistant>

All checks pass. Here's a summary of what was done:

Changes Made

`docker-entrypoint.sh`
Added support for two new environment variables in the tunnel modes (`socks`, `http-proxy`, `nativetun`, `portfw`):
- **`USQUE_HTTP2=true`** → passes `--http2` flag: switches connection from QUIC/HTTP3 to TCP/HTTP2 (useful when UDP/QUIC is blocked)
- **`USQUE_INSECURE=true`** → passes `--insecure` flag: skips TLS certificate verification (for troubleshooting HTTP/2 connection issues)

`README.md`
- Added `USQUE_HTTP2` and `USQUE_INSECURE` rows to the environment variables table
- Added a new **TCP/HTTP2 模式** section explaining when and how to use the new flags, including the new `endpoint_h2_v4`/`endpoint_h2_v6` config fields introduced in upstream v2.0.0

<current>

<request>

You are working on a task in the 'SuperNG6/docker-usque' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/docker-usque/docker-usque (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-10T07:04:42.016Z</current_datetime>

Consider the following problem statement:

<problem_statement>
review整个项目的代码
</problem_statement>

First, determine whether the <problem_statement> requires code changes, an explanation, a plan, or analysis. Then follow the appropriate path:

If the task requires code changes:

If the task is a question or only requires creating a plan or analysis: respond directly without making code changes.