9e921713-df59-4349-94fa-2c848cf46c76

<prev_user>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'jacksonpradolima/coleman4hcs' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/coleman4hcs/coleman4hcs (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-03-04T01:52:16.950Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
refactor: migrate to UV, pyproject.toml, ruff, mkdocs, and modern Python toolchain
</pr_title>

<pr_description>
Full modernization of project infrastructure: replace pip/requirements.txt with UV/pyproject.toml, add linting/formatting/type-checking/docs/release tooling, enforce Numpydoc docstrings, and add standard community files.

Package management & build
- `pyproject.toml` replaces `requirements.txt` + `pytest.ini` + `.pylintrc` — hatchling build backend, Python ≥3.14, optional

```
extras for `dev`, `docs`, `release`, `notebook`
- `Makefile` with self-documenting `help` target covering
install, lint, format, typecheck, test, docs, build, clean

### Linting, formatting, type checking
- **ruff** replaces pylint/flake8 — configured with `D`
(pydocstyle/numpy), `E`, `F`, `W`, `I`, `UP`, `B`, `SIM`, `N`
rules, line-length 120
- **pyright + ty** for static type checking
- **interrogate** for docstring coverage enforcement (fail-under
80%)
- `.pre-commit-config.yaml` with ruff, pre-commit-hooks,
conventional-commits, and a local `make check-precommit` hook

### Documentation
- **mkdocs-material** with mkdocstrings (numpy-style) and
mkdocs-jupyter for notebook rendering
- API reference stubs for all core modules
- All docstrings across 16 files converted to **Numpydoc**
style; module docstrings added to `__init__.py` files

### CI/CD workflows
- `docs.yml` — build + deploy to GitHub Pages
- `release.yml` — Python Semantic Release → uv build → syft SBOM
→ Sigstore signing → GitHub Release
- `codecov.yml` / `pylint.yml` updated to use `uv sync` / `ruff`

### Community &amp;amp; governance files
- `SECURITY.md`, `CONTRIBUTING.md`, `CITATION.cff` (from
provided BibTeX), `CHANGELOG.md`

### Other
- `.devcontainer/devcontainer.json` with UV auto-install, ruff/
pylance extensions
- `analysis.ipynb` moved to `notebooks/` and converted to a
**marimo** notebook (`notebooks/analysis.py`)
- `README.md` updated for UV workflow, Python 3.14+, Makefile
commands, notebook path
</pr_description>

## Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_new>
<comment_id>3886032038</comment_id>
```

```
<author>@jacksonpradolima</author>
@copilot please, fix.
</comment_new>
```

```
</pr_comments>

<pr_reviews>

<comment_thread>
<file>.devcontainer/devcontainer.json:7</file>
<original_commit>1ff8015</original_commit>
```

```
<comment_new>
<comment_id>2881162088</comment_id>
<author>@jacksonpradolima</author>
Why not use the make commands available?
</comment_new>
```

```
</comment_thread>

<comment_thread>
<file>.devcontainer/devcontainer.json:23</file>
<original_commit>1ff8015</original_commit>
```

```
<comment_new>
<comment_id>2881164018</comment_id>
<author>@jacksonpradolima</author>
should consider:
 "vscode": {
      "settings": {
        "python.defaultInterpreterPath": ".venv/bin/python",
        "python.testing.pytestEnabled": true,
        "python.testing.pytestArgs": [],
        "ruff.enable": true
      },

or not?
</comment_new>
```

```
</comment_thread>

<comment_thread>
<file>mkdocs.yml:1</file>
<original_commit>1ff8015</original_commit>
```

```
<comment_new>
<comment_id>2881344316</comment_id>
<author>@jacksonpradolima</author>
```

```
let's migrate from mkdocs to Zensical
</comment_new>
```

</comment_thread>

</pr_reviews>

</comments>

The last **15** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement>

Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.
    - Is it addressed to you or someone else, e.g. "Hey @username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>

<prev_assistant>

All three review comments have been addressed in commit `47252c0`:

1. **`.devcontainer/devcontainer.json` line 7** — Replaced the raw `curl | bash && uv sync && uv run pre-commit install` command with `make install && make pre-commit-install`, which properly delegates to the Makefile targets (including UV auto-installation via `ensure-uv`).

2. **`.devcontainer/devcontainer.json` line 23** — Added `python.testing.pytestEnabled: true`, `python.testing.pytestArgs: []`, and `ruff.enable: true` to the VSCode settings block.

3. **`mkdocs.yml` line 1 (Zensical migration)** — Replaced `mkdocs-material` with `zensical` in `pyproject.toml` docs dependencies, and updated all `mkdocs` CLI references to `zensical` in the Makefile, docs workflow, and README. The `mkdocs.yml` config file is kept since Zensical reads the same format.

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'jacksonpradolima/coleman4hcs' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/coleman4hcs/coleman4hcs (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-03-06T00:31:39.105Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
refactor: migrate to UV, pyproject.toml, ruff, Zensical, and modern Python toolchain
</pr_title>

<pr_description>
Full modernization of project infrastructure: replace pip/requirements.txt with UV/pyproject.toml, add linting/formatting/type-checking/docs/release tooling, enforce Numpydoc docstrings, and add standard community files.

```
### Package management &amp;amp; build
- `pyproject.toml` replaces `requirements.txt` + `pytest.ini` +
`.pylintrc` — hatchling build backend, Python ≥3.14, optional
extras for `dev`, `docs`, `release`, `notebook`
- `Makefile` with self-documenting `help` target covering
install, lint, format, typecheck, test, docs, build, clean

### Linting, formatting, type checking
- **ruff** replaces pylint/flake8 — configured with `D`
(pydocstyle/numpy), `E`, `F`, `W`, `I`, `UP`, `B`, `SIM`, `N`
rules, line-length 120
- **pyright + ty** for static type checking
- **interrogate** for docstring coverage enforcement (fail-under
80%)
- `.pre-commit-config.yaml` with ruff, pre-commit-hooks,
conventional-commits, and a local `make check-precommit` hook

### Documentation
- **Zensical** (successor to mkdocs-material) with mkdocstrings
(numpy-style) and mkdocs-jupyter for notebook rendering
- API reference stubs for all core modules
- All docstrings across 16 files converted to **Numpydoc**
style; module docstrings added to `__init__.py` files

### CI/CD workflows
- `docs.yml` — build + deploy to GitHub Pages
- `release.yml` — Python Semantic Release → uv build → syft SBOM
→ Sigstore signing → GitHub Release
- `codecov.yml` / `pylint.yml` updated to use `uv sync` / `ruff`

### Community &amp;amp; governance files
- `SECURITY.md`, `CONTRIBUTING.md`, `CITATION.cff` (from
provided BibTeX), `CHANGELOG.md`

### Other
- `.devcontainer/devcontainer.json` using `make install && make
pre-commit-install`, with pytest, ruff, and pylance VSCode
settings
- `analysis.ipynb` moved to `notebooks/` and converted to a
**marimo** notebook (`notebooks/analysis.py`)
- `README.md` updated for UV workflow, Python 3.14+, Makefile
commands, notebook path
</pr_description>

## Comments on the PR (you are @copilot in this section)
```

```
<comments>

<pr_comments>

<comment_old>
<author>@jacksonpradolima</author>
@copilot please, fix.
</comment_old>

</pr_comments>

<pr_reviews>

<comment_thread_resolved>
<file>.devcontainer/devcontainer.json:7</file>
<original_commit>1ff8015</original_commit>

<comment_old>
<author>@jacksonpradolima</author>
Why not use the make commands available?
</comment_old>

<comment_old>
<author>@copilot</author>
Updated `postCreateCommand` to use `make install && make pre-
commit-install` instead of raw UV commands. This also handles UV
installation via the `ensure-uv` target in the Makefile. See
47252c0.
</comment_old>

</comment_thread_resolved>

<comment_thread_resolved>
<file>.devcontainer/devcontainer.json:23</file>
<original_commit>1ff8015</original_commit>

<comment_old>
<author>@jacksonpradolima</author>
should consider:
 "vscode": {
      "settings": {
        "python.defaultInterpreterPath": ".venv/bin/python",
        "python.testing.pytestEnabled": true,
        "python.testing.pytestArgs": [],
        "ruff.enable": true
      },
```

```
or not?
</comment_old>

<comment_old>
<author>@copilot</author>
Added `python.testing.pytestEnabled: true`,
`python.testing.pytestArgs: []`, and `ruff.enable: true` to the
VSCode settings. See 47252c0.
</comment_old>

</comment_thread_resolved>

<comment_thread_resolved>
<file>mkdocs.yml:1</file>
<original_commit>1ff8015</original_commit>

<comment_old>
<author>@jacksonpradolima</author>
let's migrate from mkdocs to Zensical
</comment_old>

<comment_old>
<author>@copilot</author>
Migrated from mkdocs-material to Zensical in `pyproject.toml`,
`Makefile`, `.github/workflows/docs.yml`, and `README.md`. The
`mkdocs.yml` config file is kept as-is since Zensical reads the
same format. See 47252c0.
</comment_old>

</comment_thread_resolved>

</pr_reviews>

<pr_comments>

<comment_old>
<author>@copilot</author>

&gt; @copilot please, fix.

All three review items addressed in 47252c0:
- Devcontainer now uses `make install && make pre-commit-
install`
- Added `python.testing.pytestEnabled`,
`python.testing.pytestArgs`, and `ruff.enable` settings
- Migrated from MkDocs to Zensical
```

```
&gt; [!WARNING]
&gt;
&gt;


</comment_old>

  <comment_new>
  <comment_id>3900407311</comment_id>
  <author>@jacksonpradolima</author>
  @copilot please,fix.
  Also, include py.typed files.
  </comment_new>

</pr_comments>

<pr_reviews>

<comment_thread>
<file>coleman4hcs/utils/monitor.py:26-47</file>
<original_commit>47252c0</original_commit>

  <comment_new>
  <comment_id>2893035063</comment_id>
  <author>@jacksonpradolima</author>
  Keep the notes about schemas as notees in the dcostring.
  </comment_new>

</comment_thread>

<comment_thread>
<file>coleman4hcs/policy.py:522</file>
<original_commit>47252c0</original_commit>

  <comment_new>
  <comment_id>2893072026</comment_id>
  <author>@jacksonpradolima</author>
  missing this information
  </comment_new>

</comment_thread>

</pr_reviews>

</comments>

----
The last **18** git commits in this branch are the changes you
```

```
have made so far. Use those as your change commit history.
</problem_statement>
```

```
Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the
<comments> before making any changes. You will only address the
<comment_new> comments. Reply to new comments as you address them.
Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a
suggestion.
    - Is it addressed to you or someone else, e.g. "Hey
@username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can
stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and
ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>
```