a7ac6ebb-d2d8-4a05-82bb-21bf31e2f9c8

<prev_user>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'counterfact/api-simulator' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/api-simulator/api-simulator (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-08T03:48:48.202Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
Add three design proposals for multiple API support (#1718)
</pr_title>

<pr_description>
Summary

Issue #1718 asks for three distinct designs for running multiple OpenAPI specs under a single Counterfact server. This PR adds those designs as issue-proposal files (auto-converted to GitHub issues on merge).

Manual acceptance tests

- [ ] Each proposal file has valid YAML front matter with `parentIssue: 1718`, a non-empty `title`, and a non-empty body
- [ ] All three proposals address root-path determination (explicit prefix → spec `basePath`/`servers[]` → fallback)
- [ ] All three proposals describe an isolated per-API generated code layout that prevents type-name collisions
- [ ] Each design is meaningfully distinct from the other two (CLI flags vs. config file vs. directory convention)
- [ ] Backwards compatibility with today's single-spec usage is addressed in every proposal
- [ ] Secondary implications (REPL, Swagger UI, watch mode) are covered in each proposal

Tasks

- Added `.github/issue-proposals/design-multiple-apis-repeated-spec-flag.md` — **Design A**: repeat `--spec`/`--destination`/`--prefix` per API on the CLI; minimal backwards-compatible extension
- Added `.github/issue-proposals/design-multiple-apis-config-file.md` — **Design B**: typed `counterfact.config.ts` with an `apis` array and a `defineConfig` helper (Vite/Jest pattern)
- Added `.github/issue-proposals/design-multiple-apis-workspace-directory.md` — **Design C**: convention-over-configuration workspace directory scan; Counterfact auto-discovers any subdirectory containing an OpenAPI file, with an optional `counterfact.workspace.yaml` sidecar for overrides
</pr_description>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_new>
<comment_id>4072648668</comment_id>
<author>@pmcelhaney</author>
Create a variant of the CLI one where the prefix is specified as

--spec optional-prefix+openapi-spec-location.yaml

Also remove the --destination flag. All API definitions need to be siblings in a shared directory so that there can be a

```
root _.context.ts shared by all.
</comment_new>
```

</pr_comments>

</comments>

The last **2** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement><rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.
    - Is it addressed to you or someone else, e.g. "Hey @username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>

<prev_assistant>

Updated Design A with the requested changes:

1. **`prefix+spec` syntax** — the optional route prefix is now embedded directly in the `--spec` flag value using a `+` separator (e.g. `--spec /users+./specs/users.yaml`). No separate `--prefix` or `--destination` flags needed.

2. **Shared destination directory** — removed the per-API `--destination` flag. All APIs generate into the single `[destination]` argument as sibling subdirectories, enabling a root `_.context.ts` that

is shared across all APIs.

The updated example invocation is now:
```sh
counterfact ./api \
  --spec /users+./specs/users.yaml \
  --spec /products+./specs/products.yaml \
  --port 3100 --serve --generate
```

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'counterfact/api-simulator' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/api-simulator/api-simulator (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-08T18:25:21.731Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
Add three design proposals for multiple API support (#1718)
</pr_title>

<pr_description>
Turn this into an ADR once the ADR PR is merged. Will definitely want David's advice on the ADR before moving forward.

Summary

Issue #1718 asks for three distinct designs for running multiple OpenAPI specs under a single Counterfact server. This PR adds those designs as issue-proposal files (auto-converted to GitHub issues on merge).

Manual acceptance tests

- [ ] Each proposal file has valid YAML front matter with `parentIssue: 1718`, a non-empty `title`, and a non-empty body
- [ ] All three proposals address root-path determination (explicit prefix → spec `basePath`/`servers[]` → fallback)
- [ ] All three proposals describe a generated code layout that prevents type-name collisions
- [ ] Each design is meaningfully distinct from the other two (CLI flags vs. config file vs. directory convention)
- [ ] Backwards compatibility with today's single-spec usage is addressed in every proposal
- [ ] Secondary implications (REPL, Swagger UI, watch mode) are covered in each proposal

Tasks

- Added `.github/issue-proposals/design-multiple-apis-repeated-spec-flag.md` — **Design A**: repeat `--spec [prefix+]location` per API on the CLI; prefix is embedded in the flag value before a `+`; all APIs share a single destination directory as siblings so a root `_.context.ts` can be shared across all APIs
- Added `.github/issue-proposals/design-multiple-apis-config-file.md` — **Design B**: typed `counterfact.config.ts` with an `apis` array and a `defineConfig` helper (Vite/Jest pattern)
- Added `.github/issue-proposals/design-multiple-apis-workspace-directory.md` — **Design C**: convention-over-configuration workspace directory scan; Counterfact auto-discovers any subdirectory containing an OpenAPI file, with an optional `counterfact.workspace.yaml` sidecar for overrides
</pr_description>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_old>

<author>@pmcelhaney</author>
Create a variant of the CLI one where the prefix is specified as

--spec optional-prefix+openapi-spec-location.yaml

Also remove the --destination flag. All API definitions need to be siblings in a shared directory so that there can be a root _.context.ts shared by all.
</comment_old>

<comment_old>
<author>@copilot</author>

> Create a variant of the CLI one where the prefix is specified as
>
> --spec optional-prefix+openapi-spec-location.yaml...

Done in 989ee72. Design A now uses `--spec [prefix+]location` syntax (prefix embedded before a `+` in the flag value, no separate `--prefix` flag) and drops `--destination`. All APIs share a single destination directory as siblings, with a root `_.context.ts` accessible to all API route handlers.
</comment_old>

<comment_new>
<comment_id>4077316220</comment_id>
<author>@pmcelhaney</author>
Replace these three issues with an ADR. The status of the ADR will draft. We have not taken a decision yet.
</comment_new>

</pr_comments>

</comments>

The last **4** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement><rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.

```
    - Is it addressed to you or someone else, e.g. "Hey
@username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you
can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment
and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>
```