ac50a0f3-10e2-4bb0-86b7-47a89f431a

<prev_user>

<request>

You are working on an issue in the 'github/gh-aw' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/gh-aw/gh-aw (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-03-02T12:29:27.541Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section details on the original issue you should resolve

<issue_title>close-older-issues closes issues from different calling workflows</issue_title>
<issue_description>## Problem

`Explore: Live Elasticsearch` closed https://github.com/elastic/ai-github-actions-playground/issues/1138, which belongs to `medium-ideas-man`.

When multiple workflows call the same reusable workflow via `workflow_call`, `close-older-issues` can't distinguish between them:

1. Shared workflow ID. `GH_AW_WORKFLOW_ID` is derived from the reusable workflow's filename at compile time, not the caller's. All callers of `gh-aw-internal-gemini-cli.lock.yml` share the same ID and close each other's issues.

2. Search substring matching. GitHub search for `"gh-aw-workflow-id: gh-aw-internal-gemini-cli"` also matches issues containing `gh-aw-internal-gemini-cli-web-search`, crossing even

````
    different reusable workflows. Adding `-->` to the query doesn't
    help — GitHub tokenizes on HTML comment delimiters.

    ## Suggested fixes

    **Workflow ID:** Incorporate the calling workflow's identity
    into the marker. Within a `workflow_call`, `$
    {{ github.repository }}/${{ github.workflow }}` would uniquely
    identify the caller across repos. Since `GH_AW_WORKFLOW_ID` is
    also used for branch names, this likely needs a separate env var
    for the marker.

    **Search precision:** GitHub search can't exact-match these
    markers, so add a post-search filter on the issue body — the
    same pattern `findCommentsWithTrackerId` already uses:

    ```js
    const exactMarker = `<!-- gh-aw-workflow-id: ${workflowId} -->`;
    const filtered = results.filter(item =>
    item.body?.includes(exactMarker));
    ```</issue_description>

    ## Comments on the Issue (you are @copilot in this section)

    <comments>
    </comments>

    </problem_statement>


  Implement the necessary changes to the repository so that the
  requirements specified in the <problem_statement> are met.
````

<prev_assistant>

The changes have been committed and pushed. Here's a summary of what was implemented:

Summary

This fix addresses two distinct issues that cause `close-older-issues` to close issues from different calling workflows:

Problem 1: Shared Workflow ID

When multiple workflows call the same reusable workflow via `workflow_call`, they all share the same `GH_AW_WORKFLOW_ID` (derived from the reusable file at compile time). This caused all callers to use the same marker and close each other's issues.

Fix: Added `GH_AW_CALLER_WORKFLOW_ID: "${{ github.repository }}/${{ github.workflow }}"` to the safe_outputs job env vars. This is evaluated at runtime and uniquely identifies each calling workflow. In `create_issue.cjs` and `create_discussion.cjs`, we now use `callerWorkflowId || workflowId` as the effective marker ID — so when `GH_AW_CALLER_WORKFLOW_ID` is set (which it always will be post-recompile), it takes precedence.

Problem 2: Search Substring Matching

GitHub search for `"gh-aw-workflow-id: foo"` could match issues containing `"gh-aw-workflow-id: foo-bar"` because GitHub tokenizes on delimiters.

Fix: Added an exact-body post-search filter in `close_older_issues.cjs` and `close_older_discussions.cjs`:
```javascript
const exactMarker = `<!-- gh-aw-workflow-id: ${workflowId} -->`;
const filtered = results.filter(item =>
item.body?.includes(exactMarker));
```

This ensures only issues with the exact marker in their body are closed. For discussions, the `body` field was also added to the GraphQL search query to enable this filtering.

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'github/gh-aw' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/gh-aw/gh-aw (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-03-02T13:14:55.446Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
fix: prevent close-older-issues from closing issues across different calling workflows
</pr_title>

<pr_description>
When multiple workflows call the same reusable workflow via `workflow_call`, they share the same compile-time `GH_AW_WORKFLOW_ID`, causing `close-older-issues` to close each other's issues. Additionally, GitHub search tokenizes on delimiters, so searching for `"gh-aw-workflow-id: foo"` matches issues from `"gh-aw-workflow-id: foo-bar"`.

Changes

- **New `GH_AW_CALLER_WORKFLOW_ID` env var** — added to the safe_outputs job, set at runtime to `${{ github.repository }}/${{ github.workflow }}`. Unlike `GH_AW_WORKFLOW_ID` (compile-time, used for branch names), this uniquely identifies the *calling* workflow even when multiple callers share the same reusable workflow file.

- **Caller-specific markers** — `create_issue.cjs` and `create_discussion.cjs` now use `GH_AW_CALLER_WORKFLOW_ID || GH_AW_WORKFLOW_ID` as `effectiveWorkflowId` for both writing the `<!-- gh-aw-workflow-id: ... -->` marker into the body and for the `closeOlderIssues` search.

- **Exact-body post-search filter** — `close_older_issues.cjs` and `close_older_discussions.cjs` now filter search results by checking `item.body?.includes(exactMarker)` after the GitHub API search, since GitHub search cannot guarantee exact token matches:
  ```js
  const exactMarker = `<!-- gh-aw-workflow-id: ${workflowId} -->`;
  const filtered = results.filter(item => item.body?.includes(exactMarker));
  ```

```

- **Discussion GraphQL query** — added `body` field to the discussion search query to enable the exact-body filter.

- **Tests** — updated mock data to include `body` fields; added new test cases covering the substring-match exclusion scenario for both issues and discussions.

- **Recompiled lock files** — all 165 workflows updated to include the new `GH_AW_CALLER_WORKFLOW_ID` env var.

> [!WARNING]
>
>

<details>

<summary>Original prompt</summary>

>
> ----
>
> *This section details on the original issue you should resolve*
>
> <__filter_complete__></__filter_complete__></details><issue_title>close-older-issues closes issues from different calling workflows</issue_title>
><issue_description>## Problem
>
> `Explore: Live Elasticsearch` closed https://github.com/elastic/ai-github-actions-playground/issues/1138, which belongs to `medium-ideas-man`.
>
> When multiple workflows call the same reusable workflow via `workflow_call`, `close-older-issues` can't distinguish between them:
>
> **1. Shared workflow ID.** `GH_AW_WORKFLOW_ID` is derived from the reusable workflow's filename at compile time, not the caller's. All callers of `gh-aw-internal-gemini-cli.lock.yml` share the same ID and close each other's issues.
```

>
> **2. Search substring matching.** GitHub search for `"gh-aw-workflow-id: gh-aw-internal-gemini-cli"` also matches issues containing `gh-aw-internal-gemini-cli-web-search`, crossing even different reusable workflows. Adding `-->` to the query doesn't help — GitHub tokenizes on HTML comment delimiters.
>
> ## Suggested fixes
>
> **Workflow ID:** Incorporate the calling workflow's identity into the marker. Within a `workflow_call`, `${{ github.repository }}/${{ github.workflow }}` would uniquely identify the caller across repos. Since `GH_AW_WORKFLOW_ID` is also used for branch names, this likely needs a separate env var for the marker.
>
> **Search precision:** GitHub search can't exact-match these markers, so add a post-search filter on the issue body — the same pattern `findCommentsWithTrackerId` already uses:
>
> ```js
> const exactMarker = `<!-- gh-aw-workflow-id: ${workflowId} -->`;
> const filtered = results.filter(item => item.body?.includes(exactMarker));
> ```</issue_description>
>
> ## Comments on the Issue (you are @copilot in this section)
>
><comments>
></comments>
></pr_description>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_new>
<comment_id>3984314443</comment_id>
<author>@pelikhan</author>
@copilot add a new xml tag gh-aw-workflow-call-id for the call identifier and leave the gh-aw-workflow-id tag unchanged
</comment_new>

```
</pr_comments>

</comments>

----
The last **2** git commits in this branch are the changes you
have made so far. Use those as your change commit history.
</problem_statement>

Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the
<comments> before making any changes. You will only address the
<comment_new> comments. Reply to new comments as you address them.
Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a
suggestion.
    - Is it addressed to you or someone else, e.g. "Hey
@username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can
stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and
ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>
```