af95e4d5-17e3-486d-8163-7d479b098

<prev_user>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'OpenCCU/OpenCCU' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/OpenCCU/OpenCCU (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-02-22T09:10:03.272Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
fwinstall.sh: resize_rootfs code review fixes (7 changes)
</pr_title>

<pr_description>
Seven targeted fixes to `resize_rootfs()` and the zip re-unarchive path in `fwinstall.sh`, addressing correctness, safety, and output cleanliness issues.

Changes

- **[Critical] Add `mkfs.ext4` on enlarge path** — after `partprobe`/before post-move `e2fsck`, mirrors what the shrink path already does; without it the subsequent `mount /rootfs` fails on a stale/moved filesystem
- **Scope all locals** — all variables in `resize_rootfs()` now declared `local` to prevent unintended global side-effects

- **Quiet `e2fsck`** — both calls drop `-v -C 0` and redirect to `/dev/null 2>&1`; verbose fsck output was polluting the HTML-formatted user-facing stream
- **`sync` before `e2image`** — flushes write cache after `resize2fs` shrink before the block-level image move
- **Fix `echo` vs `echo -ne`** — `echo "userfs already aligned, "` → `echo -ne` for consistent inline output
- **Validate `label-id`** — instead of copying the label-id dynamically, validate that the disk's existing `label-id` is `0xdeedbeef` (the fixed OpenCCU identifier); return an error if it is not, ensuring `resize_rootfs()` only operates on genuine OpenCCU disks; sfdisk heredocs continue to hard-code `0xdeedbeef`
- **Restart progress indicator on re-unarchive** — zip path was killing the `awk` progress loop before the second `unzip`; restart it with a fresh `PROGRESS_PID` + `trap`

</pr_description>

<stacked_pr_context>
The pull request you are currently working on is a stacked pull request on top of another pull request. The base branch is `pr_recoveryfs_resize_rootfs`, not the default branch `master`. If you are asked to fix CI, build, test, or workflow failures, check the GitHub Actions workflow runs for the original branch (`pr_recoveryfs_resize_rootfs`) first. If you don't find relevant failures there, then check your branch (`copilot/pr-recoveryfs-resize-rootfs`).
</stacked_pr_context>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_old>
<author>@jens-maus</author>
@copilot The changes with copying the label-id over instead of fixing it to 0xdeefbeef are not really required. The 0xdeedbeef partuuid is something that is clearly defined and fixed in a OpenCCU project. In fact if an image is supplied that won't have an 0xdeedbeef partuuid it should not be taken at all and an

error message returned instead.
</comment_old>

<comment_old>
<author>@copilot</author>

> @copilot The changes with copying the label-id over instead of fixing it to 0xdeefbeef are not really required. The 0xdeedbeef partuuid is something that is clearly defined and fixed in a OpenCCU proj...

Done in e7be692. The dynamic label-id extraction is replaced with a validation check: if `sfdisk -d` shows a label-id other than `0xdeedbeef`, `resize_rootfs()` now returns an error immediately. Both sfdisk heredocs keep the hard-coded `0xdeedbeef`.
</comment_old>

<comment_new>
<comment_id>3940530035</comment_id>
<author>@jens-maus</author>
@coderabbitai Review
</comment_new>

<comment_new>
<comment_id>3940536366</comment_id>
<author>@jens-maus</author>
@coderabbitai resume
</comment_new>

</pr_comments>

<pr_reviews>

<comment_thread>
<file>buildroot-external/package/recovery-system/external/overlay/base/bin/fwinstall.sh:510</file>
<original_commit>e7be692</original_commit>

<comment_new>
<comment_id>2837409129</comment_id>
<author>@jens-maus</author>
It seems killing PROGRESS_PID is missing here.
</comment_new>

</comment_thread>

<comment_thread>

<file>buildroot-external/package/recovery-system/external/overlay/base/bin/fwinstall.sh:583</file>
<original_commit>e7be692</original_commit>

<comment_new>
<comment_id>2837411933</comment_id>
<author>@jens-maus</author>
After this line should PROGRESS_PID not be killed to stop the dot progress output right away?
</comment_new>

</comment_thread>

</pr_reviews>

</comments>

The last **3** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement>

Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.
    - Is it addressed to you or someone else, e.g. "Hey @username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>

A **CI/Build Failure** has been mentioned in the problem statement, make sure to follow your instructions for addressing CI/Build Failures.

<prev_assistant>

Both issues are addressed in commit `e2d5d53`:

- **Line 510** (after first unzip): Added `kill ${PROGRESS_PID} 2>/dev/null || true` so the progress dots stop as soon as the initial unarchiving finishes and before the image analysis/resize logic runs.
- **Line 585** (after re-unarchive unzip): Added the same kill immediately after the second unzip completes, stopping the restarted progress indicator right away rather than waiting for the final cleanup at line 601.

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'OpenCCU/OpenCCU' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/OpenCCU/OpenCCU (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-02-22T09:16:34.108Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
fwinstall.sh: resize_rootfs code review fixes (7 changes)
</pr_title>

<pr_description>

- [x] Explore the file and understand the changes needed
- [x] 1. Add missing `mkfs.ext4` on the enlarge path
- [x] 2. Declare all variables `local` in `resize_rootfs()`
- [x] 3. Quiet `e2fsck` verbose output
- [x] 4. Add `sync` before `e2image` move
- [x] 5. Fix inconsistent `echo` vs `echo -ne`
- [x] 6. Validate label-id is `0xdeedbeef` (error out if not)
- [x] 7. Restart progress indicator during re-unarchive in zip path
- [x] Kill `PROGRESS_PID` after first unzip (line ~510) to stop dots during analysis
- [x] Kill `PROGRESS_PID` after re-unarchive unzip (line ~585) to stop restarted dots immediately

</pr_description>

<stacked_pr_context>
The pull request you are currently working on is a stacked pull request on top of another pull request. The base branch is `pr_recoveryfs_resize_rootfs`, not the default branch `master`. If you are asked to fix CI, build, test, or workflow failures, check the GitHub Actions workflow runs for the original branch (`pr_recoveryfs_resize_rootfs`) first. If you don't find relevant failures there, then check your branch (`copilot/pr-recoveryfs-resize-rootfs`).
</stacked_pr_context>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_new>
<comment_id>3940525830</comment_id>
<author>@jens-maus</author>
@copilot The changes with copying the label-id over instead of fixing it to 0xdeefbeef are not really required. The 0xdeedbeef partuuid is something that is clearly defined and fixed in a OpenCCU project. In fact if an image is supplied that won't have an 0xdeedbeef partuuid it should not be taken at all and an error message returned instead.
</comment_new>

<comment_old>
<author>@copilot</author>

> @copilot The changes with copying the label-id over instead of fixing it to 0xdeefbeef are not really required. The 0xdeedbeef partuuid is something that is clearly defined and fixed in a OpenCCU proj...

Done in e7be692. The dynamic label-id extraction is replaced with a validation check: if `sfdisk -d` shows a label-id other than `0xdeedbeef`, `resize_rootfs()` now returns an error immediately. Both sfdisk heredocs keep the hard-coded `0xdeedbeef`.
</comment_old>

<comment_new>
<comment_id>3940530035</comment_id>
<author>@jens-maus</author>
@coderabbitai Review
</comment_new>

<comment_new>
<comment_id>3940536366</comment_id>
<author>@jens-maus</author>
@coderabbitai resume
</comment_new>

</pr_comments>

<pr_reviews>

<comment_thread>
<file>buildroot-external/package/recovery-system/external/overlay/base/bin/fwinstall.sh:511</file>
<original_commit>e7be692</original_commit>

<comment_old>
<author>@jens-maus</author>
It seems killing PROGRESS_PID is missing here.
</comment_old>

<comment_old>
<author>@copilot</author>
Fixed in e2d5d53. Added `kill ${PROGRESS_PID} 2>/dev/null || true` immediately after the first unzip succeeds, so the dots stop before the image analysis begins.
</comment_old>

```
</comment_thread>

<comment_thread_resolved>
<file>buildroot-external/package/recovery-system/external/
overlay/base/bin/fwinstall.sh:584</file>
<original_commit>e7be692</original_commit>

<comment_old>
<author>@jens-maus</author>
After this line should PROGRESS_PID not be killed to stop the
dot progress output right away?
</comment_old>

<comment_old>
<author>@copilot</author>
Fixed in e2d5d53. Added `kill ${PROGRESS_PID} 2>/dev/null ||
true` right after the re-unarchive unzip completes, stopping the
restarted progress indicator immediately.
</comment_old>

</comment_thread_resolved>

<comment_thread>
<file>buildroot-external/package/recovery-system/external/
overlay/base/bin/fwinstall.sh:601</file>
<original_commit>e2d5d53</original_commit>

  <comment_new>
  <comment_id>2837429151</comment_id>
  <author>@jens-maus</author>
  Is this line still required because PROGRESS_PID is killed
  beforehand. What about the trap to remove the state file
  upon exit? Should it be retained?
  </comment_new>

</comment_thread>

</pr_reviews>

</comments>

----
The last **4** git commits in this branch are the changes you
have made so far. Use those as your change commit history.
</problem_statement>
```

Analyze and determine if action or explanation is needed

<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.
    - Is it addressed to you or someone else, e.g. "Hey @username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>

A **CI/Build Failure** has been mentioned in the problem statement, make sure to follow your instructions for addressing CI/Build Failures.