cc61dedc-ce97-4ba6-a7ba-119c2a918c0b

<prev_user>

<request>

You are working on a task in the 'githubnext/agentics' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/agentics/agentics (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-06-26T05:28:57.711+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>
Create a PR that updates the AWs in .github/workflows to use permissions.copilot-requests: write.
</problem_statement>

First, determine whether the <problem_statement> requires code changes, an explanation, a plan, or analysis. Then follow the appropriate path:

If the task requires code changes:

If the task is a question or only requires creating a plan or analysis: respond directly without making code changes.

<prev_assistant>

PR #362 is open: https://github.com/githubnext/agentics/pull/362

What was done:
- Changed `permissions: read-all` → `permissions: { all: read, copilot-

requests: write }` in all 5 source workflows under `.github/workflows/`
- `all: read` is the object-syntax equivalent of the `read-all`
shorthand (confirmed by the gh-aw compiler)
- Recompiled all lock files — `copilot-requests: write` now appears in
the relevant compiled jobs
- Validated with `gh aw compile --validate`: 0 errors, 0 warnings

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'githubnext/agentics' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/agentics/agentics (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-06-26T05:36:25.337+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
Add `copilot-requests: write` to all .github/workflows
</pr_title>

<pr_description>
All 5 agentic workflows in `.github/workflows` lacked the `copilot-requests: write` permission required by the Copilot API.

Changes

- **Source `.md` files** — replaced `permissions: read-all` (string shorthand) with the explicit object form that preserves full read access and adds the write permission:
  ```yaml
  ```

```
  permissions:
    all: read
    copilot-requests: write
  ```
- **Lock files** — recompiled all 5 `.lock.yml` files; `copilot-requests: write` now appears in the relevant compiled jobs

Affected workflows: `daily-repo-goals`, `daily-workflow-sync`, `import-workflow`, `link-checker`, `maintainer`.
</pr_description>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_new>
<comment_id>4806668528</comment_id>
<author>@pelikhan</author>
@copilot replace permissions.all.read with minimal permissions. use gh-aw compile to ensure there are enough.
</comment_new>

</pr_comments>

</comments>

The last **2** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement><rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. Treat <comment_old> comments as context only and do not make changes solely to satisfy them.
* Only act on <comment_new> comments that explicitly mention you (@copilot). To understand the context of comments that explicitly mention you, you may use other comments that do not explicitly mention you. Do not act on comments that don't explicitly mention you or reply to them, even if they are marked as <comment_new>.
* If the PR author has pushed back on or rejected a suggestion in a thread, do not act on that thread.
* For each comment you decide to act on, determine:
    - If it is a request for changes, a question on the code, or a suggestion.
    - Is it a general comment or praise.

```
* If there are no comments you need to address or reply to, you
can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment
and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>




<system_reminder>

</system_reminder>
```

<prompt>

```
@copilot replace permissions.all.read with minimal permissions. use
gh-aw compile to ensure there are enough.
```