d4790eea-9138-468f-9b93-a0959f83a370

<prev_user>

<request>

You are working on a task in the 'k0swe/kel-agent' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/kel-agent/kel-agent (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-21T15:45:56.620+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>
Research and propose a fix for the missing artifact in Debian release https://github.com/k0swe/kel-agent/actions/runs/24731479727/job/72346842373.
</problem_statement>

First, determine whether the <problem_statement> requires code changes, an explanation, a plan, or analysis. Then follow the appropriate path:

If the task requires code changes:

If the task is a question or only requires creating a plan or analysis: respond directly without making code changes.

<prev_assistant>

<plan>
Root cause:

- The Debian package is built inside Docker with `dpkg-buildpackage`, which writes artifacts to `../`.
- In this workflow, only `${{ github.workspace }}` is bind-mounted into the container, so `../kel-agent_*_${{ matrix.arch }}.deb` is outside the mounted path.
- Those files exist only in the container filesystem and are lost when the container exits.
- The host-side `cp ../kel-agent_*_${{ matrix.arch }}.deb dist/` then fails, so upload is skipped.

Proposed fix:
- Move artifact collection into the Docker command, before container exit, copying the generated `.deb` from `../` into a `dist/` directory under `${{ github.workspace }}` (which is mounted).
- Remove the host-side `cp ../kel-agent_*_${{ matrix.arch }}.deb dist/` line.
- Keep upload step pointed at `dist/kel-agent_*_${{ matrix.arch }}.deb`.

Validation:
- Re-run the Debian matrix jobs (amd64/armhf/arm64) and confirm:
  - Build step no longer errors on `cp cannot stat`.
  - `Upload Debian artifact` runs and finds files.
  - Artifact names are present in each matrix job.
</plan>

<current>

<request>

You are working on a task in the 'k0swe/kel-agent' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/kel-agent/kel-agent (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-04-21T16:14:55.701+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>
Implement the plan:

Root cause:
- The Debian package is built inside Docker with `dpkg-buildpackage`, which writes artifacts to `../`.

- In this workflow, only `${{ github.workspace }}` is bind-mounted into the container, so `../kel-agent_*_${{ matrix.arch }}.deb` is outside the mounted path.
- Those files exist only in the container filesystem and are lost when the container exits.
- The host-side `cp ../kel-agent_*_${{ matrix.arch }}.deb dist/` then fails, so upload is skipped.

Proposed fix:
- Move artifact collection into the Docker command, before container exit, copying the generated `.deb` from `../` into a `dist/` directory under `${{ github.workspace }}` (which is mounted).
- Remove the host-side `cp ../kel-agent_*_${{ matrix.arch }}.deb dist/` line.
- Keep upload step pointed at `dist/kel-agent_*_${{ matrix.arch }}.deb`.

Validation:
- Re-run the Debian matrix jobs (amd64/armhf/arm64) and confirm:
  - Build step no longer errors on `cp cannot stat`.
  - `Upload Debian artifact` runs and finds files.
  - Artifact names are present in each matrix job.
</problem_statement>

First, determine whether the <problem_statement> requires code changes, an explanation, a plan, or analysis. Then follow the appropriate path:

If the task requires code changes:

If the task is a question or only requires creating a plan or analysis: respond directly without making code changes.