ddcb1b11-c311-4b12-a383-ca29b43526fe

<prev_user>

<request>

You are working on a task in the 'meshtastic/Meshtastic-Apple' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/Meshtastic-Apple/Meshtastic-Apple (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-05-17T18:45:40.560+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>
Is this implemented https://github.com/meshtastic/design/issues/37 if not create an issue that is likely to be picked up for implementation by an agent. iOS uses a confirmation dialog where android is using a popup the node db reset is on the device config view.
</problem_statement>

First, determine whether the <problem_statement> requires code changes, an explanation, a plan, or analysis. Then follow the appropriate path:

If the task requires code changes:

If the task is a question or only requires creating a plan or analysis: respond directly without making code changes.

<system_reminder>You have the capability to call multiple tools in a single response.
For maximum efficiency, whenever you need to perform multiple

```
  independent operations, ALWAYS call tools simultaneously whenever
  the actions can be done in parallel rather than sequentially (e.g.
  multiple reads/edits to different files). Especially when exploring
  repository, searching, reading files, viewing directories,
  validating changes. For example, you can read 3 different files in
  parallel, or edit different files in parallel. However, if some tool
  calls depend on previous calls to inform dependent values like the
  parameters, do NOT call these tools in parallel and instead call
  them sequentially (e.g. reading shell output from a previous command
  should be sequential as it requires the sessionID).</
  system_reminder>
```

<prev_assistant>

```
The feature is **not implemented**. I don't have permission to create
issues via the API, but here's the full analysis and the ready-to-file
issue:

---

## Current State (Not Implemented)

The iOS app has a NodeDB reset button in `DeviceConfig.swift` but it's
incomplete vs. the design spec:

1. **No "Preserve Favorites" toggle** — the confirmation dialog is a
plain `confirmationDialog` with a single destructive button.
2. **Always preserves favorites on-device** — `sendNodeDBReset`
hardcodes `adminPacket.nodedbReset = true` (the protobuf bool meaning
"preserve favorites = true"), so there's nirmationDialog` on the "Reset
NodeDB" button with a **Sheet** (SwiftUI `confirmationDialog`/`alert`
don't support custom views) that shows:
>   - A description of the reset action
>   - `Toggle("Preserve Favorites", isOn: $preserveFavorites)`
defaulting **on**
>   - Destructive "Reset" and "Cancel" buttons
> - Pass `preserveFavorites` to `sendNodeDBReset` and `clearDatabase`
>
> **2. `Meshtastic/Accessory/Accessory Manager/
AccessoryManager+ToRadio.swift`**
> - Update `sendNodeDBReset(fromUser:toUser:)` to accept
`preserveFavorites: Bool`
> - Replace hardcoded `adminPacket.nodedbReset = true` with
`adminPacket.nodedbReset = preserveFavorites`
>
> **3. `Meshtastic/Persistence/UpdateSwiftData.swift`**
```

> - Update `clearDatabase(includeRoutes:)` to add `preserveFavorites: Bool = false`
> - When `preserveFavorites == true`, skip deletion of `NodeInfoEntity` records where `favorite == true`
>
> **Acceptance Criteria:**
> - [ ] "Reset NodeDB" opens a sheet/dialog with a "Preserve Favorites" toggle (default: on)
> - [ ] Toggle **on** → sends `nodedbReset = true`, retains `NodeInfoEntity` where `favorite == true` locally
> - [ ] Toggle **off** → sends `nodedbReset = false`, fully clears all nodes locally (current behaviour)
> - [ ] Factory Reset flow is unaffected
> - [ ] All existing tests pass
>
> **References:** meshtastic/protobufs#791 · https://github.com/meshtastic/design/issues/37

<current>

<request>

You are working on a task in the 'meshtastic/Meshtastic-Apple' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/Meshtastic-Apple/Meshtastic-Apple (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-05-17T18:53:30.026+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>
Factory reset has an option in the confirmation dialog in the same view
</problem_statement>

First, determine whether the <problem_statement> requires code changes, an explanation, a plan, or analysis. Then follow the appropriate path:

```
**If the task requires code changes:**

**If the task is a question or only requires creating a plan or
analysis:** respond directly without making code changes.

<system_reminder>You have the capability to call multiple tools in a
single response.
For maximum efficiency, whenever you need to perform multiple
independent operations, ALWAYS call tools simultaneously whenever
the actions can be done in parallel rather than sequentially (e.g.
multiple reads/edits to different files). Especially when exploring
repository, searching, reading files, viewing directories,
validating changes. For example, you can read 3 different files in
parallel, or edit different files in parallel. However, if some tool
calls depend on previous calls to inform dependent values like the
parameters, do NOT call these tools in parallel and instead call
them sequentially (e.g. reading shell output from a previous command
should be sequential as it requires the sessionID).</
system_reminder>
```