e962284c-8354-4a6c-8578-89463a24fc

<prev_user>

<request>

You are working on a task in the 'AliceJump/ok-end-field' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/ok-end-field/ok-end-field (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-05-14T21:19:25.589+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>
"赵昭", "裴令容", "阿禾"是试验园区的要跟武陵城区分开，因为完整循环测试只支持一个小区域的测试，比如武陵城或者试验园区其他逻辑则无所谓，正常能跑
</problem_statement>

First, determine whether the <problem_statement> requires code changes, an explanation, a plan, or analysis. Then follow the appropriate path:

If the task requires code changes:

If the task is a question or only requires creating a plan or analysis: respond directly without making code changes.

<system_reminder>You have the capability to call multiple tools in a single response.
For maximum efficiency, whenever you need to perform multiple independent operations, ALWAYS call tools simultaneously whenever the actions can be done in parallel rather than sequentially (e.g. multiple reads/edits to different files). Especially when exploring repository, searching, reading files, viewing directories, validating changes. For example, you can read 3 different files in parallel, or edit different files in parallel. However, if some tool

```
  calls depend on previous calls to inform dependent values like the
  parameters, do NOT call these tools in parallel and instead call
  them sequentially (e.g. reading shell output from a previous command
  should be sequential as it requires the sessionID).</
  system_reminder>
```

<prev_assistant>

已按你的新要求处理：**把“赵昭/裴令容/阿禾”从武陵城拆分到试验园区，并让“完整循环测试”只跑一个小区域（武陵城或试验园区）**。

已完成改动
1. **数据化拆分小区域目标**
   - 文件：`/home/runner/work/ok-end-field/ok-end-field/src/data/delivery_area.py`
   - 新增：
     - `delivery_targets_by_location`
       - 武陵城：`常沄/资源/彦宁/齐纶`
       - 试验园区：`赵昭/裴令容/阿禾`
     - `get_full_cycle_targets(area_name, location_name)`

2. **完整循环测试增加“小区域”配置**
   - 文件：`/home/runner/work/ok-end-field/ok-end-field/src/tasks/DeliveryTask.py`
   - 新增配置项：`完整循环测试区域`
   - 仅在 `完整循环测试` 分支生效，按所选小区域读取并遍历目标；普通流程不受影响。

3. **可维护性增强**
   - `delivery_area.py` 新增统一区域校验 `_get_area_config`，非法区域会给出明确错误信息。

校验结果
- `python -m unittest discover -s tests -p 'Test*.py'`：失败（环境缺依赖：`numpy/cv2/qfluentwidgets/ok`，与基线一致）
- `python -m unittest tests/TestSequenceParser.py`：通过
- `parallel_validation`：CodeQL 0 告警；Code Review 仅剩非阻断建议（命名与健壮性优化类）

如果你要，我可以下一步把“完整循环测试区域”默认值改成你常用的那个（比如默认试验园区）。

<current>

<request>

You are working on a task in the 'AliceJump/ok-end-field' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/ok-end-field/ok-end-field (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-05-14T21:25:37.128+00:00</current_datetime>

Consider the following problem statement:

<problem_statement>
DELIVERY_AREA_CONFIG = {
    "武陵": {
        "delivery_locations": ["武陵城", "试验园区"],
        "delivery_targets": ["常沄", "资源", "彦宁", "齐纶", "赵昭", "裴令容", "阿禾"],
        "delivery_targets_by_location": {
            "武陵城": ["常沄", "资源", "彦宁", "齐纶"],
            "试验园区": ["赵昭", "裴令容", "阿禾"],
        },
        "transfer_search_area": {
            "武陵城": "top",
            "试验园区": "right",
        },
        "ocr_priority_locations": ["试验园区", "武陵城"],
def get_ocr_priority_locations(area_name: str) -> list[str]:
    return DELIVERY_AREA_CONFIG[area_name]["ocr_priority_locations"]
def get_full_cycle_targets(area_name: str, location_name: str) -> list[str]:
    return DELIVERY_AREA_CONFIG[area_name]["delivery_targets_by_location"].get(location_name, [])
def extract_delivery_location(text: str, area_name: str) -> str | None:这里信息有点重复了数据应该只维护一套
</problem_statement>

First, determine whether the <problem_statement> requires code

changes, an explanation, a plan, or analysis. Then follow the appropriate path:

If the task requires code changes:

If the task is a question or only requires creating a plan or analysis: respond directly without making code changes.

<system_reminder>You have the capability to call multiple tools in a single response.
For maximum efficiency, whenever you need to perform multiple independent operations, ALWAYS call tools simultaneously whenever the actions can be done in parallel rather than sequentially (e.g. multiple reads/edits to different files). Especially when exploring repository, searching, reading files, viewing directories, validating changes. For example, you can read 3 different files in parallel, or edit different files in parallel. However, if some tool calls depend on previous calls to inform dependent values like the parameters, do NOT call these tools in parallel and instead call them sequentially (e.g. reading shell output from a previous command should be sequential as it requires the sessionID).</system_reminder>

<prompt>

```
DELIVERY_AREA_CONFIG = {
    "武陵": {
        "delivery_locations": ["武陵城", "试验园区"],
        "delivery_targets": ["常沄", "资源", "彦宁", "齐纶", "赵昭",
"裴令容", "阿禾"],
        "delivery_targets_by_location": {
            "武陵城": ["常沄", "资源", "彦宁", "齐纶"],
            "试验园区": ["赵昭", "裴令容", "阿禾"],
        },
        "transfer_search_area": {
            "武陵城": "top",
            "试验园区": "right",
        },
        "ocr_priority_locations": ["试验园区", "武陵城"],
def get_ocr_priority_locations(area_name: str) -> list[str]:
    return DELIVERY_AREA_CONFIG[area_name]["ocr_priority_locations"]
def get_full_cycle_targets(area_name: str, location_name: str) ->
list[str]:
    return DELIVERY_AREA_CONFIG[area_name]
["delivery_targets_by_location"].get(location_name, [])
```

```
def extract_delivery_location(text: str, area_name: str) -> str |
None:这里信息有点重复了数据应该只维护一套
```