f17a62c1-5538-4611-b4c2-bb9309884d6d

<prev_user>

<request>

You are working on an issue in the 'dimagi/open-chat-studio' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/open-chat-studio/open-chat-studio (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-01-20T08:52:10.381Z</current_datetime>

Consider the following problem statement:

<problem_statement>
Context: Sometimes the target server for custom actions are down, and this only surfaces when one looks at the failing trace when a participant interacts with the bot. We want to add a status indicator to each custom action that shows the status of the server. Green means it is up and red means down. This will serve as a quick debug step for users. We can use daisyUI's status component/style. When configuring a custom action, we need to allow users to configure the health endpoint that we'll use to check the status. In a periodic task (see settings.py on how to do this), we just need to check all custom actions' health endpoints and update the status of the server. Interval should be 30 seconds. Users must be able to click a button to check immediately also. Please go ahead and implement this
</problem_statement>

Implement the necessary changes to the repository so that the requirements specified in the <problem_statement> are met.

A **CI/Build Failure** has been mentioned in the problem statement, make sure to follow your instructions for addressing CI/Build Failures.

<prev_assistant>

Perfect! Now let me create a comprehensive final summary document:

Summary

I have successfully implemented the health status indicator feature for custom actions in the Open Chat Studio repository. Here's what was accomplished:

✅ Implementation Complete

1. Database Schema Updates
- Added 3 new fields to the `CustomAction` model:
  - `health_endpoint` (URLField, optional): Stores the health check endpoint URL
  - `health_status` (CharField): Tracks status with choices: 'unknown', 'up', 'down'
  - `last_health_check` (DateTimeField): Records when the last check occurred
- Created play (NEW)
12. `templates/custom_actions/health_check_loading.html` - Loading state (NEW)

How It Works

1. **Automatic Monitoring**: Every 30 seconds, the Celery beat scheduler triggers `check_all_custom_actions_health()` which queues individual health checks for all custom actions that have a health endpoint configured.

2. **Health Check Logic**: Each check makes an HTTP GET request to the configured endpoint with a 5-second timeout. If the response status code is in the 2xx range, the status is set to "up". Any other response or error sets it to "down".

3. **Visual Feedback**: The status is displayed in the Custom Actions table with color-coded DaisyUI badges. Users can click the refresh button next to any status to trigger an immediate check.

4. **User Experience**: When a user clicks "Check Now", the button shows

a loading spinner while the health check task runs. The page updates seamlessly via HTMX without requiring a full page reload.

Next Steps for Users

To use this feature, users should:
1. Run migrations: `python manage.py migrate`
2. Start Celery worker with beat: `celery -A config worker --beat`
3. When creating/editing a custom action, optionally provide a health check endpoint
4. View the status in the Custom Actions table
5. Click the refresh icon to check immediately if needed

The feature is fully implemented, tested, and ready for production use!

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'dimagi/open-chat-studio' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/open-chat-studio/open-chat-studio (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-01-20T09:37:25.694Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
Add health status monitoring to custom actions
</pr_title>

<pr_description>
Technical Description

Custom action servers sometimes go down, but failures only surface when users review execution traces. This PR adds automatic health monitoring with visual status indicators.

Implementation:

- **Database**: Three fields on `CustomAction`: `health_endpoint` (optional URL), `health_status` (enum: unknown/up/down), `last_health_check` (timestamp)

- **Automated checks**: Celery task runs every 30 seconds, makes GET requests with 5s timeout to configured health endpoints. 2xx responses = up, everything else = down.

- **UI**: Status column in table with DaisyUI badges (green/red/gray). HTMX-powered "Check Now" button for immediate checks. Shows loading spinner during requests.

- **Security**: Team-scoped with permission checks, uses existing URL validation patterns.

Example usage:
```python
action = CustomAction.objects.create(
    name="Payment API",
    server_url="https://api.payment.com",
    health_endpoint="https://api.payment.com/health",  # Optional
    ...
)
# Status automatically updated every 30s
# Users see green/red badge in table
```

Migrations
- [x] The migrations are backwards compatible

Migration adds nullable fields with defaults (`health_status='unknown'`), safe to apply before code deployment.

Demo

Setup:
1. Create/edit custom action, optionally set "Health Check Endpoint" field

```
2. View status in Custom Actions table
3. Click refresh icon for immediate check

**Status indicators:**
- Green "Up" badge: server responding (2xx)
- Red "Down" badge: server error or unreachable
- Gray "Unknown" badge: no check performed yet
- `-` dash: no health endpoint configured

![Status column shows colored badges with refresh button next to
each]

### Docs and Changelog
- [x] This PR requires docs/changelog update

New optional field `health_endpoint` on Custom Action model.
Periodic task `check_all_custom_actions_health` runs every 30
seconds. New permission check on `custom_actions:check_health`
endpoint for manual triggers.

&gt; [!WARNING]
&gt;
&gt;









</pr_description>

## Comments on the PR (you are @copilot in this section)

<comments>

<pr_reviews>

<comment_thread>
<file>apps/custom_actions/forms.py:45</file>
<original_commit>d2ff4e2</original_commit>

  <comment_new>
  <comment_id>2707532452</comment_id>
  <author>@SmittieC</author>
```

@copilot can the health endpoint not come from the API spec?
</comment_new>

</comment_thread>

</pr_reviews>

</comments>

The last **5** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement>

Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.
    - Is it addressed to you or someone else, e.g. "Hey @username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>

A **CI/Build Failure** has been mentioned in the problem statement, make sure to follow your instructions for addressing CI/Build Failures.