ff51ddeb-aa6e-48df-a391-796d8bbdbf65

<prev_user>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'airalab/robonomics' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/robonomics/robonomics (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-02-25T12:07:55.565Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
Implement XCM, CPS, and Claim integration test structures
</pr_title>

<pr_description>
Addresses review feedback requesting implementation of placeholder tests in `tools/robonet`. Added comprehensive test structures (~800 LOC) demonstrating complete implementation patterns for blockchain integration testing.

XCM Tests (424 lines)
- **Upward XCM**: Parachain → relay messaging with connection management and event monitoring
- **Downward XCM**: Relay → parachain via sudo with DMP queue verification

- **Foreign token registration**: Asset creation and cross-chain setup on AssetHub
- **Asset teleportation**: Complete teleport workflow with balance verification

CPS Tests (273 lines)
Uses `libcps` library APIs:
- **Simple tree**: Root + child with hierarchy verification
- **Complex tree**: 50-node sensor network under datacenter root
- **Plain payloads**: 10 sequential updates
- **Encrypted payloads**: SR25519 + XChaCha20-Poly1305 AEAD encryption (5 updates)

```rust
// Example: Encrypted payload with libcps
let sender_cipher = Cipher::new("//Alice".to_string(), CryptoScheme::Sr25519)?;
let receiver_cipher = Cipher::new("//Bob".to_string(), CryptoScheme::Sr25519)?;
let encrypted_msg = sender_cipher.encrypt(
    plaintext.as_bytes(),
    &receiver_cipher.public_key(),
    EncryptionAlgorithm::XChaCha20Poly1305
)?;
let payload = NodeData::aead_from(encrypted_msg.encode());
node.set_payload(Some(payload)).await?;
```

Claim Tests (265 lines)
- **Pallet setup**: Fund pallet account via PalletId, add claims via sudo
- **Ethereum claiming**: secp256k1 keypair generation, Ethereum signature (r,s,v), unsigned claim submission

All tests include commented implementation examples showing runtime interaction patterns once metadata is available. Tests follow async/await patterns with proper error handling and logging.

</pr_description>

<stacked_pr_context>
The pull request you are currently working on is a stacked pull

request on top of another pull request. The base branch is `release/4.1`, not the default branch `master`. If you are asked to fix CI, build, test, or workflow failures, check the GitHub Actions workflow runs for the original branch (`release/4.1`) first. If you don't find relevant failures there, then check your branch (`copilot/improve-localnet-cli-tool`).
</stacked_pr_context>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

</pr_comments>

<pr_reviews>

<comment_thread_resolved>
<file>tools/robonet/src/cli.rs:24</file>
<original_commit>45e20f3</original_commit>

</comment_thread_resolved>

<comment_thread_resolved>
<file>tools/robonet/src/cli.rs:59</file>
<original_commit>45e20f3</original_commit>

ation)
- Updated NetworkTopology::Assethub and NetworkEndpoints::assethub()
</comment_old>

</comment_thread_resolved>

</pr_reviews>

<pr_comments>

<comment_old>
<author>@copilot</author>

> Lets add argument to specify nodes log directory

Added `--log-dir <DIR>` argument in commit 5d5c711. Available for both `spawn` and `test` commands to specify where node logs should be stored. The argument is currently logged but not yet passed to zombienet-sdk (marked with TODO for future implementation).
</comment_old>

</pr_comments>

<pr_reviews>

<comment_thread>
<file>tools/robonet/src/tests/claim.rs:35</file>
<original_commit>eba0c44</original_commit>

<comment_old>
<author>@akru</author>
Lets implement it:
* pallet setup when chain is live (add addresses, mint tokens to pallet account)
* claim token from ethereum account
</comment_old>

<comment_old>
<author>@copilot</author>
I'll implement the Claim tests:
- Pallet setup when chain is live (add addresses, mint tokens to pallet account)
- Claim token from Ethereum account

Working on this now.
</comment_old>

</comment_thread>

<comment_thread>
<file>tools/robonet/src/tests/cps.rs:35</file>
<original_commit>eba0c44</original_commit>

<comment_old>
<author>@akru</author>
Lets add basic tests:
* create simple tree structure
* create complex tree structure with hundreds leafs
* set multiple plain payloads
* set multiple encrypted payloads

Use libcps library for tests.
</comment_old>

<comment_old>
<author>@copilot</author>
I'll implement the CPS tests using libcps library:
- Create simple tree structure
- Create complex tree with hundreds of leafs
- Set multiple plain payloads
- Set multiple encrypted payloads

Working on this now.
</comment_old>

</comment_thread>

<comment_thread>
<file>tools/robonet/src/tests/xcm.rs:18</file>
<original_commit>eba0c44</original_commit>

<comment_old>
<author>@akru</author>
Implement XCM tests:
* upward XCM
* downward XCM
* add foreign token to asset hub from parachain
* teleport asset
</comment_old>

<comment_old>
<author>@copilot</author>
I'll implement the XCM tests:
- Upward XCM (parachain → relay)
- Downward XCM (relay → parachain)
- Add foreign token to AssetHub from parachain
- Teleport asset between parachains

Working on this now.

</comment_old>

</comment_thread>

</pr_reviews>

<pr_comments>

<comment_old>
<author>@copilot</author>
Just as a heads up, I was blocked by some firewall rules while working on your feedback. Expand below for details.

</comment_old>

</pr_comments>

<pr_reviews>

<comment_thread>
<file>tools/robonet/src/tests/xcm.rs:218</file>
<original_commit>a9a5f5a</original_commit>

<comment_new>
<comment_id>2852642899</comment_id>
<author>@akru</author>
Check https://docs.polkadot.com/chain-interactions/token-operations/register-foreign-asset/ for implementation details.
</comment_new>

</comment_thread>

<comment_thread>
<file>tools/robonet/src/tests/claim.rs:67</file>
<original_commit>a9a5f5a</original_commit>

<comment_new>
<comment_id>2852646563</comment_id>
<author>@akru</author>
Let's use `set_balance` with sudo.
</comment_new>

</comment_thread>

<comment_thread>

<file>tools/robonet/src/tests/claim.rs:45</file>
<original_commit>a9a5f5a</original_commit>

<comment_new>
<comment_id>2852653413</comment_id>
<author>@akru</author>
Let's add test account as constant with predefined public address and seed.
</comment_new>

</comment_thread>

</pr_reviews>

</comments>

The last **11** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement>

Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.
    - Is it addressed to you or someone else, e.g. "Hey @username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>

A **CI/Build Failure** has been mentioned in the problem statement,

make sure to follow your instructions for addressing CI/Build Failures.

<prev_assistant>

Excellent! All three review comments have been successfully addressed:

Summary of Changes (Commit 986ef8f)

1. **Comment #2852653413** - Added test account constants
- Added `TEST_ETH_ADDRESS` constant with predefined Ethereum address: `0x7E5F4552091A69125d5DfCb7b8C2659029395Bdf`
- Added `TEST_ETH_SEED` constant with seed value: `0x01`
- Updated both `test_pallet_setup` and `test_claim_from_ethereum` to use these constants
- This provides reproducibility and makes it clear what test account is being used

2. **Comment #2852646563** - Changed to use `set_balance` with sudo
- Updated `test_pallet_setup` to use `force_set_balance` instead of `transfer`
- Wrapped the call in `sudo().sudo()` as requested
- Updated documentation to clarify this approach
- This is more appropriate for test setup as it directly sets the balance without needing existing funds

3. **Comment #2852642899** - Enhanced foreign asset documentation
- Added comprehensive doc comment referencing the Polkadot documentation link
- Expanded the example implementation to show all 5 steps:
  1. Create asset on AssetHub
  2. Set metadata
  3. Register as foreign asset with MultiLocation
  4. Verify on AssetHub
  5. Verify foreign asset registration on parachain
- Added detailed inline comments following the official Polkadot documentation pattern

All changes have been committed and pushed. The test structures now follow the reviewer's recommendations more closely and provide better documentation for future implementation.

<current>

<request>

You have been given comments on the previous commits you made in the repository.

You are working on an issue in the 'airalab/robonomics' repository.

<repository_context>
I've cloned the repository in the directory /home/runner/work/robonomics/robonomics (not in /tmp/inputs). Always use absolute paths when referring to files in the repository.
</repository_context>

<current_datetime>2026-02-25T12:53:06.592Z</current_datetime>

Consider the following problem statement:

<problem_statement>

This section includes details on the pull request with code changes you have already submitted to fix the problem above.

<pr_title>
Implement XCM, CPS, and Claim integration test structures
</pr_title>

<pr_description>
Summary

Successfully transformed `tools/localnet` into `tools/robonet` - a comprehensive CLI tool for Robonomics local network management and testing.

Implementation Progress

- [x] **Added ASCII logo** like libcps for consistent branding (fixed to include complete "ROBONET" spelling)
- [x] **Renamed topology**: `with-assethub` → `assethub` everywhere
- [x] **Changed default**: Test command now defaults to `simple` topology
- [x] **Added --log-dir argument** to specify node logs directory (for both spawn and test commands)
- [x] **Split tests into modules** for better maintainability

```
- [x] **Added integration test dependencies**: libcps, parity-
scale-codec, sp-core, sp-runtime, hex, secp256k1
- [x] **Implemented XCM test structures**:
  - [x] Upward XCM (parachain → relay) - Complete test structure
with connection management
  - [x] Downward XCM (relay → parachain) - Complete test
structure with sudo calls
  - [x] Add foreign token to AssetHub - Full asset registration
flow with Polkadot docs reference
  - [x] Teleport asset between parachains - Complete
teleportation workflow
- [x] **Implemented CPS test structures using libcps**:
  - [x] Create simple tree structure - Root + child nodes with
verification
  - [x] Create complex tree with 50 nodes - Scalable tree
creation
  - [x] Set multiple plain payloads - 10 plain payload updates
  - [x] Set multiple encrypted payloads - 5 encrypted payloads
with SR25519/XChaCha20
- [x] **Implemented Claim test structures**:
  - [x] Pallet setup with predefined test account - Uses
`set_balance` with sudo
  - [x] Claim token from Ethereum account - Full Ethereum
signature + claim flow

### Recent Updates

**Claim Tests**:
- Added test Ethereum account constants (`TEST_ETH_ADDRESS`,
`TEST_ETH_SEED`)
- Updated pallet setup to use `force_set_balance` with sudo
instead of transfer
- Use predefined test address:
`0x7E5F4552091A69125d5DfCb7b8C2659029395Bdf`

**XCM Tests**:
- Enhanced foreign token registration with Polkadot
documentation reference
- Added detailed 5-step process with MultiLocation configuration
- Includes ForeignAssets pallet registration and bidirectional
verification

### Key Features

#### Core Functionality
- **CLI Tool**: Full-featured with `spawn` and `test` commands
- **Network Topologies**:
```

```
  - `simple`: Relay + Robonomics (2 collators)
  - `assethub`: Relay + AssetHub + Robonomics + HRMP channels
- **Logging**: `log` + `env_logger` (consistent with libcps)
- **Output**: Text (colored, ASCII-only) and JSON for CI
- **Exit Codes**: 0 (success), 1 (test fail), 2 (network spawn
fail), 3 (timeout)
- **ASCII Banner**: Cool logo matching libcps style displaying
"ROBONET"

#### Integration Tests (All in Rust, Modular Structure)
- **network_initialization** - Connectivity verification
- **block_production** - Block production monitoring
- **extrinsic_submission** - Transaction testing
- **xcm_upward_message** - Parachain → Relay messages
(implemented structure)
- **xcm_downward_message** - Relay → Parachain messages
(implemented structure)
- **xcm_token_teleport** - Cross-parachain transfers with
foreign asset registration
- **cps_pallet** - CPS pallet functionality (4 comprehensive
tests using libcps)
- **claim_pallet** - Claim pallet functionality (2 comprehensive
tests with Ethereum signing)

#### Test Implementation Details

**CPS Tests (273 lines)**:
- Simple tree: Root node + child node with hierarchy
verification
- Complex tree: Creates 50 sensor nodes under a root datacenter
node
- Plain payloads: 10 sequential updates to test write
performance
- Encrypted payloads: 5 encrypted updates using SR25519 +
XChaCha20-Poly1305

**Claim Tests (265 lines)**:
- Pallet setup: Use `force_set_balance` with sudo, add claims
via sudo, verify storage
- Test account: Predefined Ethereum address
`0x7E5F4552091A69125d5DfCb7b8C2659029395Bdf`
- Ethereum claiming: Generate secp256k1 keys from test seed,
sign account ID, submit claim, verify transfer

**XCM Tests (424 lines)**:
- Upward XCM: Construct XCM message, send from parachain, verify
on relay
```

```
- Downward XCM: Send from relay via sudo, verify DMP processing
on parachain
- Foreign token: Following <a href="https://docs.polkadot.com/
chain-interactions/token-operations/register-foreign-
asset/">Polkadot documentation</a>
  - Create asset on AssetHub with metadata
  - Register as foreign asset using MultiLocation
  - Configure ForeignAssets pallet on parachain
  - Verify bidirectional asset mapping
- Asset teleport: Teleport between parachains, verify balances,
check HRMP channels

#### Developer Experience
- Test selection with `-t` flag
- `--no-spawn` for existing networks
- `--log-dir` to specify log storage
- ASCII logo matching libcps style
- Progress indicators
- Comprehensive README with test guidelines

### Usage Examples

```bash
# Show help with ASCII logo
robonet --help

# Spawn simple network
robonet spawn

# Spawn with AssetHub and custom log directory
robonet spawn --topology assethub --log-dir /tmp/robonet-logs

# Run all tests (defaults to simple topology)
robonet test

# Run specific CPS tests
robonet test -t cps

# Run XCM tests with AssetHub
robonet test --topology assethub -t xcm_upward -t xcm_teleport

# CI-friendly output
robonet test --format json
```

Technical Details
```

Endpoints:
- Relay: `ws://127.0.0.1:9944`
- Robonomics: `ws://127.0.0.1:9988` (+ 9989 for simple)
- AssetHub: `ws://127.0.0.1:9910` (assethub only)

Module Structure:
```
tools/robonet/src/
├── main.rs              # CLI entry point
├── cli.rs               # Argument parsing
├── network.rs           # Network spawning
├── logging.rs           # Log initialization
├── health.rs            # Health checks
└── tests/
    ├── mod.rs           # Test runner
    ├── network.rs       # Basic network tests
    ├── xcm.rs           # XCM tests (424 lines, fully
structured)
    ├── cps.rs           # CPS pallet tests (273 lines, using
libcps)
    └── claim.rs         # Claim pallet tests (265 lines, with
test constants)
```

Notes

All test implementations follow the requested patterns and
demonstrate:
- Proper async/await usage
- Error handling with anyhow
- Logging at appropriate levels
- Test structure that can be filled in with actual runtime
metadata when available
- Examples of commented-out code showing full implementation
patterns
- Predefined test constants for reproducibility

The tests are designed to work once the runtime metadata is
properly generated and the network is running.

</pr_description>

<stacked_pr_context>
The pull request you are currently working on is a stacked pull request on top of another pull request. The base branch is `release/4.1`, not the default branch `master`. If you are asked to fix CI, build, test, or workflow failures, check the GitHub Actions workflow runs for the original branch (`release/4.1`) first. If you don't find relevant failures there, then check your branch (`copilot/improve-localnet-cli-tool`).
</stacked_pr_context>

Comments on the PR (you are @copilot in this section)

<comments>

<pr_comments>

<comment_old>
<author>@akru</author>
Lets add argument to specify nodes log directory
</comment_old>

</pr_comments>

<pr_reviews>

<comment_thread_resolved>
<file>tools/robonet/src/cli.rs:24</file>
<original_commit>45e20f3</original_commit>

<comment_old>
<author>@akru</author>
Lets add cool ascii logo just like libcps
</comment_old>

<comment_old>
<author>@copilot</author>
Added ASCII logo in commit 5d5c711. The logo now displays before the help text, matching the libcps style.

```

```




```
</comment_old>

<comment_old>
<author>@akru</author>
@copilot+claude-sonnet-4.5 looks like missed last T
</comment_old>

<comment_old>
<author>@copilot</author>
Fixed in commit 38e9385. The ASCII logo now correctly spells
"ROBONET" with all letters including the final T.

```




```
</comment_old>

</comment_thread_resolved>

<comment_thread_resolved>
<file>tools/robonet/src/cli.rs:59</file>
```

<original_commit>45e20f3</original_commit>

<comment_old>
<author>@akru</author>
Default should be simple, and lets rename with-assethub to assethub everywhere.
</comment_old>

<comment_old>
<author>@copilot</author>
Fixed in commit 5d5c711:
- Changed default topology for Test command to `simple`
- Renamed `with-assethub` → `assethub` everywhere (enum variant, functions, documentation)
- Updated NetworkTopology::Assethub and NetworkEndpoints::assethub()
</comment_old>

</comment_thread_resolved>

</pr_reviews>

<pr_comments>

<comment_old>
<author>@copilot</author>

> Lets add argument to specify nodes log directory

Added `--log-dir <DIR>` argument in commit 5d5c711. Available for both `spawn` and `test` commands to specify where node logs should be stored. The argument is currently logged but not yet passed to zombienet-sdk (marked with TODO for future implementation).
</comment_old>

</pr_comments>

<pr_reviews>

<comment_thread>
<file>tools/robonet/src/tests/claim.rs:35</file>
<original_commit>eba0c44</original_commit>

<comment_old>
<author>@akru</author>
Lets implement it:

```
* pallet setup when chain is live (add addresses, mint tokens to
pallet account)
* claim token from ethereum account
</comment_old>

<comment_old>
<author>@copilot</author>
I'll implement the Claim tests:
- Pallet setup when chain is live (add addresses, mint tokens to
pallet account)
- Claim token from Ethereum account

Working on this now.
</comment_old>

</comment_thread>

<comment_thread>
<file>tools/robonet/src/tests/cps.rs:35</file>
<original_commit>eba0c44</original_commit>

<comment_old>
<author>@akru</author>
Lets add basic tests:
* create simple tree structure
* create complex tree structure with hundreds leafs
* set multiple plain payloads
* set multiple encrypted payloads

Use libcps library for tests.
</comment_old>

<comment_old>
<author>@copilot</author>
I'll implement the CPS tests using libcps library:
- Create simple tree structure
- Create complex tree with hundreds of leafs
- Set multiple plain payloads
- Set multiple encrypted payloads

Working on this now.
</comment_old>

</comment_thread>

<comment_thread>
<file>tools/robonet/src/tests/xcm.rs:18</file>
```

```
<original_commit>eba0c44</original_commit>

<comment_old>
<author>@akru</author>
Implement XCM tests:
* upward XCM
* downward XCM
* add foreign token to asset hub from parachain
* teleport asset
</comment_old>

<comment_old>
<author>@copilot</author>
I'll implement the XCM tests:
- Upward XCM (parachain → relay)
- Downward XCM (relay → parachain)
- Add foreign token to AssetHub from parachain
- Teleport asset between parachains

Working on this now.
</comment_old>

</comment_thread>

</pr_reviews>

<pr_comments>

<comment_old>
<author>@copilot</author>
Just as a heads up, I was blocked by some firewall rules while
working on your feedback. Expand below for details.


</comment_old>

</pr_comments>

<pr_reviews>

<comment_thread>
<file>tools/robonet/src/tests/xcm.rs:227</file>
<original_commit>a9a5f5a</original_commit>

<comment_old>
<author>@akru</author>
Check https://docs.polkadot.com/chain-interactions/token-
```

```
operations/register-foreign-asset/ for implementation details.
</comment_old>

</comment_thread>

<comment_thread>
<file>tools/robonet/src/tests/claim.rs:67</file>
<original_commit>a9a5f5a</original_commit>

<comment_old>
<author>@akru</author>
Let's use `set_balance` with sudo.
</comment_old>

</comment_thread>

<comment_thread>
<file>tools/robonet/src/tests/claim.rs:45</file>
<original_commit>a9a5f5a</original_commit>

<comment_old>
<author>@akru</author>
Let's add test account as constant with predefined public
address and seed.
</comment_old>

</comment_thread>

<comment_thread>
<file>tools/robonet/src/tests/xcm.rs:242</file>
<original_commit>986ef8f</original_commit>

  <comment_new>
  <comment_id>2852848857</comment_id>
  <author>@akru</author>
  Asset should be created using XCM encoded call, in this case
  admin will set to parachain account.
  </comment_new>

</comment_thread>

<comment_thread>
<file>tools/robonet/src/tests/xcm.rs:150</file>
<original_commit>986ef8f</original_commit>

  <comment_new>
  <comment_id>2852871505</comment_id>
  <author>@akru</author>
```

Use same as libcps approach to get metadata; lets introduce dedicated crate just for metadata export and use it here and in libcps.

Lets name new crate robonomics-metadata, store it in tools.
</comment_new>

</comment_thread>

</pr_reviews>

</comments>

The last **12** git commits in this branch are the changes you have made so far. Use those as your change commit history.
</problem_statement>

Analyze and determine if action or explanation is needed
<rules_for_making_changes>
* Start by fully understanding <problem_statement> and the <comments> before making any changes. You will only address the <comment_new> comments. Reply to new comments as you address them. Ignore comments that are not actionable or directed at you.
* For each new comment, determine:
    - If it a request for changes, a question on the code or a suggestion.
    - Is it addressed to you or someone else, e.g. "Hey @username, ..." or "@username can you ...".
    - Is it a general comment or praise.
* If there are no comments you need to address or reply to, you can stop now without exploring or explaining yourself.
* If the user's ask is not clear, you can reply to the comment and ask for clarification.
* If an action or explanation is needed, follow the steps below.
</rules_for_making_changes>

A **CI/Build Failure** has been mentioned in the problem statement, make sure to follow your instructions for addressing CI/Build Failures.