

FEBUREDIHLOOODRUREXALIVE EE1170 2353800

EXISTING PROTECTIVE TILES ARE TO BE LIFTED AND SET ASIDE FOR THE EXISTING WATERPROOFING TO BE MAINTAINED

PREVIOUSLY SERVICED WATERPROOFING TO BE INSPECTED ON PERIMETER AND AT FULBORE OUTLETS AND PROTECTIVE TILES CHECKED

WATERPROOFING AND SCREED TO BE STRIPPED. NEW SCREED TO FALLS TO EXISTING FULBORE AND DERBIGUM SINGLE LAYER SP4 WATERPROOFING WITH 75MM SIDE LAPS AND 100 END LAPS AND FINISHED WITH TWO COATS OF BITUMINIZED ALUMINUM PAINT

PREVIOUSLY SERVICED WATERPROOFING TO BE INSPECTED ON PERIMETER AND AT FULBORE OUTLETS

EXISTING WATERPROOFING TO BE MAINTAINED BY CAREFUL INSPECTION. ALL EDGES AND EXPANSION JOINTS ARE TO BE CAREFULLY CHECKED. TO BE GIVEN TWO COATS BITUMENIZED ALUMINUM PAINT ON COMPLETION

WATERPROOFING TO BE STRIPPED. NEW SINGLE LAYER DERBIGUM SP4

WATERPROOFING WITH 75MM SIDE LAPS AND 100 END LAPS AND FINISHED WITH TWO COATS OF LIGHT COLOURED ACRYLIC PAINT IN

ACCORDANCE TO DERBIGUM SPECIFICATIONS

