MARA ARPA	ei nam	CYIDTIMC	DADO	WALLS		CORNICE	CELING	SUNDRIES		MOTES	
NOOM/AREA	FLOOR	SKIRTING					Off-shutter concrete				
AGE	Surface slab to be power- floated to uniform non-slip finish.	1 Pranorray Arrestantes	NIL	remain generally untreated. Remaining walls in fair	Cills to South, Southeast and Southwest openings formed by the precast screen units.		unpainted.				
	Car ramps to have granolithic screed with reeded finish. Concrete kerbs around external perimeter to detail.			Concrete retaining wall North and Northwest to garage painted black							
	external berrherer on decer			bitumastic paint to 500 mm above floor level. Parapet guard walls at changes of level and ramps							
				of 220 mm stock brick bagged both sides.					· · · · · · · · · · · · · · · · · · ·		
ISTRY STORE	Untinted granolithic.	75 mm granolithic skirting		Fair face stock brick walls to be cleaned and painted	NIL	NIL	Off-shutter concrete painted P.V.A.				
		formed with 10 mm radius cove.		P.V.A. full height. Concrete columns and retaining walls to be							
				painted P.V.A. full height.							
LEPHONE JUNCTION ROOM	Untinted granolithic	Ditto	NII	North and South brick walls rendered and set and painted P.V.A. full height.			Ditto				*
· · · · · · · · · · · · · · · · · · ·				Off-shutter East and West walls painted full height with P.V.A.							·
				Off-shutter concrete walls		NII	All soffits off-shutter	For handrails to stairs see details on drawing 02	2.70.		
HER BLOCK STAIRS	Landings: Screed with asphalt tiles. Treads: Ditto	Black tinted granolithic skirting to walls, 75 mm above line of nosing. On stair well side, the		to have applied texture paint finish to later specification.			painted P.V.A. to line of walls on one side and to line of downward black				
	Nosing: Bildon Around stair well on Landings, treads and risers.	black tinted granolithic margin strip to return downwards over stringer					skirting on well side.				
·	a black tinted granolithic screed strip margin, 100 mm wide. to be formed to a	and landing concrete edges and to project 5 mm below the soffits.									
	height 12 mm above normal screed level.										
TWEST STAIRS	Ditto	Ditto		Exposed off-shutter to have face brick infills full		NIL	Ditto	For handrails to stairs see details on drawing 02	2.70.	*** ** ** ** ** ** ** ** ** ** ** ** **	-
				height. Inner face of South wall in face brick.							
THACT COLLDS	Ditto	Ditto		Exposed off-shutter to have face brick infills full		NII	Ditto	For handrails to stairs see details on drawing Oź	2.70.		
HEAST STAIRS				height. Inner face of South wall in							
ъ.	The manufacture of the second			face brick. Enclosure to lifts to have stock brick infills, untreated, between exposed				74 THE TOTAL OF TH			
*	THE PROPERTY OF THE PROPERTY O			off-shutter columns.							
.U. SECTION	ACCEPTANCE AND ACCEPT										
ollow											
	Contribution of the contri										
											-
-	**************************************										
	BOARSHAD AT STREET AND A STREET										
	The state of the s										
			·								
•											
											· . ·
										TEMEL 7000	
				o. By Date REVISION	;	Univer	sity of the Witu	vatersrand Johannesburg F	UUDINJG UNINGINI	LC LLVLL JUU Scales; Drawing [
									OHN FASSLER ASSOCIATES - ARCHITE		m
									OHANNESBURG. TEL. No. 44-9	WN Drawn; C.K.P. Date; July 1973. Checked;	DZALI