Wirechat Beta

# Events

WireChat uses events to notify users in real-time when key actions occur, such as when a new message is created. These events help update the chat interface and notify participants who might not be actively engaged in the conversation.

## # MessageCreated Event

The **`MessageCreated`** event is triggered when a new message is created. It is broadcast over the private channel **`private-{panel}.conversation.{id}`**, where **`{panel}`** is the panel ID and **`{id}`** is the unique identifier of the conversation. This event ensures that all participants in the conversation receive real-time updates.

The event is only accessible to users who are part of the conversation, and access is validated by checking if the authenticated user belongs to the conversation.

You can listen to this event using Laravel Echo.

Example: Broadcasting the Event

```
$message = $auth->sendMessageTo($otherUser);

broadcast(new MessageCreated($message));
```

Broadcasting to a Panel By default, the default panel will be used to send broadcasts. However, you can also specify a panel to broadcast the message to:

```
$message = $auth->sendMessageTo($otherUser);

broadcast(new MessageCreated(message: $message, panel: 'admin'));
```

---

## # NotifyParticipant Event

Some participants may not be actively viewing a conversation but still need to be notified about new messages. The **`NotifyParticipant`** event is broadcast over the private channel **`private-{panel}.participant.{type}.{id}`** to notify each participant individually.