Wirechat Beta

Introduction

WireChat allows you to define how users are represented within your application. You can configure attributes such as display names, profile avatars, and profile URLs to provide a consistent experience across conversations and components.

Panel access

To decide which users can open a WireChat panel, you may implement your own authorization logic inside the **`User`** model. WireChat will call the **`canAccessWireChatPanel()`** method whenever a panel is being accessed via a route.

```php
namespace App\Models;

use Wirechat\Wirechat\Panel;
use Wirechat\Wirechat\Traits\InteractsWithWireChat;
use Wirechat\Wirechat\Contracts\WireChatUser;
use Illuminate\Foundation\Auth\User as Authenticatable;

class User extends Authenticatable implements WireChatUser
{
    use InteractsWithWireChat;
    // ...

    public function canAccessWireChatPanel(Panel $panel): bool
    {
        return $this->hasVerifiedEmail();
    }
}
```

The **`canAccessWireChatPanel()`** method should return **`true`** or **`false`** depending on whether the user is allowed to enter the given **`$panel`**. In this example, access is restricted to users who have verified their email address.

Because the current **`$panel`** is available, you can apply different rules for each panel. For instance, you may require stricter checks for an admin chat panel, while keeping other panels open to all users:

```php
namespace App\Models;
```