

MOSAIC: Data-Certified Stochastic Release under Structured Deployment Shift

Anonymous submission

Abstract

Concept-erasure evaluations usually assess an edited representation, not the public interface that remains after editing. We introduce MOSAIC, a software-only procedure that releases a task-specific stochastic token channel and decoder only when both source leakage and worst-stratum task error are certified; otherwise it abstains. Its key move is to place one simultaneous confidence event on pre-release token laws, before channel optimization. That event covers every channel searched on the table. Labeled target data then either certify a common-transform-plus-residual shift class or force abstention. We prove finite-sample Bayes-attacker and utility envelopes, global finite-alphabet optimization, and the missing-support boundary. In 1,000 locked safety trials, naive continuum selection releases contract-violating channels on 42.1% of tables; MOSAIC records none. On 100 registered real-data jobs, a direct target-table rule releases 36 interfaces. Under post-hoc bridge-admitted stress laws, 16 of those 36 violate their contract; MOSAIC retains the 20 safe releases and abstains on the other 16. A fresh 60-job geographic confirmation releases 15 interfaces across four target states and two tasks with 0/15 held-out and 0/1,500 operational violations.

1 Introduction

Representation editing is commonly evaluated by fitting a probe to a frozen embedding (Ravfogel et al. 2020, 2022; Belrose et al. 2023; Jourdan et al. 2023; Avitan, Goldberg, and Elazar 2026), although probe design can change the apparent conclusion (Pimentel et al. 2020). This leaves two deployment gaps: a different downstream rule may recover the attribute, and an edit selected on a noisy validation table may fail after population shift. Both matter when the released token is a public interface.

We study a task-specific finite-token interface. A tokenizer fixed without the certification fold maps an internal representation to $C \in [K]$; a source-blind stochastic channel $M \in \text{Stoch}(K, L)$ releases the only public token Z . Within each task label, the contract bounds the balanced accuracy of the Bayes-optimal source attacker rather than a chosen probe. This isolates conditional source signal from la-

bel prevalence. Pre-release shift is a common Markov transform plus bounded source-specific contamination, permitting large source-blind drift while charging the part that can create new source differences.

MOSAIC, Minimax-Optimized Source-Agnostic Invariant Channels, builds an exact attacker envelope from simultaneous multinomial confidence regions. Because the event precedes M , it covers every stochastic channel, including one optimized on the same table. A bridge LP uses labeled target data to learn a common transform and the largest certifiable retained mass; exact transform-and-contamination envelopes then certify source distinguishability and a jointly selected decoder. Finite-alphabet optimization is global, and MOSAIC returns `ABSTAIN` when no feasible release exists.

The central object is the data-certified bridge: a finite-sample test that turns labeled target observations into a population class on which the chosen interface remains valid. The upstream confidence event then covers the whole post-channel family, so privacy and utility can be optimized jointly without testing each channel. This differs from finite-candidate risk control because the event lies before the channel search. Locked experiments compare this transport certificate with direct target-table certification, plug-in and held-out selection, LTT, deterministic release, official erasers, and an exact population oracle.

2 Related Work

Concept-erasure methods remove source-associated directions, covariance, or components (Ravfogel et al. 2020, 2022; Belrose et al. 2023; Jourdan et al. 2023; Avitan, Goldberg, and Elazar 2026), while leakage audits show why a weak probe is not a universal guarantee (Pimentel et al. 2020; Elazar et al. 2021; Chowdhury et al. 2025). FARE certifies every downstream classifier for restricted finite encoders, and Fair Normalizing Flows bounds strong adversaries through tractable densities (Jovanovic et al. 2023; Balunović, Ruoss, and Vechev 2022). Stochastic preprocessing and fair representations motivate randomized release channels (Calmon et al. 2017; Makhdoumi et al. 2014; Agarwal and Deshpande 2024).

LTT, conformal risk control, and Pareto testing certify registered decisions and may abstain (Bates et al. 2021; Angelopoulos et al. 2025, 2024; Laufer-Goldshtein et al. 2023); robust validation addresses declared uncertainty sets (Tib-

This is an anonymized submission for review purposes only. Distribution, citation, or public sharing of this manuscript is strictly prohibited. Copyright and publication details will appear in the final version if accepted.




Figure 1: MOSAIC has three steps: certify the reference and labeled target-bridge evidence, design a source-blind stochastic token interface on that shared event, and gate deployment on bridge membership, source leakage, and task utility. The runtime persists one token only after every check passes; otherwise it abstains.

shirani et al. 2019; Cauchois et al. 2024). MOSAIC differs by certifying the categorical experiment before channel search, covering an uncountable channel family without separate tests. Its source-blind transform is a Blackwell garbling and its residual is a contamination neighborhood (Blackwell 1953; Le Cam 1964; Torgersen 1991; Huber 1964). The bridge makes that shift model testable from target data, whereas unrestricted shift is impossible to certify (Ben-David et al. 2010; Klivans, Stavropoulos, and Vasilyan 2024; Chandrasekaran et al. 2025).

3 Problem Setup

Let $S \in [G]$ denote source, $Y \in [J]$ task label, and $C \in [K]$ the fine token. For a fixed label, write $p_{s,y}(c) = \Pr(C = c \mid S = s, Y = y)$. The source-blind release channel M produces $Z \in [L]$. The balanced accuracy of the strongest downstream source attacker within label y is

$$A_y(P, M) = \frac{1}{G} \sum_{z=1}^L \max_{s \in [G]} (p_{s,y} M)(z), \quad (1)$$

with normalized advantage $\text{Adv}_G(A) = (GA - 1)/(G - 1)$. This is chance-normalized and ranges from zero to one. The registered source contract is $\max_y \text{Adv}_G(A_y) \leq \tau_P$.

Running example. Take two sources, two task labels, three fine tokens, and two released tokens. For label $y = 0$, let $p_{0,0} = (.7, .2, .1)$ and $p_{1,0} = (.4, .5, .1)$, and consider

$$M = \begin{pmatrix} .9 & .1 \\ .5 & .5 \\ .1 & .9 \end{pmatrix}, \quad g(0) = 0, \quad g(1) = 1.$$

The released source laws are $(.74, .26)$ and $(.62, .38)$, so the Bayes source attacker has accuracy .56 and normalized advantage .12 for this label. The worst source-conditional task error is .38. MOSAIC asks whether these two numbers remain below their registered thresholds for every law supported by the reference and bridge confidence regions, not only for these empirical rows.

C	fine token	Z	public token
M	channel	g	task decoder
$p_{s,y}$	reference law	$q_{s,y}$	target law
$t_y, T_y, r_{s,y}$	bridge terms	τ_P, τ_U	contracts

The main contract concerns source inference within a task label. A joint-law extension covers natural-mixture source inference: define $X = (Y, C)$, estimate $P(X \mid S)$ without balancing labels, and lift the channel as $\tilde{M}((y, c), z) = M(c, z)$. The same envelope then certifies inference from Z ; using output (Y, Z) covers an attacker given the true label as well.

For each supported source-label stratum, the certification table supplies an empirical law $\hat{p}_{s,y}$ and radius $\epsilon_{s,y}$. The simultaneous confidence set is $\mathcal{C}_{s,y} = \{p \in \Delta_K : \|p - \hat{p}_{s,y}\|_1 \leq \epsilon_{s,y}\}$. Under conditionally i.i.d. categorical sampling within each registered source-label stratum, the simultaneous event

$$\mathcal{E} = \bigcap_{s,y} \{\|\hat{p}_{s,y} - p_{s,y}\|_1 \leq \epsilon_{s,y}\} \quad (2)$$

has probability at least $1 - \delta$ after a fixed allocation across strata. We use the Weissman multinomial radius (Weissman et al. 2003) in the confirmation, although any valid simultaneous region can replace it. The tokenizer and fine alphabet must be fixed without these observations.

The external law for label y belongs to the structured class

$$q_s = t_y p_s T_y + (1 - t_y) r_s, \quad t_y \geq 1 - \eta_y, \quad (3)$$

where T_y is a source-independent fine-token channel from a registered convex uncertainty set and each residual r_s is arbitrary. Both components pass through the same release channel M . This placement matters: a constant-row software channel cannot leak information that appears before it.

4 Adaptive Within-Label Attacker Certificate

For a bounded vector v , define the exact confidence-set support function

$$\Phi(\hat{p}, \epsilon; v) = \max_{p \in \Delta_K : \|p - \hat{p}\|_1 \leq \epsilon} p^\top v. \quad (4)$$

It is obtained by moving at most $\epsilon/2$ mass from low to high coordinates of v , or from an equivalent linear-program dual. For attacker assignment $a \in [G]^L$, let $v_{M,a,s}(c) = \sum_z M(c, z) \mathbf{1}\{a(z) = s\}$. We then define

$$\bar{A}(\hat{P}, M) = \frac{1}{G} \max_{a \in [G]^L} \sum_s \Phi(\hat{p}_s, \epsilon_s; v_{M,a,s}). \quad (5)$$

Method	Finite Z	Bayes attacker	Same-table M	Target shift	Shift evidence
FARE (Jovanovic et al. 2023)	yes	yes	no	no	no
Randomized fair reps. (Agarwal and Deshpande 2024)	yes	yes	population	no	no
LTT / risk control (Angelopoulos et al. 2025; Bates et al. 2021)	general	candidate	finite family	optional	model-specific
Blackwell / deficiency (Blackwell 1953; Le Cam 1964)	experiment	all decisions	no	population	assumed
Robust validation (Cauchois et al. 2024)	no	no	no	declared ball	estimated
Testable shift (Klivans, Stavropoulos, and Vasilyan 2024)	no	no	hypothesis	yes	tested
MOSAIC	yes	exact	yes	pre-release	finite-sample

Table 1: Component-level scope of the closest frameworks. “Same-table continuum” means that one confidence event remains valid after optimizing an uncountable stochastic-channel family on that table. The MOSAIC row combines upstream same-table coverage, an exact attacker envelope, and target-shift evidence in one release rule.

Theorem 1 (Adaptive exact envelope). *On $\mathcal{E}$, simultaneously for every row-stochastic M , including a channel selected as an arbitrary function of the same table, $A(P, M) \leq \bar{A}(\hat{P}, M)$. For fixed M , the right-hand side is the exact supremum over the product of the stated ℓ_1 confidence sets.*

The proof writes the Bayes attacker as a maximum over deterministic assignments. For a fixed assignment the source confidence sets separate, giving one support function per source; all maxima are finite and commute. The implication is pointwise over the complete stochastic-channel space, which is why adaptive selection needs no channel-count correction. In the running example, the same confidence event covers the displayed M and every alternative three-by-two channel considered by the optimizer.

5 Data-Certified Shift Membership

MOSAIC certifies structured-shift membership from labeled target bridge data. Let a labeled bridge sample from the target population define simultaneous confidence sets $\mathcal{D}_{s,y}$ for its fine-token laws $q_{s,y}$. Write

$$h_{s,y}(w) = \max_{p \in \mathcal{C}_{s,y}} p^\top w, \quad \underline{q}_{s,y}(z) = \min_{q \in \mathcal{D}_{s,y}} q(z). \quad (6)$$

For each label, the bridge program chooses retained mass t and $W = tT$ by solving

$$\begin{aligned} \max_{t, W} \quad & t \\ \text{s.t.} \quad & W \geq 0, \quad W\mathbf{1} = t\mathbf{1}, \quad 0 \leq t \leq 1, \\ & h_{s,y}(W_{:z}) \leq \underline{q}_{s,y}(z) \quad \forall s, z. \end{aligned} \quad (7)$$

The support functions and coordinate lower bounds have exact LP duals, so Eq. (7) is one linear program rather than a transform search.

Running example, continued. For the displayed $y = 0$ reference rows, take bridge rows $\hat{q}_{0,0} = (.37, .25, .38)$ and $\hat{q}_{1,0} = (.45, .45, .10)$ and set the radii to zero only for this calculation. The LP returns $\hat{t}_0 = .795$ and, rounded to three digits,

$$\hat{T}_0 = \begin{pmatrix} .634 & .052 & .314 \\ .109 & .891 & 0 \\ 0 & 1 & 0 \end{pmatrix}.$$

The residuals are $r_{0,0} = (0, 0, 1)$ and $r_{1,0} = (1, 0, 0)$: substituting them into Eq. (3) reconstructs the two bridge rows.

Thus the LP turns the toy’s target table into a retained common component of .795 and a charged source-specific remainder of .205; the release optimizer must pay for that remainder rather than treating it as shared signal.

Theorem 2 (Adaptive finite-sample bridge). *Suppose the reference and bridge confidence sets jointly cover every $p_{s,y}$ and $q_{s,y}$. Any feasible $(\hat{t}, \hat{W})$ with $\hat{t} > 0$, including the same-table maximizer, defines $\hat{T} = \hat{W}/\hat{t}$ and residual laws satisfying*

$$q_{s,y} = \hat{t} p_{s,y} \hat{T} + (1 - \hat{t}) r_{s,y} \quad \forall s. \quad (8)$$

Moreover, Eq. (7) returns the largest retained mass certified uniformly over the product confidence region.

Indeed, feasibility and coverage imply $q_{s,y}(z) \geq p_{s,y}^\top \hat{W}_{:z}$ coordinatewise. The difference is nonnegative and sums to $1 - \hat{t}$, so normalization constructs $r_{s,y}$. Conversely, robust membership requires exactly these coordinatewise inequalities; maximizing the reference support and minimizing the bridge coordinate yields Eq. (7). Thus the learned singleton transform $\{\hat{T}_y\}$ and contamination $\hat{\eta}_y = 1 - \hat{t}_y$ can be inserted into the certificates below on the same event. If a required bridge source–label stratum is absent, its confidence set is the full simplex, every coordinate lower bound is zero, and Eq. (7) forces $\hat{t} = 0$. For the practitioner, the bridge either supplies a measured residual budget for the target population or stops the release before a channel is deployed.

6 Certification under Pre-Release Shift

We use three names consistently: the *data-certified bridge* tests shift membership, the *transform-exact certificate* enumerates the learned shift geometry, and the *capacity fallback* upper-bounds it when that geometry cannot be enumerated.

Define the arbitrary differential-shift capacity

$$\text{Cap}_G(M) = \frac{1}{G} \max_{a \in [G]^L} \sum_s \max_c v_{M,a,s}(c). \quad (9)$$

This equals $\sup_{r_1, \dots, r_G} A(R, M)$. For $G = 2$, its normalized value is the Dobrushin coefficient, the largest total variation distance between two rows of M .

For a transform polytope with registered extremes $\mathcal{V}_y =$

$\text{ext}(\mathcal{T}_y)$, define the shifted envelope

$$\bar{A}_y^X(M) = \frac{1}{G} \max_{T \in \mathcal{V}_y, a \in [G]^L} \sum_s \left[(1 - \eta_y) \Phi(\hat{p}_{s,y}, \epsilon_{s,y}; T v_{M,a,s}) + \eta_y \max_c v_{M,a,s}(c) \right]. \quad (10)$$

Theorem 3 (Transform-exact structured-shift certificate). *On $\mathcal{E}$, every same-table selected M and every external law in Eq. (3) satisfy $A_y(Q, M) \leq \bar{A}_y^X(M)$. For fixed M , the right-hand side is the exact supremum over the stated confidence sets, transform polytope, retained masses, and arbitrary residual laws.*

For fixed T , retained mass, and attacker assignment, the source confidence sets and residual simplexes separate. Their support values are respectively $\Phi(\hat{p}, \epsilon; T v)$ and $\max_c v(c)$. The latter is no smaller, so the worst retained mass is $1 - \eta_y$. The support objective is convex in T ; its maximum over a polytope occurs at an extreme. These finite maxima commute, proving exactness. Since the statement holds pointwise for every M , it survives adaptive channel selection.

When transform extremes cannot be enumerated, a capacity-fallback corollary is available. Define $\rho_T(M) = \max_c \text{TV}((TM)(c, \cdot), M(c, \cdot))$ and $B_y(M) = \min\{\text{Cap}_G(M), \bar{A}_y(\hat{P}, M) + \rho_{\mathcal{T}_y}(M)\}$. Then

$$A(Q, M) \leq (1 - \eta_y) B_y(M) + \eta_y \text{Cap}_G(M). \quad (11)$$

The exact envelope in Eq. (10) is never larger. When $\eta_y = 0$ and $TM = M$, both reduce to the reference certificate; when $\eta_y = 1$, both reduce to exact distribution-free capacity.

Because the fallback separately upper-bounds every law in the same structured class, both transform-exact source and utility values are pointwise no larger than their fallback values. “Never worse” is therefore an implementation check implied by the theorem; experiments measure how often tightness changes the release decision. Proofs are in the supplement.

For decoder $g : [L] \rightarrow [J]$, let $u_y(c) = \sum_z M(c, z) \mathbf{1}\{g(z) \neq y\}$. The matching exact conditional error certificate is

$$\bar{E}_{s,y}^X(M, g) = \max_{T \in \mathcal{V}_y} \left[(1 - \eta_y) \Phi(\hat{p}_{s,y}, \epsilon_{s,y}; T u_y) + \eta_y \max_c u_y(c) \right]. \quad (12)$$

It is the exact supremum over the same confidence and shift sets. Thus M , g , within-label source distinguishability, and worst-stratum utility can all be selected on one event.

Guarantee at a glance. With probability at least $1 - \delta$ over the registered reference and bridge samples, every released (M, g) meets both contracts for every target law in the learned bridge class. If the bridge has zero retained mass, a required stratum is missing, or no channel satisfies both bounds, MOSAIC abstains.

Unrestricted source-specific shift can be erased only by a fine-token-independent channel, so a bounded residual is a

deployment assumption rather than a hidden technical convenience. Likewise, a missing required source stratum is unestimable rather than evidence of safety; both boundary proofs are in the supplement. A constant-row channel is the $\varepsilon = 0$ endpoint of local differential privacy (Warner 1965).

7 Global Optimization and Abstention

For fixed decoder, support functions, transformed scores, and residual maxima have linear epigraphs. Enforcing every transform extreme and attacker assignment gives one LP in the KL channel entries; enumerating J^L decoders yields the global finite-alphabet optimum. Acceptance requires solver optimality, valid primal residuals, and independent certificate recomputation.

Release protocol. Fix tokenizers, alphabets, thresholds, split roles, and confidence allocation before viewing certification or bridge folds. Construct simultaneous regions, solve Eq. (7), and enumerate decoder LPs subject to every source constraint. Replay each returned certificate, then select the feasible registered tokenizer with minimum certified error under a fixed tie break. Zero retained mass, missing support, no feasible row, or a failed numerical check returns ABSTAIN; otherwise only (M, g) and Z are released.

With $R = \max_y |\mathcal{V}_y|$, the direct formulation is polynomial in K for fixed (G, J, L, R) and exponential only in the released alphabet L . Constraint generation adds the strongest omitted attacker until none violates the contract; the supplement gives the proof and scaling details.

8 Hash-Locked Evaluation

Synthetic confirmation. Before outcomes, we SHA-256 locked the protocol, code, evaluators, seed exclusions, gates, and theory curve. Two source-label populations, two shift regimes, eight rules, and up to five sample sizes use 1,000 independent tables per cell and familywise $\delta = .05$. A separate population evaluator grades every selected channel, and replay scripts reconstruct every decision, risk, interval, and optimizer check. The primary contrasts test unsafe plug-in selection and safe retention against held-out certification, LTT, and deterministic release; every registered cell remains reportable.

Real bridge confirmation. We registered 100 fresh jobs: 20 untouched seeds on each of Waterbirds, Camelyon17-WILDS, CivilComments-WILDS, BiasBios-Clinical, and GaitPDB, spanning vision, medical vision, text, and time series. Each job evaluates 13 frozen feature edits from the official INLP, LEACE, R-LACE, TaCo, and MANCE++ implementations; proxies are forbidden. Construction data alone fit a balanced task score and its four-bin tokenizer. Separate reference observations certify the pre-shift table, while the natural external split is divided within each supported source-label stratum into two-thirds labeled bridge data and an untouched one-third diagnostic fold. Neither diagnostics nor their outcomes enter channel or candidate selection.

Target S and Y labels supply the conditional token laws $q_{s,y}$ used by the bridge and the within-label contract. Task-only retraining serves a different objective: it improves a tar-

get predictor without constructing these source-conditional laws. Where S is sensitive, collection, consent, and permitted audit use are part of the deployment protocol; unsupported strata trigger abstention.

The familywise level is .05 over 13 candidate tables and both reference and bridge regions. The source-advantage contract is .35; worst-stratum utility thresholds are .30, .35, .40, .45, and .49, with .40 primary. We globally optimize $L = 2$, then reoptimize $L = 4$ only for the best covered $L = 2$ candidate. A strict replay accepts no decision tolerance and an exact-rational audit checks every serialized bridge slack and outward risk bound. The reported strict-v2 outputs use a disclosed structural-zero repair, and the archive retains the original and first-replay artifacts. Locked comparators use the same candidates and folds: capacity transfer, a bridge plug-in without intervals, a validation plug-in that ignores the bridge, and unconditional deployment of the best validation plug-in. All datasets, thresholds, abstentions, and missing-support outcomes remain reportable.

Fresh geographic-shift confirmation. Before downloading the target states, we register 60 Folktables jobs (Ding et al. 2021): three binary tasks (income, employment, and public coverage), four natural state shifts from California to Washington, Illinois, New York, and Florida, and five seeds. Binary sex is the audit source and is excluded from every released feature matrix. California supplies eraser-train and reference folds. Within each target state, a seeded partition of complete Public Use Microdata Areas supplies the labeled bridge and untouched diagnostic folds; no person or PUMA crosses that boundary. Every job evaluates the same 13-candidate official frontier at $K \in \{4, 8\}$, five registered utility thresholds, and 100 one-token operational draws per release. We hash-lock all 12 raw-data manifests and processed stores before any outcome is computed.

Bridge validity stress. A separate 12,000-table confirmation varies the bridge sample size from 500 to 5,000 per source-label stratum. One population obeys a common transform; two violate the registered model through either source-specific transforms or contamination above the declared budget. Acceptance requires a finite-sample retained-mass lower bound of at least .80. This study tests whether valid membership gains power with data while the two registered violations remain rejected.

9 Audited Results

The preregistered synthetic gates pass. Figure 2 reports every implementable rule in the primary cells; “capacity fallback” is MOSAIC’s generic capacity certificate. Independent replay recomputes all 64,000 method receipts, 128,000 population risks, decisions, and aggregate intervals with zero mismatch.

The paired safety difference is 42.1 points (95% bootstrap interval [39.0, 45.2]), with 421 plug-in-only violations and no reverse discordance. Across 8,000 capacity-fallback certification tables, no accepted release violates the exact population contract. In the retention cell, capacity-fallback safe deployment exceeds held-out, finite-LTT, and deterministic

rates by 53.8, 53.0, and 56.3 points. No deterministic channel is feasible. These finite-run facts align with the $1 - \delta$ guarantee.

A separately locked 5,000-table refinement evaluates exact shift geometry on the same tables. At $n = 125$, transform-exact certification safely deploys on 53.0% versus 0.3% for fallback; at $n = 250$, the rates are 99.9% and 57.8%. The exact objective is no larger on all 5,000 pairs, as theory requires, and all 10,000 method-cell decisions have zero false acceptances. Full cell tables, threshold sensitivity, amendment history, and audits are in the supplement.

Matched finite-family baselines. A separately locked replay places four rules on the same 1,000 tables in each primary scenario. In the retention cell, continuum MOSAIC certifies 579/1,000 deployments (57.9%, exact 95% interval [54.77, 60.98]), versus 283/1,000 (28.3%, [25.53, 31.20]) for Holm LTT over all 500 fixed channel-decoder pairs. MOSAIC alone deploys on 312 paired tables, LTT alone on 16, and both on 267, a 29.6-point paired difference. The exact McNemar value is 2.28×10^{-72} ; it is reported as a descriptive paired statistic. The confidence-region grid and matched deterministic restricted-encoder adaptation both abstain throughout this cell. All four rules have zero observed false acceptance. We do not label the deterministic row as FARE: official FARE trains a fair decision tree for demographic parity on its own raw-input protocol, whereas this study asks about within-label source inference under a pre-release geographic-shift contract. The row isolates the shared restricted-encoder idea without presenting a non-commensurate end-to-end comparison.

Bridge validity and power. Across a separate 12,000-table locked stress study, a correctly specified common transform is accepted on 0%, 31%, 100%, and 100% of tables as the bridge stratum size rises through 500, 1,000, 2,000, and 5,000. Underdeclared contamination has population retained mass .775 < .80; a source-specific transform has minimum retained mass .50. Both violating populations are rejected on every table at every sample size. Independent replay finds no failure on the joint confidence event and no invalid false acceptance. The study establishes power against both registered bridge violations and shows the acceptance transition as bridge support grows.

Real data-certified bridge. At the primary $\tau_U = .40$ error contract, equivalently a .60 worst-stratum accuracy floor, strict MOSAIC deploys on 20/100 jobs (20.0%, exact 95% interval [12.67, 29.18]), all externally estimable, with 0/20 observed violations (one-sided 95% upper bound 13.91%). The selected official edits comprise six INLP, five LEACE, and nine MANCE++ candidates. Capacity transfer deploys none. The bridge plug-in deploys 47 and violates 7/47 estimable diagnostics (14.9%); validation-only selection deploys 80, including 20 unestimable Camelyon jobs, and violates 18/60 estimable diagnostics (30.0%). Unconditional deployment violates 38/80 estimable jobs (47.5%) and also releases all 20 unestimable jobs. MOSAIC retains 20 safe deployments at every stronger threshold .30–.45 and adds three safe Waterbirds deployments at .49; the supplement enumer-




Figure 2: Hash-locked confirmation with 1,000 independent certification tables per cell. Error bars are exact 95% Clopper–Pearson intervals. (a) At the safety boundary, plug-in continuum selection falsely accepts 42.1% of tables; MOSAIC abstains with no false acceptance. Ignoring shift is worse. (b) In the retention cell, the capacity fallback safely deploys on 56.3%, versus 2.5% for held-out certification, 3.3% for finite LTT, and 0% for deterministic MOSAIC. (c) Deployment follows the preregistered theory curve with 0.20 percentage-point mean absolute error. Exact 95% Clopper–Pearson intervals are shown.

ates every threshold. These untouched diagnostics show the practical effect of each selection rule alongside the finite-sample bridge guarantee.

The primary releases concentrate on BiasBios-Clinical, where the bridge has strong support and certified median retained mass is .797. The other four benchmarks map the operational boundary of the method: missing source support produces a required abstention, while insufficient joint privacy–utility feasibility produces a contract-based abstention. Waterbirds illustrates the difference between an observed diagnostic and a certificate: its bridge plug-in releases all 20 jobs, whereas the strict procedure declines to release because the joint contract is not certified. The 100 jobs are repeated partitions of five benchmark populations, so results are reported by dataset as well as in aggregate.

Concrete released interface. One BiasBios-Clinical seed selects INLP at rank four for the binary clinical profession task, with binary gender used only as the audited source. A fixed task score bins each biography into four fine tokens; MOSAIC then emits one of two persistent stochastic public tokens rather than the edited embedding or the source label. Its certified source-advantage upper bound is .204 and its certified worst-stratum error upper bound is .261, below the registered .35 and .40 contracts. On the untouched diagnostic fold, the corresponding values are .052 and .184. This is the deployed object: a small versioned routing interface with a decoder, not a claim that the underlying representation is universally erased.

What the real ablations remove. The primary rows form a diagnostic ladder rather than unrelated baselines. Capacity transfer keeps simultaneous regions but replaces the learned shift geometry by a worst-case channel-capacity charge; its 0/100 deployments versus MOSAIC’s 20/100 show that the exact bridge is decision-relevant. The bridge plug-in retains target data and the fitted transform but removes con-

fidence regions, gaining 27 deployments at the cost of seven observed violations. Validation-only selection removes the target-membership gate, adding 60 deployments but producing 18 estimable violations and 20 unsupported releases. Unconditional deployment additionally removes contract-based abstention and produces 38 violations. Thus intervals, bridge membership, exact geometry, and abstention each change a measured deployment outcome.

Direct target-table comparator. An audited comparator applies the same simultaneous envelope directly to the labeled target bridge table, without making a bridge transport claim. It deploys 36/100 jobs and records 0/36 diagnostic violations, versus 20/100 and 0/20 for strict MOSAIC. This retention gain disappears once the target law moves inside the learned bridge class but outside the sampled-table region. In this post-hoc stress test, for each of the 36 direct releases, we construct the bridge-admitted law that maximizes its source attacker. The direct rule then violates 16/36 contracts (44.4%, exact 95% interval [27.9, 61.9]); MOSAIC releases the other 20, violates none, and abstains on all 16 failures. Every constructed law is an exact member of its stored bridge class and lies outside the direct confidence region. Median structural residual radius is .279, and median distance beyond the direct region is .368 in ℓ_1 after deterministic resolution of an exact attacker tie. The supplement gives the construction, numerical interface utility, and threshold frontier.

The second row closes the scope check without claiming a failure of direct target-table certification. In the separate 12,000-table study, the two prelocked violations have population retained mass below .80. Their true target laws fall inside the direct target region on 7,983/8,000 invalid tables; MOSAIC’s membership gate abstains on all 8,000. Thus direct-region coverage and bridge membership answer different questions, while the bridge has an explicit rejection

Target-law scope	Direct table	MOSAIC
Bridge-admitted, outside direct region (36 real jobs)	16 violations	20 releases; 0 violations
Direct-region, bridge-invalid (7,983 locked tables)	region contains q	7,983 abstentions

Table 2: Complementary scope cells. The first is the post-hoc real-table stress; the second reuses two prelocked bridge-invalid target laws.

K	Rule	Releases	Diagnostic viol.	Batch viol.
4	MOSAIC	15/60	0/15	0/1500
4	Direct table	47/60	0/47	2/4700
8	MOSAIC	0/60	–	–
8	Direct table	47/60	0/47	0/4700

Table 3: Fresh natural geographic shift across 60 registered ACS jobs (three tasks, four target states, five seeds). Diagnostic violations are among released jobs with complete held-out PUMA support. Batch violations count 100 operational batch replays per primary release, each sampling one public token per held-out person.

path when its declared structure fails. The supplement reports the rowwise construction and the full frozen receipt.

Numerical verification and fresh confirmations. Strict-v2 deterministic replay matches all 100 receipts, while exact-rational checks verify 1,300 bridge certificates and 1,400 outward release bounds. A pre-outcome five-seed BiasBios rerun releases every job without a diagnostic violation. The supplement records the independent ACS confirmation, correction history, and decomposed bounds.

Natural multi-state geographic transfer. Before downloading the four target states, we locked 60 ACS jobs spanning income, employment, and public-coverage tasks; Washington, Illinois, New York, and Florida targets; five seeds; and whole-PUMA holdouts. Every job runs the same 13-candidate official frontier at $K \in \{4, 8\}$. At the primary .40 contract, $K = 4$ MOSAIC releases 15/60 with 0/15 held-out violations and 0/1,500 violating operational batches. The releases span all four targets (FL=4, IL=2, NY=5, WA=4) and two tasks: employment=13 and income=2. The direct table releases 47/60 with 0/47 held-out violations. At $K = 8$, MOSAIC abstains on all 60 jobs while the direct table releases 47/60 with 0/47 held-out violations, exposing the confidence cost of the larger token table. The final column of Table 3 repeats the held-out diagnostic 100 times, sampling one certified public token per person in each replay.

Alphabet sensitivity. Four released tokens improve only five of 100 jobs within the registered 10^{-7} solver criterion, so the real gain comes from certifying shift geometry rather than enlarging the public alphabet. Across 75 synthetic jobs with $K \in \{4, 8, 16, 32, 64\}$ and $G \in \{2, 3, 4\}$, every .40 contract certifies; the largest cell has .237 median utility slack and .360-second median solve time. In the original real ACS $K = 8$ extension, retained mass is .377–.540, every candidate needs a .50-error constant release, and MOSAIC ab-

stains. With a locked increase from 6,000 to 16,000 certification rows per source-label stratum on three employment transfers, $K = 8$ MOSAIC releases Florida and New York with 0/2 held-out and 0/200 operational violations; Illinois abstains. The supplement gives the complete support study.

10 Discussion

Beyond finite candidate testing. LTT and Pareto testing control risk after registering a finite family. MOSAIC certifies the categorical experiment before release: on one covered table, every M and g inherit the same pointwise envelope. The optimizer can then search a continuum without turning internal search points into hypotheses. Tokenizers and erasers are registered statistical objects with their own familywise allocation. The matched 500-pair replay shows the practical result: a structure-aware Holm implementation leaves power on the table when the full channel space is downstream of one confidence event.

Bridge and deployment rule. The bridge measures how much of each target source law is explained by one common transformation of its reference law. Equation (7) ranges over every source-blind $K \times K$ Markov transform and returns the largest jointly supported retained mass t_y ; the residual $1 - t_y$ receives the adversarial capacity charge. More bridge data tightens this fit. The protocol registers source and task strata, tokenizer, target population, confidence allocation, and decision thresholds before optimization. A different target population, source definition, or tokenizer defines a new bridge. This gives a clear distinction from target retraining: retraining can improve a target predictor, while MOSAIC certifies a persistent source-blind token interface.

Operational use. MOSAIC is designed for stable software decision interfaces where a channel, a decoder, and a persistence rule can be versioned together. The runtime emits the token when the contract passes and otherwise returns ABSTAIN. The released interface is compact and task-specific, which makes its complete source-inference experiment enumerable and auditable.

Scope. The probability $1 - \delta$ is over the registered reference and bridge samples. The attacker knows M and may use any rule on one persistent token Z . Additional public interfaces, repeated stochastic draws, or multi-item transcripts require the corresponding joint construction. Source and task labels are audit data for every required stratum; a missing stratum triggers abstention.

11 Conclusion

MOSAIC turns editing into release design: one confidence event supports continuum optimization, while the target bridge certifies shift and forces abstention when evidence is insufficient.

References

- Agarwal, S.; and Deshpande, A. 2024. On the Power of Randomization in Fair Classification and Representation. *arXiv:2406.03142*.
- Angelopoulos, A. N.; Bates, S.; Candes, E. J.; Jordan, M. I.; and Lei, L. 2025. Learn then Test: Calibrating Predictive Algorithms to Achieve Risk Control. *The Annals of Applied Statistics*.
- Angelopoulos, A. N.; Bates, S.; Fisch, A.; Lei, L.; and Schuster, T. 2024. Conformal Risk Control. In *International Conference on Learning Representations*.
- Avitan, M.; Goldberg, Y.; and Elazar, Y. 2026. MANCE: Manifold Aware Concept Erasure. *arXiv:2607.03973*.
- Balunović, M.; Ruoss, A.; and Vechev, M. 2022. Fair Normalizing Flows. In *International Conference on Learning Representations*.
- Bates, S.; Angelopoulos, A.; Lei, L.; Malik, J.; and Jordan, M. 2021. Distribution-Free, Risk-Controlling Prediction Sets. *Journal of the ACM*.
- Belrose, N.; Schneider-Joseph, D.; Ravfogel, S.; Cotterell, R.; Raff, E.; and Biderman, S. 2023. LEACE: Perfect Linear Concept Erasure in Closed Form. *Advances in Neural Information Processing Systems*.
- Ben-David, S.; Lu, T.; Luu, T.; and Pal, D. 2010. Impossibility Theorems for Domain Adaptation. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*.
- Blackwell, D. 1953. Equivalent Comparisons of Experiments. *The Annals of Mathematical Statistics*, 24(2): 265–272.
- Calmon, F. P.; Wei, D.; Vinzamuri, B.; Ramamurthy, K. N.; and Varshney, K. R. 2017. Optimized Pre-Processing for Discrimination Prevention. In *Advances in Neural Information Processing Systems*, volume 30.
- Cauchois, M.; Gupta, S.; Ali, A.; and Duchi, J. C. 2024. Robust Validation: Confident Predictions Even When Distributions Shift. *Journal of the American Statistical Association*.
- Chandrasekaran, G.; Klivans, A. R.; Lee, L. L.; and Stavropoulos, K. 2025. Learning Neural Networks with Distribution Shift: Efficiently Certifiable Guarantees. In *International Conference on Learning Representations*.
- Chowdhury, S. B. R.; Dubey, K. A.; Beirami, A.; Kidambi, R.; Monath, N.; Ahmed, A.; and Chaturvedi, S. 2025. Fundamental Limits of Perfect Concept Erasure. In *International Conference on Artificial Intelligence and Statistics*.
- Ding, F.; Hardt, M.; Miller, J.; and Schmidt, L. 2021. Retiring Adult: New Datasets for Fair Machine Learning. In *Advances in Neural Information Processing Systems Datasets and Benchmarks Track*.
- Elazar, Y.; Ravfogel, S.; Jacovi, A.; and Goldberg, Y. 2021. Amnesic Probing: Behavioral Explanation with Amnesic Counterfactuals. *Transactions of the Association for Computational Linguistics*.
- Huber, P. J. 1964. Robust Estimation of a Location Parameter. *The Annals of Mathematical Statistics*, 35(1): 73–101.
- Jourdan, F.; Bethune, L.; Picard, A.; Risser, L.; and Asher, N. 2023. TaCo: Targeted Concept Erasure Prevents Non-Linear Classifiers From Detecting Protected Attributes. *arXiv:2312.06499*.
- Jovanovic, N.; Balunovic, M.; Dimitrov, D. I.; and Vechev, M. 2023. FARE: Provably Fair Representation Learning with Practical Certificates. In *International Conference on Machine Learning*.
- Klivans, A.; Stavropoulos, K.; and Vasilyan, A. 2024. Testable Learning with Distribution Shift. In *Proceedings of the 37th Conference on Learning Theory*, volume 247 of *Proceedings of Machine Learning Research*, 2887–2943.
- Laufer-Goldshtein, B.; Fisch, A.; Barzilay, R.; and Jaakkola, T. 2023. Efficiently Controlling Multiple Risks with Pareto Testing. In *International Conference on Learning Representations*.
- Le Cam, L. 1964. Sufficiency and Approximate Sufficiency. *The Annals of Mathematical Statistics*, 35(4): 1419–1455.
- Makhdoumi, A.; Salamatian, S.; Fawaz, N.; and Medard, M. 2014. From the Information Bottleneck to the Privacy Funnel. *arXiv:1402.1774*.
- Pimentel, T.; Valvoda, J.; Maudslay, R. H.; Zmigrod, R.; Williams, A.; and Cotterell, R. 2020. Information-Theoretic Probing for Linguistic Structure. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*.
- Ravfogel, S.; Elazar, Y.; Gonen, H.; Twiton, M.; and Goldberg, Y. 2020. Null It Out: Guarding Protected Attributes by Iterative Nullspace Projection. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*.
- Ravfogel, S.; Twiton, M.; Goldberg, Y.; and Cotterell, R. D. 2022. Linear Adversarial Concept Erasure. In *International Conference on Machine Learning*.
- Tibshirani, R. J.; Foygel Barber, R.; Candes, E.; and Ramdas, A. 2019. Conformal Prediction Under Covariate Shift. *Advances in Neural Information Processing Systems*.
- Torgersen, E. 1991. *Comparison of Statistical Experiments*, volume 36 of *Encyclopedia of Mathematics and its Applications*. Cambridge University Press.
- Warner, S. L. 1965. Randomized Response: A Survey Technique for Eliminating Evasive Answer Bias. *Journal of the American Statistical Association*, 60(309): 63–69.
- Weissman, T.; Ordentlich, E.; Seroussi, G.; Verdu, S.; and Weinberger, M. J. 2003. Inequalities for the L1 Deviation of the Empirical Distribution. Technical Report HPL-2003-97R1, Hewlett-Packard Laboratories.