

Laxmi Charitable Trust's
Sheth L.U.J College of Arts & Sir M.V. College of Science and Commerce
Department of Information Technology (Bsc.IT Semester III)
Data Structures Practical

Practical - VI

Roll No. : S033	Name: Rudra Rawal
Class : SYIT	Batch : 1
Date of Assignment : 2026-07-29	Date/Time of Submission : 2026-07-29

PART – A : Thoery

A **Binary Tree** is a non-linear data structure in which each node has at most two children: a **left child** and a **right child**.

Tree Traversal is the process of visiting every node of a binary tree exactly once in a specific order. The three basic traversal methods are:

- **Pre-order Traversal (Root → Left → Right):** Visits the root node first, then the left subtree, and finally the right subtree.
- **In-order Traversal (Left → Root → Right):** Visits the left subtree first, then the root node, and finally the right subtree.
- **Post-order Traversal (Left → Right → Root):** Visits the left subtree first, then the right subtree, and finally the root node.

These traversal techniques are commonly used for searching, displaying, and processing the nodes of a binary tree. They are usually implemented using **recursion**.

PART – B : Question

Tree Traversal: Write a program to:

- a. Implement pre-order,
- b. in-order,
- c. Post-order traversal of a binary tree.

CODE:

```
Practical_6A.py - C:/Users/mvlui/Desktop/SYIT_033/DS/Practical_6A.py (3.14.6)
File Edit Format Run Options Window Help

class Node:
    def __init__(self,item):
        self.left = None
        self.right = None
        self.val = item

def inorder(root):
    if root:
        inorder(root.left)
        print(str(root.val) + "->", end = ' ')
        inorder(root.right)

def postorder(root):
    if root:
        postorder(root.left)
        postorder(root.right)
        print(str(root.val) + "->", end = ' ')

def preorder(root):
    if root:
        print(str(root.val) + "->", end = ' ')
        preorder(root.left)
        preorder(root.right)

root = Node(1)
root.left = Node(2)
root.right = Node(3)
root.left.left = Node(4)
root.left.right = Node(5)

print("InOrder Traversal")
inorder(root)
print("\n\nPostOrder Traversal")
postorder(root)
print("\n\nPreOrder Traversal")
preorder(root)

print("\n\n Rudra_S033")
```

OUTPUT:

```
-----
InOrder Traversal
4-> 2-> 5-> 1-> 3->

PostOrder Traversal
4-> 5-> 2-> 3-> 1->

PreOrder Traversal
1-> 2-> 4-> 5-> 3->

 Rudra_S033
|
```

Curiosity Questions:

1. In a BST, which side (left or right) has **smaller numbers** than the root?
2. If we insert numbers 10, 20, 5 into a BST, which number will be at the root?
3. What will the inorder traversal of a BST give — sorted numbers or random numbers?
4. Where will the **largest number** in a BST always be found?
5. If the root of a BST is 50 and we search for 70, will we go left or right? Why?
6. If a BST has only **one node**, what is its inorder traversal?
7. Can we create a BST from characters like A, B, C instead of numbers?
8. If we insert numbers 5, 10, 15, 20 in order, will the tree be balanced or like a straight line?
9. In a BST, do we check the left child first or the right child first in inorder traversal?
10. If we delete the root of a BST, will the tree disappear?