



Subject :

Software :

Hardware :

Branch :

Semester :

Page No.

Prog No. 5

BLEM STATEMENT

ORITHM &amp; CODE :

Implement distance vector routing algorithm for obtaining routing tables at each node.

The Distance Vector Routing Algorithm is one of the fundamental algorithms for routing in a network, where each node periodically sends its routing table to its neighbours, and each node updates its routing table based on the information it receives.

In this algorithm, each node maintains a routing table that contains the distance (or cost) to every other node in the network. The distance is usually represented in terms of hop count or delay, and the nodes exchange this information with each other to update their own routing tables.

Algorithm Overview:

1. Initialization:

• Every node maintains a routing table where the distance to itself is 0, and the distance to all other nodes is infinity ( $\infty$ ), initially.

INPUT GIVEN

OUTPUT OBTAINED

REMARKS

GRADE :

Signature of Faculty

Date :

Signature of Student

Date :





Subject :		Software :	
		Hardware :	
Branch :	Semester :	Page No.	Prog No.

BLEM STATEMENT

ORITHM & CODE :

2. Distance Vector Exchange:
- Each node sends its routing table to its direct neighbours.
  - When a node receives the routing table from a neighbour, it updates its own table based on the information received.
3. Update Rule:
- If a node A has a direct route to node B with distance  $d_{AB}$ , and node C has a direct route to node B with distance  $d_{CB}$ , node A will update its routes to B as  $d_{AB} + d_{CB}$  if it is smaller than its current value for node B.
4. Convergence:
- The algorithm continues to run until no more changes happen in the routing table. i.e. the system has converged and all nodes have found their best routes to all other nodes.

INPUT GIVEN

OUTPUT OBTAINED

REMARKS

GRADE :

Signature of Faculty

Date :

Signature of Student

Date :





Subject :

Software :

Hardware :

Branch :

Semester :

Page No.

Prog No.

BLEM STATEMENT

GORITHM & CODE :

Pseudocode:

Here's a basic pseudocode outline for the Distance vector Routing Algorithm:

# Initialize the network

nodes = ["A", "B", "C", "D"]

cost = {

"A" : { "A" : 0, "B" : 1, "C" : 4, "D" : float("inf") },

"B" : { "A" : 1, "B" : 0, "C" : 2, "D" : 5 },

"C" : { "A" : 4, "B" : 2, "C" : 0, "D" : 1 },

"D" : { "A" : float("inf"), "B" : 5, "C" : 1, "D" : 0 }

}

# Function to update routing table.

def update\_routing\_table(node, neighbours):

updated = false

for neighbour in neighbours:

# For each neighbour's distance vector

for dest, cost-to-dest in distance\_vectors

[neighbour].items():

INPUT GIVEN

OUTPUT OBTAINED

REMARKS

GRADE :

Signature of Faculty

Date :

Signature of Student

Date :





Subject :

Software :

Hardware :

Branch :

Semester :

Page No.

Prog No.

PROBLEM STATEMENT

ALGORITHM & CODE :

```
new - cost = cost [node] [neighbor] + cost - to - dest
if new - cost < distance - vectors [node] [dest] :
    distance - vectors [node] [dest] = new - cost
    updated = True
return updated

# main distance vector routing process
def distance_vector_routing():
    changed = True
    while changed:
        changed = False
        # for each node, send its routing table to its neighbours.
        for node in nodes:
            neighbors = [neighbor for neighbor in nodes
                          if cost[node].get(neighbor, float("inf")) < float("inf")]
            if update_routing_table(node, neighbors):
                changed = True

# Run the algorithm
distance_vector_routing()

# Print the final routing tables
for node in nodes:
    print(f"Routing table for node {node}: {distance_vectors[node]}
```

INPUT GIVEN

OUTPUT OBTAINED

REMARKS

GRADE :


Signature of Faculty

Date :

Signature of Student

Date :



	Subject :		Software :	
			Hardware :	
Branch :	Semester :	Page No.	Prog No.	
PROBLEM STATEMENT				
ALGORITHM & CODE :	<p><code>[node]}")</code></p> <p><u>Example</u></p> <p>for the given Setup :</p> <ul style="list-style-type: none"> <li>• Node A: Direct connection to B with a cost of 1, C with a cost of 4, and no direct connection to D.</li> <li>• Node B: Direct connection to A with a cost of 1, C with a cost of 2, and D with a cost of 5.</li> <li>• Node C: Direct connection to B with a cost of 2, D with a cost of 1, and A with a cost of 4.</li> <li>• Node D: Only direct connection to C with a cost of 1 and B with a cost of 5.</li> </ul> <p>The algorithm will update the routing tables by exchanging the tables and converging to the shortest paths between all nodes.</p>			
INPUT GIVEN				
OUTPUT OBTAINED				
REMARKS				
GRADE :	Signature of Faculty		Signature of Student	
	Date :		Date :	





Subject :		Software :	
		Hardware :	
Branch :	Semester :	Page No.	Prog No.

PROBLEM STATEMENT

ALGORITHM & CODE :

Example Output

Routing table for node A: { 'A': 0, 'B': 1, 'C': 3, 'D': 8 }  
Routing table for node B: { 'A': 1, 'B': 0, 'C': 2, 'D': 5 }  
Routing table for node C: { 'A': 3, 'B': 2, 'C': 0, 'D': 1 }  
Routing table for node D: { 'A': 8, 'B': 5, 'C': 1, 'D': 0 }

INPUT GIVEN

OUTPUT OBTAINED

REMARKS

GRADE :

Signature of Faculty

Date :

Signature of Student

Date :