
ISE2 - Configuring Dynamic and Static NAT Topology

Task 1:


Network Topology





PING from PC-A to Gateway:

```
PC-A
                                                                        Physical
          Config
                    Desktop
                              Programming
                                           Attributes
  Command Prompt
                                                                              X
  C:\>ping 182.168.1.1
  Pinging 182.168.1.1 with 32 bytes of data:
  Reply from 182.168.1.1: bytes=32 time<1ms TTL=255
  Ping statistics for 182.168.1.1:
  Packets: Sent = 4, Received = 4, Lost = 0 (0% loss), Approximate round trip times in milli-seconds:
      Minimum = Oms, Maximum = Oms, Average = Oms
   C:\>ping 182.31.7.1
```

Task 2 STATIC NAT:







Dynamic NAT:

```
Gateway#clear ip nat translation *
Gateway#clear ip nat statistics
^
% Invalid input detected at '^' marker.
```

Gateway(config) #access-list 1 permit 182.168.1.0 0.0.0.255 Gateway(config) #show ip nat statistics General configition and pool public access 103.185.200.382 103.165.200.384 methods 355.286.385.204
General configition and inside source list 1 pool public access
General configitions
General configitions

```
Gateway#show ip nat translations
Pro Inside global Inside local --- 208.165.200.225 182.168.1.20
                                          Outside local
                                                              Outside global
Gateway#show ip nat statistics
Total translations: 3 (1 static, 2 dynamic, 2 extended)
Outside Interfaces: Serial0/0/1
Inside Interfaces: GigabitEthernet0/1
Hits: 89 Misses: 53
Expired translations: 18
Dynamic mappings:
-- Inside Source
access-list 1 pool public_access refCount 2
pool public_access: netmask 255.255.255.224
       start 208.165.200.242 end 208.165.200.254
       type generic, total addresses 13 , allocated 1 (7\$), misses 0
```

```
Gateway#show ip nat translations
Pro Inside global Inside local icmp 208.165.200.242:13182.168.1.20:13 icmp 208.165.200.242:14182.168.1.20:14
                                                                                                      Outside global
                                                                     182.31.7.1:13
182.31.7.1:14
                                                                                                      182.31.7.1:13
182.31.7.1:14
icmp 208.165.200.242:15182.168.1.20:15
icmp 208.165.200.242:16182.168.1.20:16
                                                                     182.31.7.1:15
182.31.7.1:16
                                                                                                      182.31.7.1:15
182.31.7.1:16
icmp 208.165.200.243:13182.168.1.21:13
icmp 208.165.200.243:14182.168.1.21:14
                                                                     182.31.7.1:13
182.31.7.1:14
                                                                                                      182.31.7.1:13
182.31.7.1:14
icmp 208.165.200.243:15182.168.1.21:15
icmp 208.165.200.243:16182.168.1.21:16
                                                                    182.31.7.1:15
182.31.7.1:16
                                                                                                     182.31.7.1:15
182.31.7.1:16
Gateway#show ip nat statistics
Total translations: 4 (0 static, 4 dynamic, 4 extended)
Outside Interfaces: Serial0/0/1
Inside Interfaces: GigabitEthernet0/1
Hits: 97 Misses: 61
Expired translations: 23
Dynamic mappings:
  -- Inside Source
 access-list 1 pool public_access refCount 4
  pool public_access: netmask 255.255.255.224
start 208.165.200.242 end 208.165.200.254
            type generic, total addresses 13 , allocated 1 (7%), misses 0
 Gateway#
```