# Практика 4

Команда ? - выводит список команд и описание к ним

```
Switch>?
Exec commands:
  connect     Open a terminal connection
  disable     Turn off privileged commands
  disconnect  Disconnect an existing network connec
  enable      Turn on privileged commands
  exit        Exit from the EXEC
  logout      Exit from the EXEC
  ping        Send echo messages
  resume      Resume an active network connection
  show        Show running system information
  ssh         Open a secure shell client connectior
  telnet      Open a telnet connection
  terminal    Set terminal line parameters
  traceroute  Trace route to destination
```

Команда show – показывает результат работы команды

```
Switch>show ?
  arp                Arp table
  cdp                CDP information
  clock              Display the system clock
  crypto             Encryption module
  dtp                DTP information
  etherchannel       EtherChannel information
  flash:             display information about flash: file system
  history            Display the session command history
  interfaces         Interface status and configuration
  ip                 IP information
  lldp               LLDP information
  mac                MAC configuration
  mac-address-table  MAC forwarding table
  mls                Show MultiLayer Switching information
  privilege          Show current privilege level
  sessions           Information about Telnet connections
  ssh                Status of SSH server connections
  tcp                Status of TCP connections
  terminal           Display terminal configuration parameters
  users              Display information about terminal lines
  version            System hardware and software status
  vlan               VTP VLAN status
```

Команда enabled – переход в привилегированный режим

Команда configure terminal – переход в привилегированный режим

```
Switch>enable
Switch#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#
```

Команда enable password * - устанавливаем пароль на терминал.

```
Switch(config)#enable password bocha
```

Команда enable secret * - в отличие от прошлой команды хранит пароль в зашифрованном виде.

```
Switch(config)#enable secret bocha
The enable secret you have chosen is the same as your enable password.
This is not recommended.  Re-enter the enable secret.
```

Команда write memory – сохраняет изменения в конфигурации

```
Switch#write memory
Building configuration...
[OK]
```

Команда reload – перезагрузка устройства

```
Switch#reload
Proceed with reload? [confirm]
C2960 Boot Loader (C2960-HBOOT-M) Version 12.2(25r)FX, RELEASE SOFTWARE (fc4)
Cisco WS-C2960-24TT (RC32300) processor (revision C0) with 21039K bytes of memory.
2960-24TT starting...
Base ethernet MAC Address: 0090.2BE7.3AD2
Xmodem file system is available.
Initializing Flash...
flashfs[0]: 2 files, 0 directories
flashfs[0]: 0 orphaned files, 0 orphaned directories
flashfs[0]: Total bytes: 64016384
flashfs[0]: Bytes used: 4671606
flashfs[0]: Bytes available: 59344778
flashfs[0]: flashfs fsck took 1 seconds.
...done Initializing Flash.

Boot Sector Filesystem (bs:) installed, fsid: 3
Parameter Block Filesystem (pb:) installed, fsid: 4


Loading "flash:/2960-lanbasek9-mz.150-2.SE4.bin"...
################################################################# [OK]
Smart Init is enabled
smart init is sizing iomem
                  TYPE        MEMORY_REQ
                  TOTAL:      0x00000000
Rounded IOMEM up to: 0Mb.
Using 6 percent iomem. [0Mb/512Mb]


                Restricted Rights Legend
Use, duplication, or disclosure by the Government is
subject to restrictions as set forth in subparagraph
(c) of the Commercial Computer Software - Restricted
Rights clause at FAR sec. 52.227-19 and subparagraph
(c) (1) (ii) of the Rights in Technical Data and Computer
Software clause at DFARS sec. 252.227-7013.
        cisco Systems, Inc.
        170 West Tasman Drive
        San Jose, California 95134-1706
Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
```

```
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnguyen
Initializing flashfs...
fsck: Disable shadow buffering due to heap fragmentation.
flashfs[2]: 2 files, 1 directories
flashfs[2]: 0 orphaned files, 0 orphaned directories
flashfs[2]: Total bytes: 32514048
flashfs[2]: Bytes used: 11952128
flashfs[2]: Bytes available: 20561920
flashfs[2]: flashfs fsck took 2 seconds.
flashfs[2]: Initialization complete....done Initializing flashfs.
Checking for Bootloader upgrade..
Boot Loader upgrade not required (Stage 2)
POST: CPU MIC register Tests : Begin
POST: CPU MIC register Tests : End, Status Passed
POST: PortASIC Memory Tests : Begin
POST: PortASIC Memory Tests : End, Status Passed
POST: CPU MIC interface Loopback Tests : Begin
POST: CPU MIC interface Loopback Tests : End, Status Passed
POST: PortASIC RingLoopback Tests : Begin
POST: PortASIC RingLoopback Tests : End, Status Passed
POST: PortASIC CAM Subsystem Tests : Begin
POST: PortASIC CAM Subsystem Tests : End, Status Passed
POST: PortASIC Port Loopback Tests : Begin
POST: PortASIC Port Loopback Tests : End, Status Passed
Waiting for Port download...Complete


This product contains cryptographic features and is subject to United
States and local country laws governing import, export, transfer and
use. Delivery of Cisco cryptographic products does not imply
third-party authority to import, export, distribute or use encryption.
Importers, exporters, distributors and users are responsible for
compliance with U.S. and local country laws. By using this product you
agree to comply with applicable laws and regulations. If you are unable
to comply with U.S. and local laws, return this product immediately.
A summary of U.S. laws governing Cisco cryptographic products may be found at:
http://www.cisco.com/wwl/export/crypto/tool/stqrg.html
If you require further assistance please contact us by sending email to
export@cisco.com.
cisco WS-C2960-24TT-L (PowerPC405) processor (revision B0) with 65536K bytes of memory.
Processor board ID FOC1010X104
Last reset from power-on

Switch>users
Translating "users"...domain server (255.255.255.255)
% Unknown command or computer name, or unable to find computer address
```