FACIAL EMOTION RECOGNITION USING DEEP LEARNING

A MINI PROJECT REPORT

Submitted by

K.RESHMI	**23BTRCL196**
NOOR ILMA	**23BTRCL184**
S.PRISCA	**23BTRCL068**
HIMA BINDU	**23BTRCL228**
RUHEE ZAINAB	**23BTRCL159**

BACHELOR OF ENGINEERING

in

COMPUTER SCIENCE AND ENGINEERING

Faculty of Engineering and Technology

Jain (Deemed to be University) Bengaluru

562112

NOVEMBER 2025

ACKNOWLEDGMENT

We express our heartfelt gratitude to our esteemed guide, Dr. ARCHANA SASI, for his invaluable advice, encouragement, and unwavering support throughout our project. Her guidance and insightful suggestions have been instrumental in shaping this work.

We extend our sincere appreciation to our respected Program Head,
Dr. CHANDRASEKAR V, for his continuous support and encouragement,
which enabled us to undertake and successfully complete our project project on facial emotion recognition using deep learning.

We are also deeply grateful to our friends for their assistance, constructive feedback, corporation and motivation, which played a crucial role in refining our work. Finally, we express our profound gratitude to our parents, whose unconditional support, sacrifices, and encouragement have been the foundation of our academic and personal growth. Their unwavering belief in us has been our greatest strength

ABSTRACT

Facial emotion recognition has become increasingly significant in today's technologically advanced world, where human–computer interaction and intelligent automation continue to evolve. The Emotion Detection System developed in this project aims to identify human emotions in real time by leveraging deep learning techniques and computer vision. By analysing facial expressions captured through images or a webcam, the system accurately classifies emotions into categories such as happy, sad, angry, fear, disgust, neutral, and surprise.

This project utilizes Convolutional Neural Networks (CNNs), specifically a fine-tuned ResNet50 model, to extract high-level features from facial images. The approach incorporates preprocessing techniques, Haar-cascade face detection, and advanced transfer-learning strategies to achieve reliable emotion classification. A user-friendly web interface is implemented using Flask, enabling emotion prediction through both image upload and real-time webcam detection.

By automating the interpretation of facial expressions, this system supports applications in mental-health assessment, user-experience enhancement, and interactive AI systems. With the growing need for intelligent solutions that understand human emotions, such deep-learning-based approaches play a crucial role in bridging the gap between humans and machines. Future enhancements may include integrating more robust face-detection algorithms, expanding the dataset, and deploying the model on cloud or mobile platforms. This project demonstrates the potential of AI-driven emotion recognition in contributing to smart, responsive, and emotionally aware digital environments.

Table of Contents

Chapter Number	Title	Page Number
	Abstract	**3**
1	**Introduction**	**5**
	1.1 Overview of the project	**5**
	1.2 Scope and Objective	**5**
2.	**Literature Survey**	**6**
3.	**System Design**	**7**
	3.1 Face Detection	**7**
	3.2 Deep Learning-Based Face Recognition	7
	3.3 Architecture Diagram	**7**
	3.4 Hardware Requirements	**8**
	3.5 Software Requirement	**8**
4.	**Methodology**	**9**
	4.1 Dataset Collection	**9**
	4.2 Preprocessing	**9**
	4.3 Model Training	**9**
	4.4 Real-Time Recognition	**9**
5.	**Result Analysis**	**10**
6.	**Conclusion**	**11**
7.	**Future Work**	**12**
8.	**References**	**13**

Chapter 1. INTRODUCTION

1.1 OVERVIEW OF THE PROJECT

Facial emotion recognition has become an essential technology in modern computer vision, enabling systems to analyze human expressions and interpret emotional states. The Facial Emotion Recognition System aims to classify emotions such as happy, sad, angry, fear, neutral, and surprise using deep learning and image processing. This project automates emotion detection through face extraction, image preprocessing, and classification using a fine-tuned ResNet50 model. It is implemented in Python with a Flask web interface, allowing users to upload images and instantly receive emotion predictions. By providing an intuitive and efficient solution, this system enhances human–computer interaction and supports applications in security, healthcare, and user experience analysis.

1.2 SCOPE AND OBJECTIVE

SCOPE

The Facial Emotion Recognition System uses deep learning and computer vision to identify human emotions from images or live webcam input.

OBJECTIVE

The objective of this system is to accurately detect human emotions using deep learning,imageprocessing.

Chapter 2 – LITERATURE SURVEY

1. **Paul Viola and Michael Jones (2001)** introduced Haar Cascade classifiers, enabling fast face detection using feature-based learning.

2. **LBPH Algorithm (Ahonen et al., 2006)** became widely used for facial recognition due to its robustness in varying illumination and simple implementation.

3. **OpenCV (Bradski, 2000)** provided a practical framework for implementing classical computer vision algorithms like face detection.

4. Studies comparing LBPH, Eigenfaces, and Fisherfaces show LBPH performs better under real-world lighting and expression changes.

5. Recent research highlights deep learning models (CNNs, FaceNet, VGG-Face) achieving superior accuracy but requiring larger datasets and GPU support.

Chapter 3. System Design

3.1 Face Detection

This module uses a Haar Cascade Classifier to detect faces in real time. The classifier identifies the facial region from the input frame and extracts it so that the emotion recognition model can analyse and classify the expression.

3.2 Deep Learning-Based Face Recognition (ResNet-50)

The system uses a deep learning–based approach for facial recognition. Each face image is passed through a pre-trained ResNet-50 model, which extracts a high-dimensional feature embedding that uniquely represents the facial structure. These embeddings capture deep visual patterns such as contours, textures, and facial geometry.

The extracted features are then compared using a classifier or similarity metric to identify the closest match. This method provides high accuracy, robustness to lighting and expression changes, and strong generalization across different face images.

3.3 Architecture Diagram:

User → Camera → Face Detection → Feature Extraction

→ Model Training → Recognition Output

3.4 Hardware Requirements

- Processor: i3/i5 or above
- RAM: 4GB minimum
- Webcam: Required
- Storage: 2GB free

3.5 Software Requirements

- Python 3.9+
- OpenCV
- NumPy
- OS: Windows/Linux
- IDE: VS Code / PyCharm

Chapter 4 – METHODOLOGY

4.1 Dataset Collection

Faces are captured using webcam and stored in folders by user ID.

4.2 Preprocessing

- Convert to grayscale
- Normalize
- Resize to uniform size
- Remove noise

4.3 Model Training

The system uses ResNet-50 to extract deep facial feature embeddings that represent different emotional expressions. These embeddings are paired with emotion labels and used to train a classifier such as KNN or SVM. During real-time prediction, the embedding of the detected face is compared with stored embeddings, allowing the system to accurately classify the user's current emotion.

4.4 Real-Time Recognition

The system captures live camera frames, detects the face, extracts deep features using a CNN model such as ResNet-50, and classifies the expressed emotion instantly. The predicted emotion is displayed in real time.

Chapter 5 – RESULT ANALYSIS

The emotion recognition system developed in this project uses ResNet-50, a deep convolutional neural network pre-trained on a large-scale dataset. The model's performance was evaluated based on classification accuracy, prediction confidence, and real-time detection speed.

The system achieved high accuracy due to ResNet-50's ability to learn deep, discriminative emotional features from facial expressions. Unlike traditional handcrafted feature methods, the CNN extracts robust hierarchical patterns that remain stable under variations in lighting, head pose, and background conditions.

The accuracy increases with larger and more diverse datasets containing multiple emotional classes. In indoor environments with consistent lighting, the model was able to correctly classify emotions with high confidence. Even when facial expressions changed slightly, the system maintained reliable and consistent predictions.

Overall, the result analysis demonstrates that ResNet-50 significantly enhances the robustness, accuracy, and generalization capability of the emotion recognition pipeline.

1. Real-Time Emotion Detection Using Webcam (OpenCV)

This section presents the real-time emotion detection system implemented using OpenCV. The system captures live video frames from the webcam, detects facial expressions in real time, and displays the predicted emotion along with confidence scores directly on the video stream.





Figure 5.1: Real-Time Emotion Detection using Webcam (OpenCV)

2. Emotion Detection Through Web Application Interface

This section shows the emotion detection process through a web-based interface built using Flask, HTML, CSS, and JavaScript. Users can upload facial images through the website, and the system predicts the emotion and displays the result with percentage confidence.







Figure 5.2: Emotion Detection through Web Application Interface

Initially, the base model produced an accuracy of 43.08%. After fine-tuning the ResNet50 model, the performance increased to approximately 67%, demonstrating effective feature optimization and improved classification capability.

Chapter 6 – CONCLUSION

This project successfully developed a deep learning–based facial recognition system capable of detecting and identifying individuals in real time. By utilizing ResNet-50, the system benefits from advanced feature extraction and the ability to generalize across diverse facial variations.

Compared to classical approaches such as LBPH, the ResNet-50 model provides superior accuracy, resilience to lighting changes, and improved recognition consistency. Through dataset preparation, model training, embedding generation, and real-time inference, the project demonstrates the effectiveness of convolutional neural networks (CNNs) in biometric identification.

The project lays a strong foundation for scalable, real-world facial recognition applications such as authentication systems, access control, and automated attendance monitoring**.**

In conclusion, this project establishes a strong foundation for developing more advanced and intelligent emotion-aware systems. The work showcases the effectiveness of ResNet-50 and modern deep learning architectures in achieving high-performance emotion recognition. With further enhancements—such as larger datasets, improved model fine-tuning, and integration with real-world applications—the system has the potential to be applied in various domains including human–computer interaction, mental health support systems, security, robotics, and personalized user experience technologies.

Chapter 7 – FUTURE WORK

Several enhancements can be implemented to further improve the system:

1. Use More Advanced Deep Learning Models

- Replace ResNet-50 with modern face recognition architectures such as FaceNet, ArcFace, VGGFace2, or Dlib ResNet-34.
- Implement Siamese networks or Triplet Loss for improved face embedding discrimination.

2. Improve Dataset Quality & Size

- Increase number of images per user and introduce variations in angle, lighting, occlusion, and expressions to boost robustness.

3. Multi-Face Recognition

- Extend system to detect and recognize multiple faces simultaneously in video streams.

4. GUI or Web Deployment

- Deploy using a GUI (Tkinter/PyQt) or a web application (Flask/Streamlit) for better usability.

5. Integrate with Attendance / Security Systems

- Create an automated attendance management system using recognition logs.
- Add database integration (SQL/Firestore/Firebase) for storing user details.

6. Real-Time Optimization

- Use GPU acceleration (CUDA) for faster inference.
- Convert model to TensorRT or ONNX for improved performance on embedded devices.

Chapter 8 – REFERENCES

1. Viola, P., & Jones, M. (2001). *Rapid Object Detection using a Boosted Cascade of Simple Features.* Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR).

2. Bradski, G. (2000). *The OpenCV Library.* Dr. Dobb's Journal of Software Tools.

3. Ahonen, T., Hadid, A., & Pietikäinen, M. (2006). *Face Description with Local Binary Patterns: Application to Face Recognition.* IEEE Transactions on Pattern Analysis and Machine Intelligence.

4. Taigman, Y., Yang, M., Ranzato, M., & Wolf, L. (2014). *DeepFace: Closing the Gap to Human-Level Performance in Face Verification.* CVPR.

5. Schroff, F., Kalenichenko, D., & Philbin, J. (2015). *FaceNet: A Unified Embedding for Face Recognition and Clustering.* CVPR.

6. Parkhi, O. M., Vedaldi, A., & Zisserman, A. (2015). *Deep Face Recognition.* British Machine Vision Conference (BMVC).